





STATE OF WEST VIRGINIA DEPARTMENT OF MINES OIL AND GAS DIVISION

Quadrangle		Deyton			
Permit		225-1			

Water Injection

WELL RECORD Oil or Gas Well The Pure Oil Company Used in Drilling Left in Well Casing and P. O. Box 551, Newark, Packers Address_ Tubing L. R. & P. "A" Farm_ Location (waters) Size Well No ... Kind of Packer_ Sherman County LaFollette, 7701 770 The surface of tract is owned in fee by Size of_ 16809 1680 Address 23221 23221 Mineral rights are owned by Depth set. Address December 17, 1920 53/16Drilling commenced_ Perf. top. February 26, 29391 Drilling completed Perf. bottom. Date Shot 3/3/21 Liners Used. Perf. top. With 60 Qts. *Used 39'- 52" OD casing as Perf. bottom. anchor for 2-3/8" OD tubing. Open Flow /10ths Water in Inch _/10ths Merc. in_ Inch Volume__ Cu. Ft. Rock Pressure_ 200 After Shot INCHES bbls., 1st 24 hrs. Ц8 FEET WELL ACIDIZED INCHES INCHES WELL FRACTURED.

RESULT AFTER TREATMENT_

ROCK PRESSURE AFTER TREATMENT

Fresh Water	RE AFTER T	REATMENTFeet		Salt Water	1600, 1960	Feet	
Formation	Color	Hard or Soft	Тор	Bottom	Oil, Gas or Water	Depth	Remarks
Clay Slate Sand			0 10 35 50 75 95 125 150 170 200 225 230 275	10 35 50 75 95 125 150 170 200 225 230 275 300			
Slate Sand Slate Coal Slate Sand			300 375 410 495 499 515	375 h10 495 499 515 550 590			
Slate Sand Slate Sand Slate Slate Lime Sandy Lime Sand	Black		550 590 615 645 760 765 770 810 870	590 615 645 760 765 770 810 870 900		CONTROL OF WELL OF WARRING TO THE WA	1958 1958

Formation	Color	Hard or Soft	Тор	Bottom	Oil, Gas or Water	Depth Found	Remarks
Sand shells Slate Sand shells Slate Sandy shells Grampus Slate Salt Sand Slate Lime Slate	重交 特帶各		980 1020 1080 1120 1150 1208 1310 1148 1640 1660	1020 1080 1120 1150 1280 1310 1448 1640 1660 1675	Salt Water	1600*	
Sand Slate Maxon Sand			1745 1765 1950	1765 1950 2040	Salt Water	19601	Not enough to
Red Rock Slate Red Rock Slate Little Lime Pencil Cave Big Lime			2040 2070 2100 2130 2175 2281 2282	2070 2100 2130 2175 2281 2282 2498			drill with.
Big Injun Slate			21,98 2521	2521 2716			***
Weir Sand Slate Berea Sand			2716 2780	2780 29 3 3 2979	Gas Oil & Gas	2724° 2950° &	Little
			2933	*717	V11 & 080	29591	shot & 200
Slate TOTAL DEPTH	er og en		2979	29 80 29 80		an managaran da kanala da kana	
TOTAL DEPTH A	at see so to be a see see at 7	OUT IN 1951		2982			
Casinghead lo	wered 31 i	n 1951 and a	ll measureme	nts should l	e made from	a point 3º a	bove same.
	Adjust for great and a second	3977					
			in the second	topping 1 in Line (1) and (1) in A Section (1), e			
						\$1,5 ⁵ k]	And the state of t
				,	19360. 1936.	skus regori	
							e in Carlotte Communication
		of geometric to				er da er	e gar
							The second secon
	болимировані ученосці водина до под под под под под под под под под			e et a 15 e 15 e 15 e	Date	September	
				APPROVED		RE OTT COMPAN	Owner
				Ву		nal Signed By J. A ritle) sem	7
					Area S	uperintenden	

	Date September 16	, 1958
APPROVED	THE PURE OIL COMPANY Original Signed By	, Owner
Ву	Guy J. Artile) sea	The same