



JAMES ARCHER

IRENA BATES  
NOW  
WHEELING STEEL CORP.

JOHN McKIM

WHEELING STEEL CORPORATION  
FORMERLY CYRUS FERGUSON  
423 AC.± TRACT.

J. J. WALKER

OHIO RIVER

WHEELING STEEL CORPORATION

CORPORATION LINE

FOLLANSBEE

WELL No. 128  
ELEV = 765.7

Cross in large Stone at base of large tree

- NEW LOCATION
- DRILL DEEPER
- ABANDONMENT

COMPANY WHEELING STEEL CORPORATION  
 ADDRESS GENERAL OFFICE WHEELING, W. VA.  
 FARM WHEELING STEEL CORPORATION FORMERLY CYRUS FERGUSON  
 TRACT ACRES 423± LEASE NO. \_\_\_\_\_  
 WELL (FARM) No. 128 SERIAL No. \_\_\_\_\_  
 ELEVATION (SPIRIT LEVEL) 765.7  
 QUADRANGLE STEBENVILLE  
 COUNTY BROOKE DISTRICT CROSS CREEK  
 ENGINEER GEORGE K. LANG - C.C. SMITH'S SONS  
 ENGINEER'S REGISTRATION No. 1590  
 FILE No. \_\_\_\_\_ DRAWING No. \_\_\_\_\_  
 DATE NOV. 12, 1948 SCALE 1" = 1000'

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION  
CHARLESTON

WELL LOCATION MAP

FILE No. BRO-63

+ DENOTES LOCATION OF WELL ON UNITED STATES TOPOGRAPHIC MAPS. SCALE 1 TO 62,500. LATITUDE AND LONGITUDE LINES BEING REPRESENTED BY BORDER LINES AS SHOWN.  
 --- DENOTES ONE INCH SPACES ON BORDER LINE OF ORIGINAL TRACING.

WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
W E L L R E C O R D

Permit No. Bro 63  
Steubenville Q und.

Company	Wheeling Steel Corporation	CASING & TUBING		
Address	Wheeling, West Virginia			
Farm	Corporation Acres 423	10	85	85
Location	Mahans Run	8 1/2	528	528
Well No.	128 Elev. 765.7	6 5/8	1022	1022
District	Cross Creek County - Brooke			
Surface	Wheeling Steel Corp., Wheeling, W. Va.	Coal at 247'24",		
Mineral	Same	286'48".		
Commenced	10/1/51			
Completed	2/11/52			
Fresh Water	45' Salt water 595'			

Sand & Gravel	Brown	0	38	Slate	Dark	1160	1160
Limestone	White	38	45	Limestone	White	1180	1195
Slate	Dark	45	70	Slate & Shls.	Dark	1195	1220
Rock	Red	70	75	Limestone	White	1220	1260
Slate	Light	75	140	Slate & Shls.	Dark	1260	1290
Sand	Brown	140	190	Shale	Gray	1290	1320
Rock	Red	190	200	Shale	Black	1320	1340
Slate	Dark	200	247	Slate	Black	1340	1346
Coal	Dark	247	249	Sand	Brown	1346	1366
Lime	White	249	260	Slate & Shls.	Dark	1366	1388
Slate	Dark	260	286				
Coal	Dark	286	290	Wellbottomed at 1388'.			
Slate	Dark	290	320	Dry Hole - no oil, no gas.			
Slate	White	320	360	Will be used for intake purposes. (injection)			
Slate	Dark	360	400				
Shale	Dark	400	420	Water	45'		
Slate	Light	420	455	Water	595' Salt Sand		
Sand	Light	455	465	Berea Sand	1348'-1356'		
Slate	Light	485	500				
Slate	Dark	500	520				
Limestone	White	520	535				
Shale	Dark	535	580				
Sand	White	580	645				
Slate	Black	645	660				
Sand	Brown	660	695				
Slate	Dark	695	705				
Limestone	White	705	740				
Sand	White	740	830				
Slate	Dark	830	850				
Limestone	Black	850	880				
Sand	White	880	995				
Slate	Dark	995	1015				
Limestone	Dark	1015	1030				
Slate & Shls.	Dark	1030	1090				
Limestone	Dark	1090	1120				
Shale	Dark	1120	1160				