



New Location ..    
 Drill Deeper .....    
 Abandonment.....

No coal   
 Surface: - Harry S. Wallace, Jr.   
 West Union, West Va.

Company HARRY F. DAVIS   
 Address 14 Edgewood Park, Parkersburg, W.Va   
 Farm Harry S. Wallace, Jr   
 Tract \_\_\_\_\_ Acres 3.0 Lease No. \_\_\_\_\_   
 Well (Farm) No. One Serial No. \_\_\_\_\_   
 Elevation (Spirit Level) 801'   
 Quadrangle West Union - 54 E   
 County Doddridge District West Union   
 Engineer W. Sibert Jr   
 Engineer's Registration No. 1227   
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_   
 Date April, 1960 Scale 1" = 60'

STATE OF WEST VIRGINIA   
 DEPARTMENT OF MINES   
 OIL AND GAS DIVISION   
 CHARLESTON

**WELL LOCATION MAP**   
 FILE NO. DDO-343

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.   
 - Denotes one inch spaces on border line of original tracing.

*plugged 1960?*

*too crowded to plot*



STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION 7

Quadrangle West Union

Permit No. DOD-343

WELL RECORD

Oil or Gas Well DRY  
(KIND)

Company Harry F. Davis  
Address 14 Edgewood Park - Parkersburg, W. Va.  
Farm Harry S. Wallace, Jr. Acres 3.0  
Location (waters) Middle Island Creek  
Well No. 1 Elev. 801'  
District West Union County Doddridge  
The surface of tract is owned in fee by Harry S. Wallace, Jr.  
West Union, W. Va. Address \_\_\_\_\_  
Mineral rights are owned by Same  
Address \_\_\_\_\_  
Drilling commenced April 15, 1960  
Drilling completed May 18, 1960  
Date Shot Fractured From \_\_\_\_\_ To \_\_\_\_\_  
With \_\_\_\_\_  
Open Flow \_\_\_\_\_ /10ths Water in \_\_\_\_\_ Inch  
\_\_\_\_\_ /10ths Merc. in \_\_\_\_\_ Inch  
Volume \_\_\_\_\_ Cu. Ft.  
Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
WELL ACIDIZED \_\_\_\_\_  
WELL FRACTURED \_\_\_\_\_

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13	21'	21'	
10	83'	--	Size of
8 1/4	390'	--	
6 3/4	949'	-0	Depth set
5-3/16 5-1/2	170 1/2'	170 1/2'	
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED 5 1/2" SIZE Approx 190' No. Ft. \_\_\_\_\_ Date \_\_\_\_\_  
COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES

RESULT AFTER TREATMENT no results

ROCK PRESSURE AFTER TREATMENT \_\_\_\_\_

Fresh Water 35' Feet \_\_\_\_\_ Salt Water \_\_\_\_\_ Feet \_\_\_\_\_

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth	Remarks
Surface		Soft	0	2			
Shale		Soft	2	30			
Shells	Red	Hard	30	60			
Shells-Shale	Red	Hard	60	87			
Shale	Gray	Soft	87	95			
Shale	Blk	Soft	95	105			Hole full of water 87'
Shale	Gray	Soft	105	117			
Shale	Red	Soft	117	119			
Lime	White	Hard	119	129			
Shale & Shells		Hard	129	149			
Sand	White	Hard	149	164			
Shale	Red	Soft	164	168			
Lime	White	Hard	168	180			
Shale	Gray	Soft	180	183			
Shale & Shells		Hard	183	195			
Shale	Red	Soft	195	200			
Shale & Shells		Hard	200	215			
Shale	Red	Soft	215	225			
Shale	Gray	Soft	225	235			
Shale	Green	Soft	235	250			
Shale & Shells		Hard	250	261			
Sand	White	Hard	261	281			
Shale & Shells		Hard	281	290			
Shale	Gray	Soft	290	300			
Shale	Red	Soft	300	307			
Shale & Shells		Green	Hard	310			
Shale	Gray	Soft	310	355			
Lime	Black	Hard(Very)	362	376			
Lime	White	V. Hard	376	380	(Over)		

(over)

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Shale & Shell		Hard	380	381			
Shale	Gray	Soft	384	394			
Sh. & Shells	Gray	Hard	394	460			
Lime	White	Hard	460	463	(OASE)		
Sh. & Shells	Gray	Hard	463	485			
Shale	Red	Soft	485	505			
Sh. & Sand	Gray	Hard	505	515			
Sh. & Sand	Brown	Hard	515	520			
Shale	Red	Soft	520	540			
Sh. & Shells	Gray	Hard	540	548			
shale	Red	Soft	568				
Sh. & Shells	Gray	Hard	568	575			
Shale	Red	Soft	575	607			
Lime	White	Hard	609	615			
Shale	Red	Soft	615	621			
Sh. & Shells	Pink	Hard	621	650			
Sh. & Shells	Gray	Hard	650	660			
Shale	Gray	Soft	660	680			
Shale	Red	Soft	680	703			
Sand	Brown	Hard	703	709			
Sh. & Shells	Pink	Hard	709	730			
Sh. & Shells	Gray	Hard	730	750			
Shale	Gray	Soft	750	770			
Shale	Pink	Soft	770	780			
Sh. & Shells	Red	Hard	780	795			
Sand	White	Hard	795	810			
Sh. & Shells	Pink	Hard	810	830			
Sh. & Shells	Gray	Hard	830	842			
Shale	Black	Soft	842	873			
Sand	White	Hard	873	889	-- Little Dunkard		
Shale	White	Soft	889	900			
Sand	White	Hard	900	925	-- Big Dunkard		
Lime-Slate	Gray	Hard	925	985			
Sand-Shale	Black	Hard	985	1010			
Sh. & Shells	Gray	Hard	1010	1021			
Sand	White	Hard	1021	1065			
Sand	Brown	Soft	1065	1080			
Sand	White	Hard	1080	1100			
Sand-Slate	Black	Hard	1100	1145			
Lime	Gray	Hard	1145	1160			
Sand	White	Hard	1160	1276			
Lime	Gray	Hard	1276	1310			
Shells-Sh.	Gray	Hard	1310	1391			
Sand	White	Hard	1391	1412			
Lime	White	Hard	1412	1435			
Lime	Brown	Hard	1435	1453			
Sand-Sh.	Gray	Hard	1453	1475			
Sh. & Shells	Black	Hard	1475	1495			
Shale	Black	Soft	1495	1510			
Lime	Black	Hard	1510	1519			
Lime	Gray	Hard	1519	1560			
MAXON	White	Hard	1560	1580	show of oil @ 1570'		
Lime-Slate	Gray	Hard	1580	1588			
Shale	Gray	Soft	1588	1602			
Lime	Gray	Hard	1602	1634	LITTLE LIME		
Slate-Sh.	Gray	Hard	1634	1640			
Sand	White	Hard	1640	1644	BLUE MONDAY		
Pencil Cave	Br.-Gr.	Hard	1644	1650			
BIG LIME	Gray	Hard	1650	1742			
Lime-Sand	White	Hard	1742	1790	Pay 1752-1754' - 8,000 natural		
BIG INJUN			1790	1820	DRY		
Sand-Shale (SQUAW)			1820		Total Depth		

MEET RECORD

Date....., 19.....

APPROVED

, Owner

By

(Title)

