





*Note for final inspection 3-13-64*

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION 2

Rotary   
Spudder   
Cable Tools   
Storage

Quadrangle Vadis

Permit No. DOD-1085

WELL RECORD

Oil or Gas Well Oil & Gas  
(KIND)

Company Petroleum Promotions, Inc.  
Address Box 105, Weston, West Virginia  
Farm Haught-Hansford Acres 50.08  
Location (waters) Brushy Fork  
Well No. #1 Elev. 1177'  
District New Milton County Doddridge  
The surface of tract is owned in fee by O. C. Haught  
Address Salem, W. Va.  
Mineral rights are owned by Same  
Address \_\_\_\_\_  
Drilling commenced January 20, 1964  
Drilling completed February 10, 1964  
Date Shot \_\_\_\_\_ From \_\_\_\_\_ To \_\_\_\_\_  
With \_\_\_\_\_  
Open Flow /10ths Water in Show Inch \_\_\_\_\_  
/10ths Merc. in Inch \_\_\_\_\_  
Volume No Test Cu. Ft. \_\_\_\_\_  
Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
WELL ACIDIZED \_\_\_\_\_

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
18	16'	16'	
10	223'	Pulled	Size of
8 3/4	1187'	Pulled	
6 3/4			Depth set
5 3/16	2358'	Cemented	
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED 2358' SIZE 5 3/4 No. Ft. 2/10/64 Date  
50 lbs. cement; 10 lbs. "Mud" Benton  
COAL WAS ENCOUNTERED AT None FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES

WELL FRACTURED W/ 20,000 gals. treated water, 24,000# Sand, 200 gals. Acid  
RESULT AFTER TREATMENT 2 MCF Gas, 1000 lbs. Oil  
ROCK PRESSURE AFTER TREATMENT 850PSI 24 Hrs.  
Fresh Water \_\_\_\_\_ Feet \_\_\_\_\_ Salt Water 726' 955' Feet 1495'

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth	Remarks
O Clay			0	4			
Sand			4	10			
Red Rock & Sand			10	84			
Sand			84	105			
Slate & Shells			105	130			
Sand			130	149			
Slate & Shells			149	157			
Sand			157	178			
Red Rock			178	185			
Lime Broken			185	200			
Red Rock & Slate			200	288			
Lime & Slate			288	382			
Slate & Shells			382	405			
Red Rock & Shells			405	608			
Red Rock & Lime			608	620			
Lime, Sandy			620	640			
Red Rock & Slate			640	698			
Red Rock			698	705			
Lime, Sandy			705	715			
Sand			715	757			
Sand & Slate			757	795			Water @ 726' † bailer/hr.
Lime & Slate			795	938			
Sand			938	975			Water @ 955' † bailer/hr.
Slate			975	985			
Red Rock			985	1025			
Lime			1025	1036			
Slate & Shells			1036	1042			
Red Rock & Lime			1042	1087			
Slate & Shells			1087	1130			
Red Rock & Shells			1130	1188			



Formation	Color	Hard or Soft	Top 2	Bottom	Oil, Gas or Water	Depth Found	Remarks
Lime			1188	1190			
Slate & Shells			1190	1255			
Red Rock & Lime			1255	1296			
Slate			1296	1340			
Lime			1340	1379			
Slate & Shells			1379	1446			
Sand			1446	1519			
Slate & Shells			1519	1592	Water @	1495'	5gals./hr/
Sand			1593	1623			
Slate & Shells			1623	1658			
Sand			1658	1851			
Sand & Slate			1851	1968			
Sand			1968	2020			
Slate & Shells			2020	2160			
Sand			2160	218			
Sand & Slate			2182	2209			
Red Rock & Lime			2209	2238			
Lime			2238	2252			
Slate			2252	2262			
Lime			2262	2280			
Lime & Slate			2280	2292			
Slate			2292	2301			
Lime (Big)			2301	2349			
Lime & Sand (Kenner)			2349	2358			
Lime & Sand (Injun)			2358	2458			
Slate			2458	2460			
			TD	2460			

Date 3-8, 1964  
 APPROVED Jerry Marnon, Owner  
 By Supt. (Title)