



New Location   
 Drill Deeper   
 Abandonment

Elev. at Flint = 836'  
 Error in Closure = Less than 1' in 200'

Company Prior Oil Company  
 Address 224 Washington Bud., Belpro. O.  
 Farm L. L. Gaskins  
 Tract \_\_\_\_\_ Acres 72 Lease No. \_\_\_\_\_  
 Well (Farm) No. 000 Serial No. \_\_\_\_\_  
 Elevation (Spirit Level) 817  
 Quadrangle Centerpoint - SC  
 County Doddridge District Grant  
 Engineer W. J. Wildman  
 Engineer's Registration No. 1227  
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_  
 Date Dec. 9, 1964 Scale 1" = 300'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. Dod-1204

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
 - Denotes one inch spaces on border line of original tracing.



STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

Rotary   
Spudder   
Cable Tools   
Storage

Quadrangle CENTERPOINT

WELL RECORD

Permit No. D00-1204

Oil or Gas Well GAS  
(KIND)

Company PRIOR OIL COMPANY  
Address 224 WASHINGTON BLVD., BELPRE, OHIO  
Farm L. L. GASKINS Acres 72  
Location (waters) BIG FLINT  
Well No. ONE Elev. 817  
District GRANT County DODDRIDGE  
The surface of tract is owned in fee by L. L. GASKINS  
Address WEST UNION, W.VA.  
Mineral rights are owned by L. L. GASKINS  
Address WEST UNION, W.VA.  
Drilling commenced 12/14/64  
Drilling completed 1/12/65  
Date Shot \_\_\_\_\_ From \_\_\_\_\_ To \_\_\_\_\_  
With \_\_\_\_\_  
Open Flow \_\_\_\_\_ /10ths Water in \_\_\_\_\_ Inch  
\_\_\_\_\_ /10ths Merc. in \_\_\_\_\_ Inch  
Volume \_\_\_\_\_ Cu. Ft.  
Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
WELL ACIDIZED 250 GAL.  
WELL FRACTURED 30,000 # ROTARY-DRILLED WITH MUD AND CIRCULATING GEL

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer _____
16			
13			
10			Size of _____
8 3/4	21	21	
6 5/8			Depth set _____
5 3/16			
4 1/2	1868	1868	Perf. top <u>1936</u>
2			Perf. bottom <u>1937</u>
Liners Used			Perf. top <u>1954</u>
			Perf. bottom <u>1956</u>

CASING CEMENTED 4 1/2 SIZE 1868 No. Ft. 12/22/64 Date  
100 lbs. cement - down  
COAL WAS ENCOUNTERED AT NO COAL FEET \_\_\_\_\_ INCHES  
FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES  
FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES

RESULT AFTER TREATMENT 2,100 MCF  
ROCK PRESSURE AFTER TREATMENT 510# - 24 HRS.  
Fresh Water NONE RECORDED Feet \_\_\_\_\_ Salt Water NONE RECORDED Feet \_\_\_\_\_

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth	Remarks
Surface			0	25			
Shale & sand			25	207			
Sand, shale & lime			207	430			
Sand & shale			430	615			
Shale & sand			615	1270			
Sand & sandy lime			1270	1540			
Broken sand & lime			1540	1610			
Lime			1610	1960			

