



New Location.....  
 Drill Deeper.....  
 Abandonment.....

Elevation reference :- Well location 137' above Clinton Doak No. 1 - (878')  
 Error in Closure :- Less than 1' in 200'

1.49  
2.50

*M. Stutz*

Company PRIOR OIL COMPANY  
 Address 224 Washington Blvd., Belpre, Ohio.  
 Farm Joel Davis  
 Tract \_\_\_\_\_ Acres 156.5 Lease No. \_\_\_\_\_  
 Well (Farm) No. One Serial No. \_\_\_\_\_  
 Elevation (Spirit Level) 1015  
 Quadrangle Centerpoint - SC  
 County Doddridge District Grant  
 Engineer *M. Stutz*  
 Engineer's Registration No. 1227  
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_  
 Date Feb. 2, 1965 Scale 1" = 660'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

**WELL LOCATION MAP**  
 FILE NO. DOD - 1219

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
 - Denotes one inch spaces on border line of original tracing.



STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

Rotary   
Spudder   
Cable Tools   
Storage

Quadrangle CENTERPOINT

WELL RECORD

Permit No. DOD-1219

Oil or Gas Well GAS  
(KIND)

Company PRIOR OIL COMPANY  
Address 224 WASHINGTON BLVD., BELPRE, OHIO  
Farm JOEL DAVIS Acres 156  
Location (waters) BIG FLINT  
Well No. ONE Elev. 1015'  
District GRANT County DODDRIDGE  
The surface of tract is owned in fee by DENZIL FORD  
Address WEST UNION, W. VA.  
Mineral rights are owned by DENZIL FORD, ET AL  
Address WEST UNION, W. VA.  
Drilling commenced 2/12/65  
Drilling completed 5/30/65  
Date Shot From To  
With  
Open Flow 10ths Water in Inch  
10ths Merc. in Inch  
Volume Cu. Ft.  
Rock Pressure lbs. hrs.  
Oil bbl. 1st 24 hrs.  
WELL ACIDIZED 500 GAL.  
WELL FRACTURED 40,000# - 20/40

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			
10	24'	24'	Size of
8 1/2	751'	751'	
6 3/8			Depth set
5 3/16			
4 1/2	2148'	2148'	Perf. top 2040'
2			Perf. bottom 2100'
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED 4 1/2" SIZE 2148' No. Ft. 2/19/65 Date  
COAL WAS ENCOUNTERED AT 730 FEET INCHES  
FEET INCHES FEET INCHES  
FEET INCHES FEET INCHES

RESULT AFTER TREATMENT 2,711 MCF ROTARY-DRILLED WITH MUD & CIRCULATING GEL  
ROCK PRESSURE AFTER TREATMENT 600#  
Fresh Water NONE RECORDED Feet Salt Water NONE RECORDED Feet

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth	Remarks
Surface			0	667			
Shale			667	730			
Coal			730	738			
Sand			738	820			
Shale, sand & slate			820	1000			
Sand, shale			1000	1127			
Sand, shale			1127	1230			
Sand, shale			1230	1395			
Sand, shale			1395	1475			
Sand, shale			1475	1545			
Sand			1545	1635			
Sand			1635	1685			
Sand			1685	1820			
Sand			1820	1930			
Lime, sand, shale			1930	1972			
Lime, shale, sand			1972	2043			
Sand, shale			2043	2118			
Sand, shale			2118	2150			

