

- New Location
- Drill Deeper
- Abandonment

Source of elev.: Elev. Well No 1 : 1103
 Error in closure: - Less than 1' in 200

Company R. WAYNE CHRISTENSON
 Address 1161 North Ballinger Hy., Flint, Michigan
 Farm Henry A' House Heirs
 Tract _____ Acres 122 Lease No. _____
 Well (Farm) No. Five Serial No. _____
 Elevation (Spirit Level) 1118
 Quadrangle Vadis WC
 County Doddridge District New Milton
 Engineer [Signature]
 Engineer's Registration No. 1227
 File No. _____ Drawing No. _____
 Date June 22, 1965 Scale 1" = 300'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. DOD - 1275

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.



STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION 2

Rotary
Spudder
Cable Tools
Storage

Quadrangle _____

WELL RECORD

Oil or Gas Well Dry Hole
(KIND)

Permit No. DOD-1275

Company R. Wayne Christenson
Address 1161 N. Ballenger--Flint, Mich.
Farm Henry Ahouse Acres 122
Location (waters) Brushy Fork
Well No. Five (5) Elev. 1118'
District New Milton County Doddridge
The surface of tract is owned in fee by O.C. Haught
Salem, West Va. Address _____
Mineral rights are owned by 1/2 O.C. Haught-Salem
Rex Lumpston et al Address New Milton
Drilling co. commenced July 15, 1965
Drilling completed August 16th, 1965
Date Shot None From _____ To _____
With _____
Open Flow 10ths Water in none Inch _____
10ths Merc. in Inch _____
Volume none Cu. Ft. _____
Rock Pressure none lbs. _____ hrs. _____
Oil none bbls., 1st 24 hrs. _____
WELL ACIDIZED no
WELL FRACTURED no


Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			None
16			Kind of Packer _____
13	22'	22'	
10	257'	0	Size of _____
8 1/4	1181'	0	
6 1/2	1585'	0	Depth set _____
5 3/16			
3			Perf. top <u>none</u>
2			Perf. bottom _____
Liners Used	<u>none</u>		Perf. top _____
			Perf. bottom _____

CASING CEMENTED _____ SIZE _____ No. Ft. _____ Date _____

COAL WAS ENCOUNTERED AT _____ FEET _____ INCHES
_____ FEET _____ INCHES _____ FEET _____ INCHES
_____ FEET _____ INCHES _____ FEET _____ INCHES

RESULT AFTER TREATMENT none
ROCK PRESSURE AFTER TREATMENT none
Fresh Water 20' Feet _____ Salt Water _____ Feet _____

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth	Remarks
Mud	brown	soft	0	5			
red rock	red	"	5	20			
sand	white	"	20	40	fresh water		
red-rock	red	"	40	68			
sand	white	"	68	75			
gray slate	gray	"	75	90			
sand	white	"	90	120	fresh water		
slate	gray	"	120	130			
red rock	red	"	130	150			
slate	gray	"	150	191			
red rock	red	"	191	257			
red & shells	"	hard	257	285			
slate-shell	gray	"	285	305			
sand	white	"	305	310			
red rock	red	soft	310	370			
slate	gray	"	370	390			
limey	white	hard	390	410			
red rock	red	soft	410	440			
slate	gray	"	440	455			
lime	white & red	hard	455	510			
sand	"	"	510	555			
slate	gray	soft	555	565			
lime	white	hard	565	585			
slate	gray	soft	585	648			
sand	white	hard	648	685			
slate	brown	soft	685	735			
sand	white	hard	735	750			
slate	gray	soft	750	766			
sandy-slate	"	"	766	775			
red rock	red	"	775	832			



Formation	Color	Hard or Soft	Top 2	Bottom	Oil, Gas or Water	Depth Found	Remarks
sand	white	hard	832	850	salt water		
slate	gray	soft	850	910			
lime	white	hard	910	960			
shale	gray	soft	960	972			
lime	white	hard	972	1012			
sand	"	"	1012	1030			
slate	grey	soft	1030	1038			
red rock	red	"	1038	1050			
slate	grey	"	1050	1055			
lime	white	hard	1055	1076			
sandy-lm	"	"	1076	1086			
sand	"	"	1086	1100			
slate	grey	soft	1100	1110			
lime	white	hard	1110	1120			
sand	"	"	1120	1134			
slate blue-grey		soft	1134	1152			
sand	white	hard	1152	1185			
slate	grey	soft	1185	1200			
lime	white	hard	1200	1221			
slate	grey	soft	1221	1229			
lime	white	hard	1229	1233			
sand	"	"	1233	1295			
slate	grey	soft	1295	1305			
lime	white	hard	1305	1365			
shell&slate gry		"	1365	1404			
lime	white	"	1404	1445			
shell&slate gry		"	1445	1460			
sand	white	"	1460	1585	water at 1525'		
lime	"	"	1585	1601			
shell-slate gry		soft	1601	1656			
sandy-lime wht		hard	1656	1720			
sand	white	"	1720	1808			
slate	grey	soft	1808	1815			
sand	white	hard	1815	1850			
slate	grey	soft	1850	1950			
red rock	red	"	1950	2035			
slate	grey	"	2035	2050			
lime	white	hard	2050	2075	little lime 2050'		
slate	grey	soft	2075	2081			
lime	white	hard	2081	2150	Big Line 2081'		
sand	"	"	2150	2164	Keener sand		
sandyline	"	"	2164	2183			
sand-limey	"	"	2183	2201			
sandyline	"	"	2201	2233			
sandy line	"	"	2233	2251			
shale	grey	soft	2251	2258	T. D.		

All pay sections completely limed out, with no sand development, no show of oil or gas in entire hole.

Date August 15th, 19 65

APPROVED R. WAYNE CHRISTENSON, Owner

By Homer Robinson
Homer Robinson (Title) Field Sup't.

