



DRAWING NO. _____
 SCALE 1"=1000'
 MINIMUM DEPTH OF
 PROVEN STRATA OF
 ELEVATION _____

I, THE UNDERSIGNED, HEREBY CERTIFY THAT
 THIS PLAN IS CORRECT TO THE BEST OF MY
 KNOWLEDGE AND BELIEF AND SHOWS ALL THE
 INFORMATION REQUIRED BY LAW AND THE REGU-
 LATIONS AND ORDINANCES ISSUED BY THE DEPART-
 MENT OF MINES
 DIVISION
 DATE APR 25 1960
 OPERATOR'S WELL NO. 54235/A-26
 API WELL NO. _____
 STATE COUNTY TIERMINT

PLACE SEAL HERE

(A) DETAILS LOCATION OF
 WELL ON UNITED STATES
 TOPOGRAPHIC MAPS
 FORM IV-6
 (8-78)

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION

DATE APR 25 1960
 OPERATOR'S WELL NO. 54235/A-26
 API WELL NO. _____
 STATE 47 COUNTY 017 TIERMINT 2137

WELL TYPE: OIL GAS LIQUID INJECTION WASTE DISPOSAL
 USE: "GAS" PRODUCTION STORAGE DEEP SHALLOW
 LOCATION: ELEVATION 1145' WATERSHED LEFT PR. OF ARROWS CR.
 DISTRICT WEST UNION COUNTY DODD RIVER
 QUADRANGLE Oxford 7 1/2' Holbrook NE
 SURFACE OWNER _____ ACREAGE _____
 OIL & GAS ROYALTY OWNER MAXWELL R LEASE ACREAGE _____
 LEASE NO. _____
 PROPOSED WORK: DRILL CONVERT DRILL DEEPER REDRILL FRACTURE OR
 STIMULATE PLUG OFF OLD FORMATION PERFORATE NEW
 FORMATION OTHER PHYSICAL CHANGE IN WELL (SPECIFY)
F.E.R.C. FILING
 PLUG AND ABANDON CLEAN OUT AND REPLUG
 TARGET FORMATION _____ ESTIMATED DEPTH _____
 WELL OPERATOR CITES SERVICE Co. DESIGNATED AGENT Edna J. Mathews
 ADDRESS P.O. Box 873 ADDRESS P.O. Box 873
CHARLESTON WV CHARLESTON WV

6-6 Straight Fork Bluestone Creek (133)

RECORD OF LEWIS MAXWELL WELL NO. 45,
 WELL WAS DRILLED BY THE COLUMBIA CARBON CO. OF WYLLIAMSPORT, PA.
 ON ARDOLDS CREEK, DOODRIDGE COUNTY, WEST VIRGINIA
 CONTRACTOR F. S. GREATHOUSE OF WESTON, WEST VIRGINIA

DRILLING COMMENCED	FEB. 12/23		FINISHED DRILLING MAR. 27/1925	
RECORD KEPT OF ALL FOR- MATION	TOP AND	BOTTOM AND	THICKNESS	
CONDUCTOR	0	16	16	feet
Soil & Red Rock	0	160	160	" "
Sand white & hard	160	200	40	" "
Slate white & soft	200	225	25	" "
Sand white & hard	225	310	85	" "
Red Rock Soft	310	350	40	" "
Lime white & Hard	350	410	60	" "
Slate white Soft	410	525	115	" "
Sand white & Hard	525	565	40	" "
Red Rock Soft	565	595	30	" "
Sand white & Hard	595	610	15	" "
Slate Black & Soft	610	620	10	" "
Lime white & Hard	620	645	25	" "
Slate white & Soft	645	660	15	" "
Little Dunkard Sand	660	695	30	" "
Slate white Soft	695	740	45	" "
Red Rock Soft	740	779	30	" "
Big Dunkard Sand White				
& Hard	770	810	40	" "
Slate white & Soft	910	845	65	" "
Lime white & Hard	845	1030	185	" "
Gas Sand Hard	1030	1130	100	" "
Slate white & Soft	1130	1135	5	" "
1st Salt Sand	1135	1215	85	" "
Slate white & Soft	1215	1235	20	" "
2nd Salt Sand	1235	x x x x x x x x x x x x x x x x		
OIL & LITTLE WATER	1265	1270	5	feet of pay
OIL	1279	1285	6	" " "
TOTAL DEPTH	1285			

10" CASING PUT IN WELL 686 feet 7" x 13" Casing 34 feet
 8-1/4" CASING PUT IN WELL 953- 11" WITH HOOK WALL PACKER PULLED
 ON 8-1/4" CASING AND PULLED IN TOW 32 JOINTS DOWN PULLED CASING
 OUT AND PUT ON STEEL NIPPLE AND RUN BACK AND SCREWED ON AND
 CLAMPED UP CASING.

DRILLERS ON WELL W. E. FLANIGAN OF WESTON WEST VIRGINIA.
 " " " O. L. PRATT " " " " " "
 TOOL DRESSERS D. R. Beachlar " " " " " "
 " " " HENRY FLESHER " " " " " "

RECORD COPIED FROM ORIGINAL WELL RECORD

By F. S. GREATHOUSE,
 WESTON, WEST VIRGINIA.

017-2137

no E log