



FILE NO. \_\_\_\_\_  
 DRAWING NO. \_\_\_\_\_  
 SCALE 1" = 1320'  
 MINIMUM DEGREE OF ACCURACY \_\_\_\_\_  
 PROVEN SOURCE OF ELEVATION \_\_\_\_\_

I THE UNDERSIGNED, HEREBY CERTIFY THAT THIS PLAT IS CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF AND SHOWS ALL THE INFORMATION REQUIRED BY LAW AND THE REGULATIONS ISSUED AND PRESCRIBED BY THE DEPARTMENT OF MINES.  
 (SIGNED) [Signature]  
 R.P.E. \_\_\_\_\_ L.L.S. 249

PLACE SEAL HERE

(H) DENOTES LOCATION OF WELL ON UNITED STATES TOPOGRAPHIC MAPS  
 FORM IV-6 (8-78)



DATE MAR 26, 1980  
 OPERATOR'S WELL NO. GW 6 (C-3)  
 API WELL NO. \_\_\_\_\_  
47 - 017 - 2150  
 STATE COUNTY PERMIT

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION

WELL TYPE: OIL \_\_\_ GAS X LIQUID INJECTION \_\_\_ WASTE DISPOSAL \_\_\_  
 (IF "GAS") PRODUCTION \_\_\_ STORAGE \_\_\_ DEEP \_\_\_ SHALLOW X  
 LOCATION: ELEVATION 860' WATER SHED MEATHOUSE FORK  
 DISTRICT NEW MILTON COUNTY DODDRIDGE  
 QUADRANGLE SMITHBURG 7 1/2 Centerpoint SW  
 SURFACE OWNER \_\_\_\_\_ ACREAGE \_\_\_\_\_  
 OIL & GAS ROYALTY OWNER MAXWELL 'C' LEASE ACREAGE \_\_\_\_\_  
 LEASE NO. \_\_\_\_\_  
 PROPOSED WORK: DRILL \_\_\_ CONVERT \_\_\_ DRILL DEEPER \_\_\_ REDRILL \_\_\_ FRACTURE OR STIMULATE \_\_\_ PLUG OFF OLD FORMATION \_\_\_ PERFORATE NEW FORMATION \_\_\_ OTHER PHYSICAL CHANGE IN WELL (SPECIFY) \_\_\_\_\_  
F.E.R.C. FILING  
 PLUG AND ABANDON \_\_\_ CLEAN OUT AND REPLUG \_\_\_  
 TARGET FORMATION \_\_\_\_\_ ESTIMATED DEPTH \_\_\_\_\_  
 WELL OPERATOR CITIES SERVICE Co. DESIGNATED AGENT SAM J. MATTHEWS (99)  
 ADDRESS PO BX 873 ADDRESS PO BX 873  
CHARLESTON WV 25373 CHARLESTON WV 2532

*CB*  
CONSUMERS CARBON COMPANY

RECORD OF LEWIS HAINWELL WELL NO. 5.

*revised C-3*

Contractor P. E. Gaffney  
 Commenced August 1, 1905  
 Completed September 7, 1905  
 Total Depth 2265 ft.  
 Producing Gas from

<u>FORMATION</u>	<u>TOP</u>	<u>BOTTOM</u>
Conductor	10	
Water	60	
10" casing	160	
First Coal	210	
Water	335	
Coal 5 ft.	537	542
Gay Run Sand	740	
8 1/2" casing	780	
Coal	900	
Salt Sand	1080	1110
Little Lime	1425	
Manon Sand	1445	
Big Lime	1457	1437? 1457
6-5/8" casing	1475	
Big Injun Sand	2560	
Gas	1530	
Bottom Sand	1645	
Sandy Sand	1685	1670
Hard Sand Little Oil	1735	1820
Top Gordon Strat	2217	
Gas	2222	
Bottom Gordon Stray	2232	
Gordon Sand	2259	2245
<u>Total Depth</u>	<u>2265</u>	

Tubed with 3 1/2" Taping

Packer set 454 ft. from bottom in Hard Sand.  
 B. E. Packer on 6-5/8" casing.  
 8 1/2" and 10" casing Palled.

017-2150