

State of West Virginia Division of Environmental Protection Section of Oil and Gas

Reviewed.

Well Operators Report of Well Work

Farm name:

Carroll #2

Operator Well #:

Carroll #2

Location:

Elevation: 1,054'

Quadrangle:

West Union 7.5'

West Union

County

Doddridge

District:

Latitude Longitude 14,610 feet south of feet west of 2,550

39 Deg. 20 Min. 00 Sec. 80 Deg. 45 Min. 00 Sec.

Company:

Alpha Gas Corp.

P.O. Box 68

Reynoldsville WV 26422

| Agent: | John Spiker | Casing | Used in Drilling | Left in Well | Cement Fill up |
|--|----------------------|--------|------------------|-----------------|-------------------|
| Inspector: Permit Issued: | nit Issued: 09-10-01 | 11 3/4 | | | |
| Well Work Commenced: 05-11-02 Well Work Completed: 05-23-02 Verbal Plugging Permission granted on: | | 8 5/8 | 1032 | 1032 | 245 sks |
| | | 4 1/2 | 2815 | 2762 | 265 sks |

Permission gra Rotary X Cable_ Total Depth (ft) 2815' Fresh water depth (ft) N/A Salt water depth (ft) N/A

Is coal being mined in are (Y/N) N

Coal depths (ft) N/A

RECEIVED Office of Oil & Gas Permitting

JUN 1 2 2002

W Department of

OPEN FLOW DATA

Big Injun Producing formation 411 mcf/d Gas: Initial open flow 500 mcf/d Pay zone depths (ft) Initial open flow Final open flow

Environmental Protection 1910-1988 bbls/day bbls/day

Final open flow Time of open flow between initial and final tests

Static rock pressure

340# psig (surface pressure) after

48 Hours Hours 48

2634-2640 Pay zone depths (ft) Other producing formation Gordon Initial open flow bbls/day Oil mcf/day Gas: Initial open flow bblss/day Final open flow * mcf/day Final open flow 48 Hours Time of open flow between initial and final tests Hours psig (surface pressure) after 48

Oil:

Static rock pressure * = commingled zones

For: Alpha Gas Corporation,

Date: 05-30-02

JUN 1 4 200

Dooo 4639

Carroll #2 05-27-02

Stimulation

| Stage #1 | perfs | sand | avg rate | isip |
|----------|-----------|---------|----------|-------|
| Gordon | 2768-2774 | 200 sks | 24 bpm | 2300# |
| Stage #2 | 1910-1984 | 500 sks | 30 bpm | 1900# |

Drillers Log

| Fill | 0 | 15 |
|-------|------|------|
| Sh | 15 | 135 |
| Sđ | 135 | 145 |
| Sd/Sh | 145 | 1200 |
| Sd · | 1200 | 1215 |
| Sh | 1215 | 1730 |
| Sd | 1730 | 1765 |
| Sh | 1765 | 1800 |
| Lime | 1800 | 1815 |
| Sh | 1815 | 1850 |
| BL | 1850 | 1910 |
| Sd | 1910 | 2040 |
| Sh | 2040 | 2620 |
| Sd | 2620 | 2645 |
| Sh: | 2646 | 2815 |
| Td | 2815 | |
| | | |

Electric Log Tops

| 1851 |
|------|
| 1908 |
| 1930 |
| 2399 |
| 2620 |
| |