

WR-35
Rev (9-11)

State of West Virginia
Department of Environmental Protection
Office of Oil and Gas
Well Operator's Report of Well Work

DATE: 1/18/2013
API #: 47-017-06085

Farm name: Powell, Dennis H. and Melle Operator Well No.: Leatherman Unk 2H

LOCATION: Elevation: 881' Quadrangle: Smithburg 7.5'

District: Grant County: Doddridge
Latitude: 6,885 Feet South of 39 Deg. 17 Min. 30 Sec.
Longitude 5,665 Feet West of 80 Deg. 40 Min. 00 Sec.

Company: Antero Resources Appalachian Corp

Address:	Casing & Tubing	Used in drilling	Left in well	Cement fill up Cu. Ft.
1625 17th Street Denver, CO 80202	20" 94#	40'	40'	38 Cu. Ft. Class A
Agent: CT Corporation System	13-3/8" 48#	380'	380'	528 Cu. Ft. Class A
Inspector: Sam Ward	9-5/8" 36#	2707'	2707'	1514 Cu. Ft. Class A
Date Permit Issued: 5/22/2012	5-1/2" 20#	14446'	14446'	3395 Cu. Ft. Class M
Date Well Work Commenced: 7/29/2012				
Date Well Work Completed: 12/18/2012	2-3/8" 4.7#	6630'		
Verbal Plugging: N/A				
Date Permission granted on: N/A				
Rotary <input checked="" type="checkbox"/> Cable <input type="checkbox"/> Rig <input type="checkbox"/>				
Total Vertical Depth (ft): 6,643' TVD				
Total Measured Depth (ft): 14,446' MD				
Fresh Water Depth (ft.): 103'				
Salt Water Depth (ft.): None available				
Is coal being mined in area (N/Y)? N				
Coal Depths (ft.): 154', 236', 273'				
Void(s) encountered (N/Y) Depth(s) N, N/A				

OPEN FLOW DATA (If more than two producing formations please include additional data on separate sheet)

Producing formation Marcellus Pay zone depth (ft) 6,545' TVD (Top)

Gas: Initial open flow ----- MCF/d Oil: Initial open flow N/A Bbl/d

Final open flow 5,821 MCF/d Final open flow N/A Bbl/d

Time of open flow between initial and final tests N/A Hours

Static rock Pressure 3550 psig (surface pressure) after ----- Hours

Second producing formation Pay zone depth (ft)

Gas: Initial open flow MCF/d Oil: Initial open flow Bbl/d

Final open flow MCF/d Final open flow Bbl/d

Time of open flow between initial and final tests Hours

Static rock Pressure psig (surface pressure) after Hours

RECEIVED

FEB 21 2013

WV GEOLOGICAL SURVEY
MORGANTOWN, WV

I certify under penalty of law that I have personally examined and am familiar with the information submitted on this document and all the attachments and that, based on my inquiry of those individuals immediately responsible for obtaining the information I believe that the information is true, accurate, and complete.

Lisa Babinelli
Signature

2/19/13
Date

Were core samples taken? Yes _____ No **X**

Were cuttings caught during drilling? Yes **X** No _____

Were Electrical, Mechanical or Geophysical logs recorded on this well? If yes, please list **Yes- CBL**

This is a subsequent well. Antero only runs wireline logs on the first well on a multi-well pad (Neely Unit 1H AP#47-017-06066). Please reference the wireline logs submitted with Form WR-35 for Neely Unit 1H.

NOTE: IN THE AREA BELOW PUT THE FOLLOWING: 1). DETAILS OF PERFORATED INTERVALS, FRACTURING OR STIMULATING, PHYSICAL CHANGE, ETC. 2). THE WELL LOG WHICH IS A SYSTEMATIC DETAILED GEOLOGICAL RECORD OF THE TOPS AND BOTTOMS OF ALL FORMATIONS, INCLUDING COAL ENCOUNTERED BY THE WELLBORE FROM SURFACE TO TOTAL DEPTH.

Perforated Intervals, Fracturing, or Stimulating:

Perforations: 7,135' - 14,377' MD (1452 holes)

Frac'd w/ 11,000 gals 15% HCL Acid, 150,553 bbls Slick Water carrying 843,928# 100 mesh, 3,000,406# 40/70 and 1,861,910# 20/40 sand.

Plug Back Details Including Plug Type and Depth(s): **N/A**

Formations Encountered: <u>Surface:</u>	Top Depth	/	Bottom Depth
Big Lime est.	1,571'		2,321'
Fifty Foot Sandstone est.	2,322'		4,174'
Bradford est.	4,175'		4,640'
Benson est.	4,641'		4,897'
Alexander est.	4,898'		5,114'
Elk est.	5,115'		5,664'
Rhinestreet est.	5,665'		6,045'
Sycamore est.	6,046'		6,114'
Sonyea est.	6,115'		6,257'
Middlesex est.	6,258'		6,315'
West River est.	6,316'		6,359'
Genundewa est.	6,360'		6,431'
Burket	6,432'		6,460'
Tully	6,461'		6,525'
Hamilton	6,526'		6,544'
Marcellus	6,545'		6,643' TVD

RECEIVED

FEB 21 2013

WV GEOLOGICAL SURVEY
MORGANTOWN, WV

Hydraulic Fracturing Fluid Product Component Information Disclosure

Fracture Date:	12/13/2012
State:	West Virginia
County:	Doddridge
API Number:	47-017-06085
Operator Name:	Antero Resources
Well Name and Number:	Leatherman Unit 2H
Longitude:	-80.6908639
Latitude:	39.2761139
Long/Lat Projection:	NAD27
Production Type:	Gas
True Vertical Depth (TVD):	6,643
Total Water Volume (gal)*:	5,733,042

RECEIVED

FEB 21 2013

WV GEOLOGICAL SURVEY
MORGANTOWN, WV

Hydraulic Fracturing Fluid Composition:

Trade Name	Supplier	Purpose	Ingredients	Chemical Abstract Service Number (CAS #)	Maximum Ingredient Concentration in Additive (% by mass)**	Maximum Ingredient Concentration in HF Fluid (% by mass)**	Comments
Freshwater	Antero Resources		Water	7732-18-5	100.00%	92.12936%	
Hydrochloric Acid 10-15%	Reagent	Acid	Hydrochloric Acid	7647-01-0	15.00%	0.03090%	
100 Mesh	US Silica	Proppant	Sand	14808-60-7	100.00%	1.68401%	
40/70 White	US Silica	Proppant	Sand	14808-60-7	100.00%	5.98454%	
20/40 White	US Silica	Proppant	Sand	14808-60-7	100.00%		
Sodium Persulfate	Chemplex	Breaker	Sodium Persulfate	7775-27-1	100.00%	0.00143%	
Ferriplex 66	Chemplex	Iron Control	Acetic Acid	64-19-7	50.00%	0.00021%	
			Citric Acid	77-92-9	30.00%	0.00013%	
			Water	7732-18-5	35.00%	0.00015%	
Plexbreak 145	Chemplex	Non-emulsifier	Cocamide Diethanolamine Salt	68603-42-9	10.00%	0.00007%	
			Diethanolamine	111-42-2	5.00%	0.00004%	
			Ethylene Glycol Monobutyl Ether	111-76-2	15.00%	0.00011%	
			Methyl Alcohol	67-56-1	15.00%	0.00011%	
			Water	732-18-5	66.00%	0.00047%	
Plexhib 256	Chemplex	Corrosion Inhibitor	Alcohol Ethoxylate Surfactants	Trade Secret	30.00%	0.00019%	
			Methyl Alcohol	67-56-1	70.00%	0.00045%	
			n-olefins	Trade Secret	10.00%	0.00006%	
			Propargyl Alcohol	107-19-7	8.00%	0.00005%	
			thiourea-formaldehyde copolymer	68527-49-1	30.00%	0.00019%	
Plexaid 673	Chemplex	Scale Inhibitor	Methyl Alcohol	67-56-1	25.00%	0.00395%	
			Sodium Salt of Phosphonodimethylated Diamine	Trade Secret	5.00%	0.00079%	
			Water	7732-18-5	85.00%	0.01343%	
Plexcide 15G	Chemplex	Biocide	Water	7732-18-5	90.00%	0.02433%	
			Glutaraldehyde	111-30-8	14.00%	0.00378%	
			Didecyl Dimethyl Ammonium Chloride	7173-51-5	3.00%	0.00081%	

			Alkyl Dimethyl Benzyl Ammonium Chloride	68424-85-1	3.00%	0.00081%
			Ethanol	64-17-5	3.00%	0.00081%
Plexslick 921 E	Chemplex	Friction Reducer	Alcohol Ethoxylate Surfactants	Trade Secret	8.00%	0.00477%
			Hydrotreated Petroleum Distillate	64742-47-8	30.00%	0.01789%
			Polyacrylamide-co-acrylic acid	6/9/9003	32.00%	0.01908%
			Water	7732-18-5	35.00%	0.02087%
LGR-01	Magnablend	Guar Gel	Solvent naphtha, heavy aliphatic	64742-96-7	55.00%	0.05825%
			Guar Powder	9000-30-0	45.00%	0.04766%
			Organophilic clay	mixture of 68953-58-2, 68911-87-5, 14808-60-7	3.00%	0.00318%
			Sorbitan sesquiolate	9007-43-0	4.00%	0.00424%
			Ethoxylated Alcohol	78330-21-9	2.00%	0.00212%

* Total Water Volume sources may include fresh water, produced water, and/or recycled water

** Information is based on the maximum potential for concentration and thus the total may be over 100%

Ingredient information for chemicals subject to 29 CFR 1910.1200(i) and Appendix D are obtained from suppliers Material Safety Data Sheets (MSDS)

RECEIVED

FEB 21 2013

WV GEOLOGICAL SURVEY
MORGANTOWN, WV