

Latitude 39° 17' 30"

39° 17' 30"

7.5'
+

Longitude

Topo Location

7.5' Loc. 1.05S 15' Loc. 3.93S
 0.12W (calc.) 2.35W

Company C-1259

Farm E. H. Dotson

15' Quad West Union SC
(sec.)

7.5' Quad Pennsboro

District Central

WELL LOCATION PLAT

County 017 Permit 30132

Central District, Doddridge County, W. Va.
 Hope Cons. & Ref. Co., 445 W. Main St., Clarksburg, W. Va.
 On 40 acres, surface and mineral rights owned by J. L. Young,
 Greenwood, W. Va.
 Elevation, 875' L.
 6-5/8" casing, 1780'; 2" tubing, 1930'.
 Coal was encountered at 535'; thickness unknown.
 Abandonment reported to Dept. of Mines Sept. 11, 1935.
 Well was shot at 1878'.
 Salt water at 1345'.
 Oil well. Exhausted.

	Top.	Bottom.
Pittsburgh Coal	535	
Second Cow Run Sand	1000	- 1015
First Salt Sand (water, 1345')	1338	- 1360
Second Salt Sand	1410	- 1535
Maxton Sand	1675	- 1705
Little Lime	1710	- 1732
Pencil Cave	1732	- 1775
Big Lime	1775	- 1852
Big Injun Sand (oil, 1878')	1852	- 1926
Total depth		1930

COMPLETION DATA SHEET
NO 2

FORMATION RECORD

Well No 1889 Name J. L. Young

Name	Order	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
Pittsburgh Coal				836	7	7		
Second Coe Sand				1000	1015	15'		
First Salt Sand				1336	1360	22'		
Second Salt Sand		Water	1345	1410	1535	125'		
Sharon Sand				1675	1705	30'		
Little Limestone				1710	1738	28'		
Pencil Core				1738	1775	45'		
Big Limestone				1775	1862	77'		
Big Injan Sand			Oil	1862	1926	74'	1930	

Well was not shot at _____ feet; well was shot at 1978 feet.

Well was fresh water at _____ feet; fresh water at 1945 feet.

Well was producing _____ bbls. _____ exhausted.

September 11, 1935

Approved Hope Construction & Refining Company
Owner By

Hope Construction & Refining Co
J. L. Young



Robt Smith Mrs.

Set-132-A

- Location
- Oil Well
- ⊗ Gas Well
- ⊙ Artesian
- ⊖ Artesian
- ⊕ Dry Hole

Field Book No 600.P17
Scale 1" = 400'
Aug. 7th 1935

ENGINEERS CERTIFICATE

I, the undersigned, hereby certify that this map is correct and shows all the information to the best of my knowledge and belief, required by the laws of the State of Ohio.

OHIO AND GAS DIVISION

PRELIMINARY DATA SHEET NO. 1

File No. 132-A Well No. 1890
 Mine Construction & Refining Company of 645 West Main St.
Clarksville, W. Va. on the J. L. Young Farm
 containing 40 acres, located
 District in Doddridge County, West Virginia

The surface of the above tract is owned in fee by J. L. Young
 of Greenwood, W. Va. address, and the mineral rights are owned by
J. L. Young of Greenwood, W. Va.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit
 No. --- issued by the West Virginia Department of Mines, Oil and Gas Division

Elevation of surface at top of well 975 feet
 The number of feet of the different sized casings used in the well:

Size	Material	Length (feet)	Weight (lbs)	Notes
1 7/8"	6-8/10"	1800	5"	used as...
1 1/2"	6-8/10"	---	---	---
1 1/4"	6-8/10"	---	---	---
1 1/8"	6-8/10"	---	---	---
1"	6-8/10"	---	---	---
3/4"	6-8/10"	---	---	---

Coal was encountered at 555 feet, thickness 14 inches, and at
565 feet; thickness 14 inches; and at
 Layers were used as follows: (Give details)
 Date September 11, 1928.
 Assessed By: E. S. Construction & Refining Co.

OHIO AND GAS DIVISION

No coal operations in this section. Mine Construction & Refining Company
 Clarksville, W. Va.
 October 10th, 1928
 Well and Location
 District Doddridge
 County Doddridge
 Well No. 1890
 Name J. L. Young

AFFIDAVIT

STATE OF WEST VIRGINIA,
 County of Doddridge ss:
Franklin S. Williams and Albert Griffith
 being first duly sworn according to law depose and say that they are experienced in the work of plugging
 and filling of oil and gas wells and were employed by Mine Construction & Refining Co., well operator,
 and participated in the work of plugging and filling the above well, that said work was commenced on the
10th day of September, 1928, and that the well was plugged and filled in
 the following manner:

Manner in which well was plugged:
 Drilled to tubing and filled with clay to 1800' above 6 5/8" lead plug
 at 1800' removed 2000' 6 5/8" casing leaving 607 ft in hole bridged
 at 1800' filled with clay to 1800' filled with cement from 1800' to
 2000' removed bridge at 565' below Pittsburgh coal filled with
 cement from 565' to 515' 20' ft above 2 1/8" coal seam. Filled with clay
 from 515' to surface.

Manner in which well was plugged:
 Cemented from 565' to 20' below 2 1/8" coal to 515' 20' ft above
 2 1/8" coal.

Description of monument:
 Will erect concrete monument as soon as rig is torn down.

and that the work of plugging and filling said well was completed on the 10th day of September,
 1928.

Witness my hand and seal of office at Clarksville, W. Va.
Franklin S. Williams
Albert Griffith

