

PEARCY-SPERRY NO. 2 WELL.

70192

Greenbrier District, Doddridge County, W. Va.
By.....

J. B. Trainer, Contractor.

Drilling commenced Aug. 3, 1914; completed Oct. 16, 1914.

13" casing, 188'; 10", 1215' (pulled); 8 1/2", 2169'; 3" tubing, 2932' (pulled); 1 1/2" tubing, 2932'.

Packer set by J. B. Trainer.

Gas, 15/10 Water through 8 1/2" opening at 2237'.

Gas in Thirty-foot Sand about one million feet at 2791'.

Top of packer, 2190'; bottom of packer, 2194'.

Bottom of perforation on 106'.

Rock pressure, 560 lbs.

Minute pressure: 1 min., 105 lbs.; 2 min., 165 lbs.; 3 min., 205 lbs.; 4 min., 235 lbs.; 5 min., 255 lbs.; 6 min., 280 lbs.; 7 min., 295 lbs.; 8 min., 303 lbs.; 9 min., 310 lbs.; 10 min., 320 lbs.; 15 min., 360 lbs.; 30 min., 390 lbs.; 60 min., 410 lbs.

Second drilling, packer set by C. E. Doty, at 2189'.

Third drilling June 1916.

Sept. 10, 1918, tubed with 1 1/2" tubing. 2" x 8 1/2" O. W. S. hook wall packer set at 2226'. Top of perforation, 2895'.

Minute pressure: 1 min., 27 lbs.; 2 min., 35 lbs.; 3 min., 40 lbs.; 4 min., 45 lbs.; 5 min., 50 lbs.; 15 min., 75 lbs.; 20 min., 80 lbs.

Pearcy lease and the 4 wells sold to M. G. Sperry May 20, 1946.

Record in Eastern Petroleum Co. Well Record book of Clifton Oil & Gas Co.

	Top.	Bottom.
Conductor	0	10
(8 bailers water at 150')		
Native coal	230	235
Coal	485	487
Pittsburgh Coal	795	800
Little Dunkard Sand	1155	1200
Big Dunkard Sand	1250	1280
Gas Sand	1480	1520
First Salt Sand	1570	1590
Second Salt Sand	1675	1725
3rd Salt Sand	1750	1940
Little Lime	2134	2149
Pencil Cave	2149	2163
Big Lime	2163	2222
Big Injun Sand (gas, 2237'; 15/10 W. in 8 1/2" casing) (reduced hole to 6 1/2" at 2277')	2222	2318
Squaw Sand	2350	2375
Gantz Sand	2450	2500
Fifty-foot Sand	2575	2600
Thirty-foot Sand (gas at 2791')	2780	2815
Gordon Stray Sand	2840	2850
Gordon Sand	2860	2871
Fourth Sand (gas, 2891-2895')	2891	2929
Total depth (first drilling)		2881
Total depth (second drilling)		2929
Total depth (third drilling)		2930