

PEARCY-SPERRY NO. 3 WELL.

Greenbrier District, Doddridge County, W. Va.

By.....

J. L. Trainer, Contractor.

Elevation.....

Drilling commenced Sept. 11, 1915; completed Nov. 27, 1915.

13" casing, 305'; 10", 1120' (pulled); 8", 1497' (pulled); 6", 1556';
5", 2145'.

Tubed with 2843' of 2" tubing.

Top joint 8 1/2" casing not set up.

Packer length, 3' 4", on 5" casing.

Nipple and shoe below packer. 3' 6" on 5" casing.

Gas, 22/10 Water through 2" opening at 2156'.

Gas, 13/10 Water through 2" opening at 2710'.

Gas, 25/10 Water through 5" at 2779'.

Top of perforation, 2779'; top of packer, 2701'; bottom of packer, 2705'.

Percy lease and the 4 wells sold to H. G. Sperry May 20, 1926.

Record in Eastern Petroleum Co. Well Record book of Clifton Oil & Gas Co.

	Top.	Bottom.
Conductor	0	16
Native coal	140	142
(water at 285', 4 bailers)		
Coal	415	...
Pittsburgh Coal	705	710
Little Dunkard Sand	1050	1075
Big Dunkard Sand	1160	1200
Gas Sand	1385	1425
First Salt Sand (6 bailers water at 1456') (hole full water, 1491')	1445	1548
Second Salt Sand	1590	1636
3rd Salt Sand	1660	1794
Little Lime	2055	2070
Pencil Cave	2070	2085
Big Lime	2085	2143
Big Injun Sand (gas, 2156', small quantity)	2143	2245
Squaw Sand	2275	2305
Gantz Sand	2345	2390
Fifty-foot Sand	2510	2535
Thirty-foot Sand (gas at 2710'; 13/10 W. in 5")	2691	2719
Gordon Stray Sand	2750	2758
Gordon Sand (gas increased to 24/10 W. in 5" at 2779')	2770	2785
Fourth Sand	2810	2830
Total depth		2848

70193