

EXPLORATION RECORD

NAME	COLOR	CHARACTER	OIL, GAS OR WATER	TOP	BOTTOM	THICK- NESS	TOTAL DEPTH	REMARKS
Clay	Red			0'	20'	20'	20'	
Rock				20	20	0	20	
Slate				20	20	0	20	
Sand				20	102	82	102	
Red Rock				102	120	18	120	
Sand				120	220	100	220	
Slate R.R.				200	300	100	300	
Sand				300	325	25	325	
Slate				325	340	15	340	
Sand	Light			340	360	20	360	
Sl. & R.R.				360	420	60	420	
Coal				420	424	4	424	
Slate	Dark			424	435	11	435	
Sand	Light	Soft	Gas @ 435	435	445	10	445	Exhausted
Sl. & Lime	"	Medium		445	480	35	480	
Sand	"	Soft		480	515	35	515	
Slate	"	"		515	530	15	530	
L. Dunkard	"	Hard		530	550	20	550	
Lime	"	"		550	570	20	570	
Sl. & Sh.	"	Medium		570	615	45	615	
Sand	"	"		615	625	10	625	
Sl. & Sh.	"	"		625	645	20	645	
B. Dunkard	"	Hard		645	675	30	675	
Sl. & Sh.	"	Soft		675	730	55	730	
Sand	"	Hard	Gas @ 740	730	760	30	760	Exhausted
Slate	Dark	Soft		760	770	10	770	
Gas Sand	"	Hard		770	875	105	875	
Slate	"	"		875	1010	135	1010	
1st Salt Sd.	"	Hard		1010	1060	50	1060	
Slate	"	Soft		1060	1125	65	1125	
2nd Salt Sd.	Light	Hard	Gas 1215-21	1125	1250	125	1250	Exhausted
Slate	Dark	Soft		1250	1310	60	1310	
3rd Salt Sd.	White	Medium		1310	1340	30	1340	
Sl. & Sh.	Dark	Soft		1340	1415	75	1415	
Marton Sand	White	Hard	Oil 1420-28	1415	1440	25	1440	Show - Black
Slate	"	Soft		1440	1447	7	1447	
L. Lime	Dark	Hard		1447	1465	18	1465	
Slate	Light	Soft		1465	1475	10	1475	
Bl. Monday	"	Hard	Gas @ 1492	1475	1512	37	1512	
Slate	White	Soft		1512	1513	1	1513	
Big Lime	Gray	Close & HA.		1513	1560	47	1560	
Big Injun	Dark	"	O-G 1614-2	1560	1657	97	1657	Show
Slate	Light	Soft		1657	1705	48	1705	
Squaw	Dark	Hard		1705	1720	15	1720	
Slate	Light	Soft		1720				
TOTAL DEPTH							1761	in slate.

shot
 Well was ~~not~~ shot at Marton Sand feet; well was shot at _____ feet.

Salt

Salt

WEST VIRGINIA DEPARTMENT OF MINES

OIL & GAS SECTION

PRELIMINARY DATA SHEET NO. 1

File No. Gil-1-A

Well No. 7556

PITTSBURGH & WEST VIRGINIA GAS Company, of 435 Sixth Avenue,

Pittsburgh, Penna., on the Sam E. West Farm

containing 83 1/2 acres. Location _____

DeKalb District, in Gilmer County, West Va.

The surface of the above tract is owned in fee by Sam E. West of Glenville, W. Va. address, and the mineral rights are owned by _____ of _____

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit No. _____ issued by the West Virginia Department of Mines, Oil and Gas Section, _____ 1929.

Elevation of surface at top of well, 779 ^{feet} ~~_____~~

The number of feet of the different sized casings used in the well,

_____ ¹⁰ foot _____ size. Good conductor.

187 foot 10 size, seg. 200 feet 6 1/2 size seg.

1810 foot 8-5/16 size, seg. _____ feet _____ size seg.

_____ foot _____ size, seg. _____ feet _____ size seg.

_____ packer of _____ size, set at _____

_____ packer of _____ size, set at _____

_____ in. casing perforated at _____ feet to _____ feet.

_____ in. casing perforated at _____ feet to _____ feet.

Coal was encountered at 650 feet; thickness 60 inches, and at

_____ feet; thickness _____ inches; and at _____ feet; thickness

_____ inches.

Liners were used as follows: (Give details) _____

*876
to 1/2 inch 7 7/8*

**AFFIDAVIT IN TRIPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL**

(REQUIRED BY SECTION 9, CHAPTER 20, ACTS 1929)

**WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS SECTION**

Sam E. West,
COAL OPERATOR
DeKalb, Gilmer County, W. Va.
ADDRESS

Pittsburgh & West Virginia Gas Co.
NAME OF WELL OPERATOR
No. 435-6th Avenue, Pittsburgh, Pa.
COMPLETE ADDRESS

COAL OPERATOR
ADDRESS

September 27
WELL
DeKalb

COAL OPERATOR
ADDRESS

Gilmer County
Well No. 7556

Sam E. West Farm

AFFIDAVITS BE MADE IN TRIPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT. ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA,
COUNTY OF Gilmer

H. E. Wilt and W. H. Satterfield
being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Pitts. & W. Va. Gas Company, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 4th day of September, 19 29, and that the well was plugged and filled in the following manner:

Manner in which sand was pegged: Bridged at 145' filled with Red Clay
filled with Stone to 158' and plug at 158' " " Stone to 170'
15' higher at 175' filled with Stone to 185' " " Stone to 195'
Manner in which coal was pegged: Bridged at 450' filled to 440' on 10'
plug 440' filled to top with Red Clay.

(THE ABOVE DESCRIPTIONS MUST BE IN DET. AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, OIL AND GAS ACT OF 1929.)

19 29

11001101