

Troy District, Gilmer County, W. Va.
Hope Construction & Refining Co., 445 W. Main St., Clarksburg, W. Va.
On 25 acres, surface owned by Icy M. Wilcox, Vadis, W. Va.; owner of
mineral rights unknown.

Drilled prior to June 1, 1929.

Elevation, 980' Alt.

6-5/8" casing, 1715'.

Coal was encountered at 205-215'.

Abandonment reported to Dept. of Mines March 3, 1930.

	Top.	Bottom.
No record of formation overlying the coal seam.		
Pittsburgh Coal	205 -	215
Cow Run Sand (1st)	648 -	699
Cow Run Sand (2nd)	716 -	750
6-5/8" casing, 1715'.		

No oil or gas between the bottom of coal seam and (1715) the
point at which 6-5/8" casing is set.

(RECORD INCOMPLETE)

FORMATION RECORD

Hoge Construction & Drilling Co.
Well No. 1872.

NAME	COLOR	CHARACTER	OIL, GAS OR WATER	TOP	BOTTOM	THICK- NESS	TOTAL WELL DEPTH
No record of formation overlying the coal seam.							
Pittsburgh Coal				805	815	10ft	
Cow Run Sand (1st)				645	690		
Cow Run Sand (2nd)				715	750		
6-5/8" casing					1715		
No oil or gas between the bottom of coal seam and				(1715) the point at which			
6-5/8" casing is set.							

Well was not shot at _____ feet; well was shot at _____ feet.

Salt Fresh water at _____ feet; salt fresh water at _____ feet.

Well was _____ producing hole.

DEPARTMENT OF MINES
OIL & GAS SECTION
PRELIMINARY DATA SHEET NO. 1

11-4-24

Well No. 1378
No. _____
Hope Construction & Refining Co. Company, of 445 West Main Street
Clarksburg, W. Va. on the H. E. Butcher Farm
containing 28 acres. Location Troy
District, in Gilmer County, W. Va.

The surface of the above tract is owned in fee by _____
Icy M. Wilcox of Vadis, W. Va and the
 mineral rights are owned by unknown of _____

The oil and gas privileges are held under lease by the
above named company, and this well is drilled under permit No. _____
issued by the West Virginia Department of Mines, Oil and Gas Section,
drilled prior to June 1st, 1929.

Elevation of surface at top of well, 980 ~~feet~~ feet ~~above~~ sea level.

The number of feet of the different sized casing used in the well.

_____ feet _____ size. Wood conductor,
1715 feet 6-5/8" size, esp. _____ feet _____ sized esp.
_____ feet _____ size, esp. _____ feet _____ sized esp.
_____ feet _____ size, esp. _____ feet _____ sized esp.

_____ packer of _____ size, set at _____
_____ packer of _____ size, set at _____

_____ in. casing perforated at _____ feet to _____ feet.
_____ in. casing perforated at _____ feet to _____ feet.

Coal was encountered at 308 feet; thickness 180 inches, and at
_____ feet; thickness _____ inches; and at _____ feet;
thickness _____ inches.

Liners were used as follows: (Give details) _____

AFFIDVIT IN TRIPPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL

(REQUIRED BY SECTION 2, CHAPTER 22, ACTS 1929)

WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS SECTION

No Coal Operations in this section.

Hope Construction & Refining Company

COAL GRATOR

NAME OF WELL OPERATOR
445 West Main Street
Clarksburg, W. Va.

COMPLETE ADDRESS

ADDRESS

April, 2, 1930. 19

COAL GRATOR

WELL AND LOCATION

ADDRESS

Troy District

COAL GRATOR

Gilmer County

ADDRESS

Well No. 1375

N. E. Butcher Farm

AFFIDVIT TO BE MADE IN TRIPPLICATE: ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (IF EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDVIT

STATE OF WEST VIRGINIA,

COUNTY OF Lewis

BE:

Joseph R. Bailey and Emory B. White
being first duly sworn according to law depose and say that they are experienced in the work of plugging

and filling oil and gas wells and were employed by Hope Const. & Refining Co., well operator,
and participated in the work of plugging and filling the above well, that said work was commenced on the

26th day of February, 1930, and that the well was plugged and filled in
the following manner:

Hole filled with mud from 1825 to depth of 1751, being at a
Manner in which was plugged: point 20 feet above Injun Sand; Cement plug placed at 1751;
6 5/8" Lead plug placed at 1751; 6 5/8" casing pulled and filled with mud to depth of 955 feet, being
at a point 20 feet above it sand; cement plug placed at 955; bridged at depth of 700, being at a
point 20 feet below Cow Run Sand; filled with mud to depth of 425, being at a point 20 feet above
Cow Run Sand; cement plug placed at depth of 425 feet; bridged at depth of 245 feet, being at a point
20 feet below Pittsburgh Coal; filled with cement from 245 feet to 165 feet, being at a point 20 feet
above Pittsburgh Coal; filled with mud and clay to surface.

Manner in which was plugged: Bridged at depth of 245 feet, being at a point 20 feet
below Pittsburgh Coal; filled with cement from 245 feet to 165 feet, being at a point 20 feet
above Pittsburgh Coal; filled to surface with mud & clay.

OK
4/11/30
S. J. W.

Description of cement: 6" X 8" X 5 feet Concrete with lead plate No. of well.

(THE ABOVE DESCRIPTIONS BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 22, OIL AND GAS ACT OF 1929.)
and that the work of plugging and filling said well was completed on the 23 day of March

1930