



No. 1 of 3  
 COAL OPERATOR  
 ADDRESS  
 COAL OPERATOR  
 ADDRESS  
 COAL OPERATOR  
 ADDRESS

Hope Natural Gas Company  
 NAME OF WELL OPERATOR  
 443 West Main Street, Clarksburg, W. Va.  
 COMPLETE ADDRESS  
 November, 4, 1930. 19  
 WELL AND LOCATION  
 Center District  
 Gilmer County  
 Well No. 7493  
 Albu Stamp Farm

AFFIDAVIT TO BE MADE IN TRIPPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT. ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

**AFFIDAVIT**

STATE OF WEST VIRGINIA,  
 COUNTY OF Gilmer ss:  
W. Bonner and William Turner

being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Hope Natural Gas Company, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 14th day of July, 1930, and that the well was plugged and filled in the following manner:

Manner in which sand was plugged: **Total Depth 2330 ft.**

Bridged hole at 2125 ft., filled to 2113 with clay. Filled with clay to 2042 ft. Drove wood plug at 2042 and dumped 200 lbs. mixed cement on plug. Bridged hole at 1880 ft. and filled with clay to 1852 ft. Filled with clay from 1852 to 1727 ft. Filled with clay to 1717 and drove wood plug at 1717 ft. Drove lead plug on wood plug at 1717 ft. Tested plug 48-Hrs. all gas shut off. Bridged hole at 1685 ft. Filled with clay to 1390 ft. Drove wood plug at 1390 ft. and filled with clay to 1297 ft. Set wood plug at 1297 ft. and drove 8" lead plug at 1290 ft. Filled solid with clay to 990 ft. Filled with clay to 980 ft. Drove split wedge

2330

plug 980 ft. and drove 8" lead plug on wedge plug. Filled with clay from 980 ft. to 907 ft. Drove wood plug at 907 ft. and dumped 100 lbs. mixed cement on plug. Filled with clay from 907 ft. to 657 ft. Set Spit wedge plug at and 625 ft. Drove 300 lbs. lead wool on plug. All gas shut off. Filled with clay from 625 ft. to 265 ft. Drove wood plug at 265 ft. and dumped 200 lbs. mixed cement on plug. Pulled 10" casing and filled to top of hole with clay. (All casing pulled)  
 NO COAL. All gas shut off.

Description of monument: Size 8" x 8" x 5", made of concrete with a 3" pipe through the center, and marked "H. N. G. Co., Well No. 7493."

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, OIL AND GAS ACT OF 1929.)  
 and that the work of plugging and filling said well was completed on the 4th day of August

1930  
 And further deponents saith not.

611-7A

W. Bonner