


Latitude 39° 07' 30"

Longitude 80° 45' 08"



2.19a
0.35w

Topo Location

7.5' Loc. _____ 15' Loc. _____
_____ (calc.) _____

Company Hope Cons. & Ref. Co

Farm A. L. Rymer # 579

15' Quad _____
(sec.)

7.5' Quad Auburn

District Troy

WELL LOCATION PLAT

County 021 Permit 30012

**AFFIDAVIT IN TRIPPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL**

(REQUIRED BY SECTION 8, CHAPTER 20, ACTS 1920)

**WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS SECTION**

Well not in coal area,
COAL OPERATOR

Hope Construction & Refining Company,
NAME OF WELL OPERATOR

445 West Main St. Clarksburg, W. Va.
COMPLETE ADDRESS

ADDRESS

COAL OPERATOR

January 16, 19 21
WELL AND LOCATION

Troy District

Gilmer County

COAL OPERATOR

Well No. 579

A. L. Rymer Farm

AFFIDAVIT TO BE MADE IN TRIPPLICATE, ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA,

COUNTY OF _____

SH:

Gilmer - 12A

Joseph E. Straley and Brecks A. Saltbatt

being first duly sworn according to law depose and say that they are experienced in the work of plugging

and filling oil and gas wells and were employed by HOPE CONSTRUCTION & REFINING CO. well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the

16th day of December, 1921, and that the well was plugged and filled in the following manner:

Manner in which said well was plugged: Filled up solid with red mud from bottom of hole to 2519, which was 20 ft. above Gunter Sand, set cement plug at 2519. Hole bridged at 2105 at a point 30 ft. below Injun Sand, filled solid with clay to 1970 which was 20 ft. above Injun Sand, and in Big Lime sand, drove 4-5/8" Lead Plug at 1970. Pulled 6-5/8" Casing and filled solid with clay to 1600 at 20 ft. above Little Lime sand. Set Cement Plug at 1600 ft. Bridged hole at 1670 at 20 ft. below Salt Sand. Filled solid with Mud to 1470, at 20 ft. above Salt Sand, and set Cement Plug at 1470 ft. Filled hole solid with mud to 1150 at about 10 ft. below 6" Casing, made gas test and found hole completely sealed, set Cement Plug at 1150. Pulled 6 1/2" Casing and filled solid with mud to 960 ft. Set Cement plug at 960 ft. above Big Hubbard Sand. Bridged hole at 805 ft. Set Cement Plug at 805 ft. and filled solid with Red Mud to surface.

21/12/21

Description of monument: Erected Concrete Ring Monument extending 30" below surface of ground and 30" Above ground, bearing an inscription "H O & R Co Well 579"

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 16, CH. 20, ACTS 1920.)
and that the work of plugging and filling said well was completed on the 16th day of January

1921
And further deponents saith not.

DEPARTMENT OF MINES
JAN 27 1921
J. E. Straley