



Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
Soil & Clay				0	10	10	10	
Gritty Lime	Stone			10	140	130	140	
Sand				608	625	20	625	
Gritty Lime				680	690	10	690	
Sand-Slate				690	760	70	760	
Sand		Hard		760	856	96	856	
Slate				856	876	20	876	
Broken Sand				876	966	90	966	
Coal				969	978	9	978	
Slate-Shells				978	1141	163	1141	
Sand				1141	1154	13	1154	
Hard Lime				1522	1530	8	1530	
3rd. Salt Sand			Gas 1629	1612	1659	47	1659	
Shale		Soft	" 1635	1659	1667	8	1667	(S.L.1664)
Lime	Gray	Hard	" 1644	1667	1700	33	1700	
Red Rock				1700	1730	30	1730	
Maxon Sand	Pink	Hard		1730	1755	25	1755	
Slate	Dark	Soft		1755	1758	3	1758	
Slate & Shell				1758	1820	62	1820	
Slate	Black	Soft		1820	1835	15	1835	
Lime	Dark	Hard		1835	1853	18	1853	
Slate	"	Soft		1853	1858	5	1858	
Blue Monday	White	Hard	Gas&Oil	1858	1888	30	1888	(S.L.1868)
Big Lime	"	"	1865	1888	1957	69	1957	
Big Injun	"	"	Gas 1872	1957	2045	88	2045	
Slate	"	Soft		2045	2120	75	2120	
TOTAL DEPTH							2120	

Well was ~~not~~ shot at 1874' - Blue Monday feet; well was shot at _____ feet.

Salt _____ salt
 Fresh water at _____ feet; fresh water at _____ feet.

Well was producing 5- 3/16" _____

**AFFIDAVIT IN TRIPPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL**

(REQUIRED BY SECTION 9, CHAPTER 28, ACTS 1922)

**WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS SECTION**

Vol 24 A

W.E. Snodgrass

COAL OPERATOR

Salem, Mo.

ADDRESS

COAL OPERATOR

ADDRESS

COAL OPERATOR

ADDRESS

Pgh. & W. Va. Gas Company

NAME OF WELL OPERATOR

Clarksburg, W. Va.

COMPLETE ADDRESS

September 18th, 19 31.

WELL AND LOCATION

Center District

Gilmer County

Well No. **7538**

W.E. Snodgrass Farm

AFFIDAVIT TO BE MADE IN TRIPPLICATE, ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO BE DELIVERED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA,

COUNTY OF **Gilmer**

} DE:

E.F. Martin

and

J.S. Law

being first duly sworn according to law depose and say that they are experienced in the work of plugging

and filling oil and gas wells and were employed by **Pgh. & W. Va. Gas Co.** well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the

2nd day of **September**, 19 **31.** and that the well was plugged and filled in the following manner:

Manner in which sand was plugged:

Bridge at 1938. Filled with clay from 1938 to 1939. Cement 1939 to 1939. Bridge at 1761. Filled with stone to 1761. Lead Plug 2026 to 1761. Bridge at 1700. Filled with stone from 1700 to 1699. Filled with clay from 1699 to 1557. Cement 1557 to 1522.

Manner in which coal was plugged:

Bridge at 1035. Filled with stone from 1035 to 1008. Cement 1008 to 948. Bridge at 212. Filled with clay to top of hole.

Description of monument:

Cement and iron pipe, with cast iron plate, lettered Pgh. & W. Va. Gas Co. Well No. 7538.

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, 20, AND 20A ACT OF 1922.)
and that the work of plugging and filling said well was completed on the **18th** day of **September**

19 **31.**

And further deponents saith not.

*416
X-1113*

CT 11

Center District, Gilmer County, W. Va. Gilmer 24A
 Pittsburgh & W. Va. Gas Co., Clarksburg, W. Va.
 On 17.5 acres, surface and mineral rights owned by W. E. Snodgrass,
 Salem, Mo.

Well completed July 1, 1926.

Elevation, 971' L.

10" casing, 189'; 8 $\frac{1}{4}$ ", 876'; 6-5/8", 1514'; 5-3/16", 1868'.

Coal was encountered at 969-978'.

Liner: 110' of 6-5/8" casing used as liner.

Completion reported to Dept. of Mines (deepening), July 15, 1931.

Began drilling, June 11, 1926; completed drilling, July 1, 1926.

Began drilling deeper, June 11, 1931; completed drilling deeper,
 June 30, 1931. Completed (deepening) was dry hole.

Well was shot at 1874' in Blue Monday Sand.

	Top.	Bottom.
Soil and clay	0	10
Gritty limestone	10	140
Sand	605	625
Gritty lime	680	690
Sand-Slate	690	760
Sand, hard	760	856
Slate	856	876
Broken sand	876	966
Coal	969	978
Slate-Shells	978	1141
Sand	1141	1154
Hard lime	1522	1530
3rd Salt Sand (gas, 1629', 1635' & 1644')	1612	1659
Shale, soft (SLM--1664')	1659	1667
Lime, gray, hard	1667	1700
Red rock	1700	1730
Maxton Sand, pink, hard	1730	1755
Slate, dark, soft	1755	1758
Slate and shell	1758	1820
Slate, black, soft	1820	1835
Lime, dark, hard	1835	1853
Slate, dark, soft	1853	1858
Blue Monday Sand, white, hard (gas and oil, 1865'; gas, 1872') (SLM-1868')	1858	1888
Big Lime, white, hard	1888	1957
Big Injun Sand, white, hard	1957	2045
Slate, white, soft, to bottom	2045	2120

Central West Va Gas COMPANY

Record of Well No. **7538** Located on **W. E. Snodgrass** Farm
 District **Center** District **Gilmer** County **West Va** State **19**
 Division **K.** District No. **19** Drilled under Well Order
 Rig built by **19** Began **19** Completed **19**
 Well drilled by **19** Began **June 11 1926** Completed **June 11 1926**
 Depth of Well **1659** feet Size of Hole **6 5/8** Producing **Gas**
 Elev: **971 G** 2120

AMOUNT	SIZE	KIND	REMARKS
189 ft	10"	Casing	Reclaimed Sept-18-1931.
876 ft	8 1/4"	"	Reclaimed Sept-18-1931.
110 ft	6 7/8"	"	Left in hole.
1653 ft	3"	Tubing	6 7/8" x 2 Anchor Packer, Packer set 1626 ft.
1868	5 1/16"	Casing	

COAL VEINS **969-978**

NAME	FORMATIONS		OIL	GAS	WATER	REMARKS
	TOP	BOTTOM				
Graty Limer	140					
Sand	605	675				Shot - July-9-1931. with 20 quarts. Length of shell 6 ft.
Graty Limer	680	690				Length of Anchor Shell 16 ft.
Sand	690	760				Top of shot 18 ft. Bottom of shell at 18 ft. Shot by Cooper Murdy. Bickel Torpedo. Co.
Sand	760	856				
Slate	856	876				
Sand	876	966				
Coal	969	978				
Slate & Shells	978	1141				
Sand	1141	1154				
Graty Limer	1572	1580				
3rd Sack	1612	1659				
Slate	1659	1667				
Lime	1667	1700				
Red Rock	1700	1730				
Maxom Sand	1730	1755				
Slate	1755	1758				
Slate & Shells	1758	1820				
Slate	1820	1835				
Lime	1835	1855				
Slate	1853	1858				
Blue Monday Sand	1858	1888	Show	Show		
Big Lime	1888	1957	1865	1872		
Big Injun	1957	2045				
Slate	2040	2120				

total depth
 Hole filled up to 1653 ft with steel casing, lead and wool, to shut off water.
 Drilled down with Company Tools, completed June-11-31. from 1659.
 Plugged & Abandoned Sept-18th, 1931 as follows:
 Bridge at 1938. Clay 1938 to 1838. Cement 1838 to 1830.
 Bridge at 1761. Filled with stone to 1751. Lead Plug 1750 to 1751. Bridge at 1700. Stone 1700 to 1690. Clay 1690 to 1537. Cement 1537 to 1522.
 Bridge at 1035. Stone 1035 to 1008. Cement 1008 to 945.
 Bridge at 212. Filled with clay to top.

1538

FORMATIONS

NAME	TOP	BOTTOM	OIL	GAS	WATER	REMARKS
Soil & clay		10	✓			
Gritty Lime Stone	10	140	✓			
Sand	605	625	✓			
Gritty Lime	680	690	✓			
Sand Slate	690	760	✓			
Sand Hard	760	856	✓			
Slate	856	876	✓			
Broken Sand	876	966	✓			
Coal	969	978	✓			
Slate & Shell	978	1141	✓			
Sand	1141	1144	✓			
Hard Lime	1522	1530	✓			
3 in Salt Sand	1612	1659	✓			Total Depth 1659
Slate	1659	1667				
Lime	1667	1700				
Red Rock	1700	1730				
Maxom Sand	1730	1755				
Slate	1755	1758				
Slate & Shells	1758	1820				
Slate	1820	1835				
Lime	1835	1853				
Slate	1853	1858				
Blue Monday Sand	1858	1888	1865	1872		Show.
Big Lime	1888	1957				
Big Injun	1957	2045				
Slate	2040	2120	T.D.			

Handwritten notes or signatures at the bottom of the page, mostly illegible due to fading and bleed-through.