

NOT LOCATED

Rt. Fk. of Steer Ck.

o

Gil-25A

McCall Drilling Co., Inc. *Company*
 #611 Keystone Bldg., Pgh., *Address*
 Penna.

COMPLETION DATA SHEET
 NO. 2
 FORMATION RECORD

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
Injun	Gray	Hard		1640	1800	160		
Slate	Dark	Soft		1800	1850	50		
Lime	Gray	Hard		1850	1900	50		
Slate	Dark	Soft		1900	1920	20		
Lime	Gray	Hard		1920	1950	30		
Slate	Dark	Soft		1950	1960	10		
Lime	Dark	Hard		1960	1990	30		
Slate	"	Soft		1990	2050	60		
Lime	Dark	Hard		2050	2150	100		
Slate	"	Soft		2150	2275	125		
Sandy Lime	Gray	Hard		2275	2300	25		
Red Rock	Red	Soft		2300	2305	5		
Slate	Dark	Soft		2305	2340	35		
Gordon	Gray	Hard		2340	2347	7		
Slate	Dark	Soft		2347	2440	93		
5th Sand	Gray	Hard		2440	2460	20		
late & Shells		Hard		2460	2585	125		
							2585	

Well was not shot at *no record*

feet, well was shot at

feet

WEST VIRGINIA DEPARTMENT OF MINES

Oil and Gas Section

1-25-A

PRELIMINARY DATA SHEET NO. 1

File No. _____ Well No. 1-69

McCall Drilling Co., Inc. Company, of Pittsburgh, Penna.

on the F. H. Stout Farm

containing 20 acres, Location

Center District, in Gilmer County, West Virginia.

The surface of the above tract is owned in fee by F. H. Stout

of Shock, W. Va. address, and the mineral rights are owned by

F. H. Stout of Shock, W. Va.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit No. Old Well issued by the West Virginia Department of Mines, Oil and Gas Section.

19

Elevation of surface at top of well, 726 Feet Spirit Barometric

The number of feet of the different sized casings used in the well.

feet	size, casing	feet	size, casing	size, Wood conductor
148	10"	805	8-1/4"	size, wood conductor
1889	6-5/8"			size, casing
				size, casing
	packer of		size, set at	
	packer of		size, set at	
	in casing perforated at		feet to	feet
	in casing perforated at		feet to	feet
Coal was encountered at	No record	feet, thickness	inches, and at	
feet, thickness	inches, and at	feet, thickness	inches	
Liners were used as follows: (Give details)				None

FORM 2-B
AFFIDAVIT IN TRIPPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL

(REQUIRED BY SECTION 8, CHAPTER 20, ACTS 1887)

WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS SECTION

Fletcher Stout
COAL OPERATOR
Shack. W. Ja.
ADDRESS

M. C. Smith
NAME OF WELL OPERATOR
1110 ...
COMPLETE ADDRESS

COAL OPERATOR
ADDRESS
COAL OPERATOR
ADDRESS

19
WELL AND LOCATION
Center District
Truman County
Well No. *2-70*
Fletcher Stout Farm

AFFIDAVIT TO BE MADE IN TRIPPLICATE: ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO BE RETURNED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA,

COUNTY OF *Truman* } ss:

Donald Grinkley and *J. Y. Stewart*
being first duly sworn according to law depose and say that they are experienced in the work of plugging

and filling oil and gas wells and were employed by *M. C. Smith* as well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the

27 day of *August*, 19*31*, and that the well was plugged and filled in the following manner:

Manner in which sand was plugged:	6 5/8 hole.	8 1/4 hole
	Bridge 1880	Bridge 1150
	Rock to 1820	Rock to 1000
	2 wood plugs	Plug wood
	Clay & rock to 1710	Clay to 1000
	50 lb. lead	Plug wood
	plug wood	Rock 1000
	Clay & rock to 1650	Clay 1050
Manner in which coal was plugged:	Plug wood	Plug wood
	Clay to 1640	Clay & rock to 1010
	Plug wood	Plug wood
	Clay & rock 1620	Rock & clay to 930
	Plug wood	

Description of measurement:
10 inch hole
Wood plug set on shoulder at 550; Rock 540. Bridged at 50 ft. Filled to top.

THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, CHAPTER 20, ACTS 1887, AND THAT THE WORK OF PLUGGING AND FILLING SAID WELL WAS COMPLETED ON THE *1* day of *August*, 19*31*.

19 *31*