





Center District, Gilmer County, W. Va. 25-A  
 South Penn Oil Co., P. O. Drawer 1255, Pittsburgh, Pa.  
 On 58.6 acres, surface owned by Chas. Riddle and Dr. D. C. Mullens,  
 both of Rose Dale, W. Va., and mineral rights by Hunter M.  
 Bennett, Weston, W. Va., and Alice B. Bennett, Gertrude B.  
 Howell, and Mary Bowie.

Elevation, 979.5' L.

10" casing, 279' 6"; 8 1/4", 855'.

Coal was encountered at 465-472'.

Abandonment reported to Dept. of Mines Oct. 8, 1931.

Well was shot (depth unknown).

Salt water at 1610'.

	Top.	Bottom.
Gravel and quicksand	0	34
Sand	34	160
Red rock	160	262
Sand	262	300
Slate and red rock	300	400
Sand and lime	400	460
Coal	465	472
Sand	505	530
Lime	530	550
Sand	550	560
Sand	577	590
Lime	661	690
Sand	700	730
Sand	900	928
Lime	1020	1155
Sand	1155	1165
Sand	1184	1225
Slate	1547	
<i>1st Salt</i> Sand (show of oil and gas, 1565')	1560	1580
Slate	1580	1585
<i>2nd Salt</i> Sand (oil and gas, 1592'; oil, 1600'; salt water, 1610')	1585	
Total depth		1610



WEST VIRGINIA DEPARTMENT OF MINES

Oil and Gas Section

*Well 28-A*

PRELIMINARY DATA SHEET NO. 1

File No.

Well No. 1

South Penn Oil

Company, of P. O. Drawer 1255, Pittsburgh, Pa.

on the W. G. Bennett

Farm

containing 58.6 acres. Location

Center

District, in Gilmer

County, West Virginia.

Chas. Riddle

The surface of the above tract is owned in fee by Dr. D. C. Mullens

Rosedale, W. Va.

Rosedale, W. Va.

address, and the mineral rights are owned by Weston, W. Va.

Hunter M. Bennett

Alice B. Bennett

Gertrude B. Howell

Mary Bowie

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit No. \_\_\_\_\_ issued by the West Virginia Department of Mines, Oil and Gas Section.

19

Elevation of surface at top of well, 979.5

Spirit Barometric.

The number of feet of the different sized casings used in the well.

_____	feet	_____	size, csg.	_____	feet	_____	size, Wood conductor
279' 6"	feet	10"	size, csg.	_____	feet	_____	size, csg.
855	feet	8 1/4"	size, csg.	_____	feet	_____	size, csg.
_____	feet	_____	size, csg.	_____	feet	_____	size, csg.
_____	packer of	_____	size, set at	_____	feet	_____	feet
_____	packer of	_____	size, set at	_____	feet	_____	feet
_____	in casing perforated at	_____	feet to	_____	feet	_____	feet
_____	in casing perforated at	_____	feet to	_____	feet	_____	feet

Coal was encountered at 465-472 feet; thickness 84 inches, and at \_\_\_\_\_ feet; thickness \_\_\_\_\_ inches; and at \_\_\_\_\_ feet; thickness \_\_\_\_\_ inches.

Liners were used as follows: (Give details) \_\_\_\_\_

AFFIDAVIT IN TRIPLICATE TO TIME AND MANNER OF PLUGGING AND FILLING WELL

(REQUIRED BY SECTION 8, ARTICLE 4, CHAPTER 22 OF THE CODE)

WEST VIRGINIA DEPARTMENT OF MINES OIL AND GAS DIVISION

Hunter M. Bennett  
COAL OPERATOR OR OWNER

Weston, W. Va.

ADDRESS

COAL OPERATOR OR OWNER

ADDRESS

COAL OPERATOR OR OWNER

ADDRESS

SOUTH PENN OIL COMPANY

NAME OF WELL OPERATOR

P. O. Drawer 1255, Pittsburgh, Pa.

COMPLETE ADDRESS

November 12, 19 31

WELL AND LOCATION

Center District

Gilmer County

Well No. 1

W. G. Bennett Farm

AFFIDAVIT TO BE MADE IN TRIPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT. ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA,

COUNTY of Roane } ss:

John Starkey

being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by SOUTH PENN OIL COMPANY, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 19th day of October, 19 31, and that the well was plugged and filled in the following manner:

Manner in which sand was plugged: Total depth 1610'; filled up with non-porous sediment to 1540'; set 8 1/2" x 3' wood plug from 1540'-1537'; Lead wool from 1537' to 1535'; set cement plug from 1535' to 1527'. All gas shut off. Filled up with non-porous sediment to 855'; pulled 8 1/2" casing; filled up with non-porous sediment to 502'; set vent pipe at 502'; set cement plug from 502' to 445'; filled up with non-porous sediment to 279'; pulled 244' of 10" casing, leaving 35' in the hole; filled with non-porous sediment to surface.

Manner in which coal was plugged:

Description of monument: Erected marker as described in Rule 18 of 1931 Regulations. All done in workman-like manner.

Handwritten initials and numbers: 21113