

Latitude 38° 45' 00"

Longitude 80° 57' 30"

Longitude



1.682
0.96W

Topo Location

7.5' Loc. _____ 15' Loc. _____
_____ (calc.) _____

Company South Penn O.I. Co.

Farm W.G. Bennett #2

15' Quad _____
(sec.)

7.5' Quad Rosedale

District Center

WELL LOCATION PLAT

County 021 Permit 30030

Center District, Gilmer County, W. Va.
 South Penn Oil Co., P. O. Drawer 1255, Pittsburgh, Pa.
 On 83.6 acres, surface owned by Chas. Riddle, Rosedale, W. Va.,
 and mineral rights by Hunter M. Bennett, Weston, W. Va.
 Elevation, 1174' L.
 8 $\frac{1}{4}$ " casing, 390'; 6-5/8", 990'; 5-3/16", 2194'.
 Coal was encountered at 1810-1813'.
 Abandonment reported to Dept. of Mines Oct. 17, 1931.
 Well was shot in Big Injun Sand.

	Top.	Bottom.
Sand	450	- 500
Sand	600	- 640
Sand	780	- 840
Lime	840	- 955
Sand	955	- 1000
Sand (gas show, 1040')	1030	- 1150
Sand	1390	- 1420
Sand	1475	- 1530
Coal	1810	- 1813
Sand	1876	- 1960
Lime	2000	- 2025
Pencil Cave	2025	- 2040
Big Lime	2040	- 2125
Big Injun Sand (gas)	2125	- 2220
Shells	2220	- 2420
Gantz? Sand	2420	- 2435
50-Ft. Sand	2580	- 2595
Slate, lime, and shells	2595	- 3090
Hard lime shells	3090	
Total depth		3275

WELL RECORD

Lease No. _____ Acres _____

A. G. Bennett

Farm Well No. *2*

Center

District or Township

Gilmer 30-A

County

W. Va.

State

Rig Commenced _____ 19 _____

Rig Contractor _____

Rig Completed _____ 19 _____

Drg. Contractor _____

Drilling Commenced *7-10* 19*01*

Drilling Completed *10-6* 19*01*

N. _____ S. *50* E. _____ W. *21*

Rock Formation	Top	Bottom	Steel Line Measurement	Remarks
<i>Sand</i>	<i>450</i>	<i>500</i>		
<i>"</i>	<i>600</i>	<i>640</i>		
<i>"</i>	<i>780</i>	<i>840</i>		
<i>Lime</i>	<i>840</i>	<i>955</i>		
<i>Sand</i>	<i>955</i>	<i>1000</i>		
<i>"</i>	<i>1030</i>	<i>1150</i>		
<i>Light Gas</i>	<i>1040</i>			
<i>Sand</i>	<i>1390</i>	<i>1420</i>		
<i>"</i>	<i>1475</i>	<i>1530</i>		
<i>Coal</i>	<i>1810</i>	<i>1813</i>		
<i>Sand</i>	<i>1876</i>	<i>1960</i>		
<i>Lime</i>	<i>2000</i>	<i>2025</i>		
<i>Pencil Cave</i>	<i>2025</i>	<i>2040</i>		
<i>Big Lime</i>	<i>2040</i>	<i>2125</i>		
<i>Big Injun Shells</i>	<i>2125</i>	<i>2220</i>		<i>Gas -</i>
<i>Gantz</i>	<i>2420</i>	<i>2435</i>		
<i>Fifty foot</i>	<i>2580</i>	<i>2595</i>		
<i>Lime & shells</i>	<i>2595</i>	<i>3090</i>		
<i>Hard Lime shells</i>	<i>3090</i>			
<i>T D</i>		<i>3275</i>		

CASING RECORD AS TALLIED

NOT STEEL LINE MEASUREMENT

Size	Put in Well		Pulled Out		Left in Well		Shot Date
	Feet	In.	Feet	In.	Feet	In.	
							Amount
							Sand
							Result
							Packer Size
							Depth Set

Gas Test _____

Approved: _____

Production First 24 Hours } _____

Bbbs. _____

Supt. _____

SOUTH WEST OIL COMPANY

Company

COMPLETION DATA SHEET

P. O. Drawer 1255

Address

W-20-A

NO. 2

Pittsburgh, Pa.

FORMATION RECORD

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
Sand				450	500	50		
Sand				500	640	140		
Sand				780	840	60		
Lime				840	955	115		
Sand				955	1000	45		
Sand				1050	1150	100		
			Gas show	1040				
Sand				1350	1420	70		
Sand				1475	1530	55		
Coal				1610	1613	3		
Sand				1676	1960	284		
Lime				2000	2025	25		
Pencil Cave				2025	2040	15		
Big Lime				2040	2185	145		
Big Injun				2125	2220	95		
			Gas	7				
Shells				2220	2420	200		
Gantz Sand				2420	2435	15		
Fifty Foot				2580	2595	15		
Slate, Lime & Shells				2595	3090	495		
Hard Lime Shells				3090				
Total Depth							3275	

Big Injun Sand

feet

WEST VIRGINIA DEPARTMENT OF MINES

Oil and Gas Section

Oil-30-A

PRELIMINARY DATA SHEET NO. 1

File No.

Well No. 2

South Penn Oil

Company of P. O. Drawer 1255, Pittsburgh, Pa.

on the W. G. Bennett Farm

containing 83.6 acres. Location

Center District in Gilmer County, West Virginia.

The surface of the above tract is owned in fee by Chas. Riddle

of Rosedale, W. Va. address, and the mineral rights are owned by

Hunter M. Bennett of Weston, W. Va.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit No. _____ issued by the West Virginia Department of Mines, Oil and Gas Section,

19 _____

Elevation of surface at top of well, 1174' Spirit Barometric.

The number of feet of the different sized casings used in the well.

feet	size, csg.	feet	size, csg.	Wood conductor
<u>390</u>	<u>8 1/4"</u>			
<u>990</u>	<u>6 5/8"</u>			
<u>2194</u>	<u>5 3/16"</u>			

_____ packer of _____ size, set at _____

_____ packer of _____ size, set at _____

_____ in casing perforated at _____ feet to _____ feet.

_____ in casing perforated at _____ feet to _____ feet.

Coal was encountered at 1810-1813 feet; thickness _____ inches, and at

feet; thickness _____ inches; and at _____ feet; thickness _____ inches.

Linners were used as follows: (Give details) _____

AFFIDAVIT IN TRIPLICATE TO TIME AND MANNER OF PLUGGING AND FILLING WELL

(REQUIRED BY SECTION 9, ARTICLE 4, CHAPTER 22 OF THE CODE)

WEST VIRGINIA DEPARTMENT OF MINES OIL AND GAS DIVISION

Hunter M. Bennett
COAL OPERATOR OR OWNER
Weston, W. Va.
ADDRESS

30-A
SOUTH PENN OIL COMPANY
NAME OF WELL OPERATOR
P. O. Drawer 1255, Pittsburgh, Pa.
COMPLETE ADDRESS

COAL OPERATOR OR OWNER
ADDRESS

December 16, 19 31

WELL AND LOCATION

Center District

Gilmer County

COAL OPERATOR OR OWNER
ADDRESS

Well No. 2

W. O. Bennett Farm

AFFIDAVIT TO BE MADE IN TRIPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT. ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA,

COUNTY OF Roane ss:

John Starkey

being first duly sworn according to law depose and say that they are experienced in the work of plugging

and filling oil and gas wells and were employed by SOUTH PENN OIL COMPANY, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the

2nd day of November, 19 31, and that the well was plugged and filled in the following manner:

Manner in which sand was plugged: Total depth 3275'; filled with non-porous material to 2105'; set 5 3/16 x 3' common wood dry hole plug from 2105'-2102'; set lead plug from 2102' to 2100'; lead wool from 2100' to 2097'; set cement plug from 2097' to 2087'; set 5 3/16 x 3' common wood dry hole plug from 2087'-to 2084'; filled with non-porous sediment to 2012'; set bridge of iron and rock from 2012' to 2002'; set 5 3/16" lead plug from 2002' to 2000'; filled with non-porous sediment to 1943'; set cement plug from 1943' to 1898'; Bliss shut-off valve set at 1898'; 5 3/16 lead plug set from 1898' to 1896'; filled with non-porous

476
01/11/3

Manner in which coal was plugged: sediment to 1843'; set cement plug from 1843' to 1790'; filled with non-porous sediment to 1650'; pulled 5 3/16" casing; filled with non-porous sediment to 1010'; set cement plug from 1010' to 1000'; pulled 6 5/8" casing; filled to 489' with non-porous sediment; set cement plug from 489' to 457'; Bliss shut-off valve set at 457'; filled to 440' with non-porous sediment; set 8 1/2" x 3' Common wood dry hole plug from 440' to 437'; pulled 8 1/2" casing; filled to surface with non-porous sediment.

Description of monument: Piece of 8 1/2" Casing set in hole 11 ft. and extends above surface 5 ft. Filled around with stone and inside of marker filled with stone to within 18 inches of top. The top filled with cement and a brass plate set in cement giving name of farm, well No., date abandoned and the operator.

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, ARTICLE 4, CHAPTER 22 OF THE CODE.)
and that the work of plugging and filling said well was completed on the 25th day of November