





36-A

DeKalb District, Gilmer County, W. Va. <sup>36-A</sup>  
 South Penn Oil Co., P. O. Drawer 1255, Pittsburgh, Pa.  
 On 20 $\frac{1}{2}$  acres, surface and mineral rights owned by A. N. Selman,  
 Revere, W. Va.

Elevation, 871.5' L.  
 10" casing, 201'; 8 $\frac{1}{2}$ " 942'; 5-3/16", 1772'; 2" tubing, 1671';  
 3" tubing, 1656'.

Packer, 3 x 8 $\frac{1}{4}$ ", set 29' 10" from bottom.

Packer, 3 x 8 $\frac{1}{4}$ ", set 191' 11" from bottom.

~~Completion~~ reported to Dept. of Mines July 29, 1932. (Deepening?)

Well was shot Oct. 24, 1921, with 40 qts., in 2nd Salt Sand.

Well was shot Sept. 30, 1927, with 10 qts., in Big Injun Sand.

	Top.	Bottom.
2nd Cow Run Sand	935	- 1025
Salt Sand (little gas, 1485')	1460	- 1523
Maxton Sand (gas, 1656-1661')	1636	
Total depth		1671

DRILLED DEEPER: COMMENCED DRILLING 1656

Maxton Sand	1636	- 1700
Red rock	1700	- 1710
Little Lime	1727	- 1750
Pencil Cave	1750	- 1754
Big Lime (5-3/16" casing, 1758' SLM)	1754	- 1810
Keener Sand	1810	- 1845
Lime	1845	- 1860
Big Injun Sand	1860	- 1909
Break in sand, 1883-1893'; oil, 1904-		
1909' → SLM, 1909'.		
Slate	1909	- 1960
Lime and shells	1960	- 1985
Slate	1985	- 2005
Lime and shells	2005	- 2015
Slate	2015	- 2045
Lime and shells	2045	- 2055
Slate	2055	- 2110
Lime and shells	2110	- 2130
Slate	2130	- 2170
Lime and shells	2170	- 2190
Slate	2190	- 2225
Berea Sand	2225	- 2255
Slate	2255	- 2300
Lime and shells	2300	- 2304
Slate, to bottom	2304	- 2315

(Drilled 60' below Berea Sand).

1671

644' New Etc

SOUTH PENE OIL  
P. C. Drawer 1222,  
Pittsburgh, Pa.

Company  
Address

COMPLETION DATA SHEET  
No. 2  
FORMATION RECORD

Well No. 1, A. N. Selman Farm.

21-36-A

Name	Color	Character	Oil Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
End Cow Run				935	1025			
Salt				1460	1523			
		Little gas		1485				
Maxon Sand			Gas	1636	1661			
				1656				
Total depth							1671	
Drilled Deeper					1656			
Commenced Drilling					1700			
Maxon				1636	1700			
Red Rock				1700	1710			
Little Lime				1727	1750			
Pencil Cave				1750	1754			
Big Lime				1754	1810			
5-3/16" casing					1758	Steel line	1758	
Keener				1810	1845			
Lime				1845	1860			
Big Injun				1860	1909			
Break in sand				1883	1893			
			Oil	1904	1909	" "		1909
Slate				1909	1960			
Lime & Shells				1960	1985			
Slate				1985	2005			
Lime & Shells				2005	2015			
Slate				2015	2045			
Lime & Shells				2045	2055			
Slate				2055	2110			
Lime & Shells				2110	2130			
Slate				2130	2170			
Lime & Shells				2170	2190			
Slate				2190	2225			
Berea				2225	2255			
Slate				2255	2300			
Lime & Shells				2300	2304			
Slate				2304	2315			
Total depth					2315		2315	
Drilled 60' below Berea Sand.								

shot  
Well was ~~run~~ 10-24-21, -40 qts. 2nd Salt feet; well was shot 29-30-27, -10 qts. Injun feet.

WEST VIRGINIA DEPARTMENT OF MINES

Oil and Gas Section

*Oil-36-A*

PRELIMINARY DATA SHEET NO. 1

File No. \_\_\_\_\_ Well No. 1

SOUTH PENN OIL Company of P. O. Drawer 1255,  
Pittsburgh, Pa. on the A. N. Selman Farm  
 containing 20-1/4 acres. Location \_\_\_\_\_

DeKalb District, in Gilmer County, West Virginia.

The surface of the above tract is owned in fee by A. N. Selman,  
 of Revere, W. Va. address, and the mineral rights are owned by  
A. N. Selman of Revere, W. Va.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under  
 permit No. \_\_\_\_\_ issued by the West Virginia Department of Mines, Oil and Gas Section.

Elevation of surface at top of well, 871.5' Spirit  
 Barometric.

The number of feet of the different sized casings used in the well.

	feet	size	Wood conductor
201	feet 10"	size, casg. 1671	feet 2" tubing sized casg.
942	feet 8-1/4"	size, casg. 1656	feet 3" tubing sized casg.
1772	feet 5-3/16"	size, casg.	feet sized casg.
	packer of 3 X 8 1/2		size, set at 29'10" from bottom
	packer of 3 X 8 1/2		size, set at 191'11" from bottom
	in casing perforated at		feet to feet
	in casing perforated at		feet to feet

Coal was encountered \_\_\_\_\_ feet; thickness \_\_\_\_\_ inches, and at \_\_\_\_\_  
 feet; thickness \_\_\_\_\_ inches, and at \_\_\_\_\_ feet; thickness \_\_\_\_\_ inches

Liners were used as follows: (Give details) \_\_\_\_\_

AFFIDAVIT IN TRIPPLICATE TO TIME AND MANNER OF PLUGGING AND FILLING WELL

(REQUIRED BY SECTION 5, ARTICLE 4, CHAPTER 22 OF THE CODE)

WEST VIRGINIA DEPARTMENT OF MINES OIL AND GAS DIVISION

41-36-A

(NO COAL)

SOUTH PENN OIL COMPANY

COAL OPERATOR OR OWNER

NAME OF WELL OPERATOR

P.O. Drawer 1255, Pittsburgh, Pa

ADDRESS

COMPLETE ADDRESS

January 20, 19 32

COAL OPERATOR OR OWNER

WELL AND LOCATION

DeKalb District

ADDRESS

Gilmer County

COAL OPERATOR OR OWNER

Well No. 1

ADDRESS

A. N. Selman Farm

AFFIDAVIT TO BE MADE IN TRIPPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT. ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA,

COUNTY OF Roane

SS:

W. K. McCray

XXXX

being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by South Penn Oil Company, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 26th day of November, 19 32, and that the well was plugged and filled in the following manner:

Manner in which sand was plugged:

Drilled to 2315 ft. and filled back to 1909 ft. Total depth 1909 ft. Fill with non-porous material to 1840 ft. Set wood plug from 1840 to 1827 ft. Set cement plug from 1837 to 1827 ft. Filled with non-porous material to 1765 ft. Pulled 5-3/16" casing. Filled with non-porous material to 1750 ft. Set wood plug from 1727 to 1730 ft. Set cement plug from 1727 to 1717 ft. Filled with non-porous material to 1616 ft. Set wood plug from 1616 to 1613 ft. Set cement plug from 1613 to 1603 ft. Filled with non-porous material to 1553 ft. Set wood plug from 1553 to 1550 ft. Set cement plug from 1550 to 1545 ft. Filled with non-porous material to 1440 ft. Set wood plug from 1440 to 1437 ft. Set cement plug from 1427 to 1427 ft. Filled with non-porous material to 942 ft. Pulled 8 1/2" casing. Filled with non-porous material to 203 ft. Set wood plug 203 to 200 ft. Set cement plug from 200 to 190 ft. Filled with non-porous material to surface and set in hole a piece of 8 1/2" casing, in hole 12 ft. and above surface 4 ft. for marker. Filled inside of marker within one foot of top with non-porous material and placed in top one foot of cement

Description of monument:

which was anchored a brass plate giving name of farm, Well No., Date abandoned, and Company.

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 16, ARTICLE 4, CHAPTER 22 OF THE CODE.)

Plugging and filling said well was completed on the 30th day of December