

WELLS NO 5867-5724  
THE NATURAL GAS CO  
A. H. COOPER  
DE KALB

... on the  
Face number of 200 Area  
GILBERT Camp, W. Va.



ENGINEERS CERTIFICATE

I, the undersigned, hereby certify that this map is correct and shows all the information to the best of my knowledge and belief, received by the oil and gas section of the mining laws of West Virginia.

NOT LOCATED

77A

Troy District, Gilmer County, W. Va.  
 Hope Natural Gas Co., 445 W. Main St., Clarksburg, W. Va.  
 On 220 acres, surface and mineral rights owned by A. H. Cooper,  
 Coxs Mills, W. Va.

Elevation, 900' L.

8 $\frac{1}{4}$ " casing, 952'; 5-3/16", 1747'; 2" tubing, 1855'.

Abandonment reported to Dept. of Mines July 9, 1935.

Well was shot at 1780-1779'.

No record of water.

Gas well. Now exhausted to the extent that it is not commercially  
 productive.

	Top.	Bottom.
Little Dunkard Sand	710	- 730
Big Dunkard Sand	800	- 900
Gas Sand	1050	- 1185
First Salt Sand	1410	- 1470
Maxton Sand	1610	- 1680
Little Lime	1680	- 1720
Pencil Cave	1720	- 1725
Big Lime	1725	- 1774
Big Injun Sand (gas, 1780-1787')	1774	
Total depth		1857

WEST VIRGINIA DEPARTMENT OF MINES

THE OIL AND GAS DIVISION

PRELIMINARY DATA SHEET NO. 1

File No.

Well No. 5724

Hope Natural Gas Company

Company of 440 West Main St.

Clarksburg, W. Va.

on the A. N. Cooper

Farm

containing 320 acres. Location

Troy

District, in

Silber

County, West Virginia

The surface of the above tract is owned in fee by A. N. COOPER

of Cox's Mills, W. Va.

address, and the mineral rights are owned by

A. N. Cooper

of Cox's Mills, W. Va.

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit No. --- issued by the West Virginia Department of Mines, Oil and Gas Division

193

Elevation of surface at top of well, 900

Spirit Barometric

The number of feet of the different sized casings used in the well.

	feet		size, csg.		feet	size, csg.		feet	size, csg.
952	feet	8 1/2"	size, csg.	1747	feet	6 3/8"	size, csg.		
1855	feet	2"	size, csg.		feet		size, csg.		
	feet		size, csg.		feet		size, csg.		
			packer of				size, set at		
			packer of				size, set at		
							in casing perforated at	feet to	feet.
							in casing perforated at	feet to	feet.

Coal was encountered at feet; thickness inches, and at feet; thickness inches; and at feet; thickness inches.

Liners were used as follows: (Give details)

Date

AFFIDAVIT IN TRIPLICATE TO TIME AND MANNER OF  
PLUGGING AND FILLING WELL

PREPARED BY SECTION 2, ARTICLE 4, CHAPTER 22 OF THE CODE

WEST VIRGINIA DEPARTMENT OF MINES  
OIL AND GAS DIVISION

Well not in coal area,  
COAL OPERATOR OR OWNER

Hope Natural Gas Company  
NAME OF WELL OPERATOR

ADDRESS

Clarksburg, W. Va.  
COMPLETE ADDRESS

COAL OPERATOR OR OWNER

October 22nd, 1935, 19

WELL AND LOCATION

ADDRESS

Troy District

COAL OPERATOR OR OWNER

Gilmer County

ADDRESS

Well No. 5724

A. H. Cooper Farm

AFFIDAVIT TO BE MADE IN TRIPLICATE. ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT. ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES.

AFFIDAVIT

STATE OF WEST VIRGINIA,  
COUNTY OF Gilmer } as:

Dorsey D. Lockard and Udbert P. Ellyson

being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Hope Natural Gas Co., well operator, and participated in the work of plugging and filling the above well, that said work was commenced on

10th, day of July, 1935, and that the well was plugged and filled in the following manner:

92'8" of 5 3/16" casg. left in hole. Unable to fish out.

Manner in which sand was plugged: filled with clay to 1704' 20' above Injun sand. Pulled 6 5/8" casg. & set cement plug. permanently bridged at 1500' 30' below salt sand & filled with clay to 1300' 20' above salt sand & set cement plug. bridged & lead plug set at 982.8 1/2" casg. pulled. filled to 850' with clay & mud & wooden plug set. Permanently bridged & cement plug set at 720' & hole filled to surface with mud & clay.

Manner in which coal was plugged: Not in coal area.

Description of monument: 8" X 8" X 5' concrete [scribble] extending 30" above surface and enough below to make it permanent.

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, ARTICLE 4, CHAPTER 22 OF THE CODE)

and that the work of plugging and filling said well was completed on the 22nd day of October

1935

And further deponents saith not.

*[Handwritten signatures]*