

40°35'00"

**Latitude**

.115  
1.49w

80°37'30"

**Longitude**

**Topo Location**

7.5' Loc. \_\_\_\_\_ 15' Loc. \_\_\_\_\_  
(calc.) \_\_\_\_\_

**Company** Bradford Supply Co

**Farm** C E Bremmaman #35

**15' Quad** \_\_\_\_\_  
(sec.)

**7.5' Quad** Wellsville

**District** Grant

**WELL LOCATION PLAT**

**County** 029 **Permit** 30145

C. E. BRENNEMAN ESTATE NO. 35 WELL.

Grant District, Hancock County, W. Va.  
By Bradford Supply Co., Bradford, Pa.  
Abandoned under permit Han-.....-A?  
On 318 acres, on Dry Run.  
Elevation, 757' L.

145A  
see plat 22A

Date of completion, etc., not given.  
Shot with 80 qts.

10" wood conductor, 16'; 8 $\frac{1}{4}$ " casing, 47'; 6 $\frac{1}{4}$ " , 492'; all left in.

Oil well. Record to Dept. of Mines stamped Nov. 28, 1951.

Record to RCT from Mrs. Griffith May 21, 1952. O.F.No.115.

	Top.	Bottom.
Coal	125 -	...
Slate and sandy shells	...	492
Berea Grit (pay, 702-711') (soft sand, 702-706')	695 -	702
Finished drilling		721
Cleaned to		733



STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

115

WELL RECORD

Permit No. MAN-145-A

Oil or Gas Well \_\_\_\_\_  
(KIND)

Company Bradford Supply Company  
 Address Bradford, Pa.  
 Farm C. E. Ereneman Est. Acres 318  
 Location (waters) Dry Run  
 Well No. 35 Elev. 757'  
 District Grant County Hancock  
 The surface of tract is owned in fee by \_\_\_\_\_  
 Address \_\_\_\_\_  
 Mineral rights are owned by \_\_\_\_\_  
 Address \_\_\_\_\_  
 Drilling commenced \_\_\_\_\_  
 Drilling completed \_\_\_\_\_  
 Date Shot From \_\_\_\_\_ To \_\_\_\_\_  
 With 80 qts.  
 Open Flow /10ths Water in \_\_\_\_\_ Inch  
 /10ths Merc. in \_\_\_\_\_ Inch  
 Volume \_\_\_\_\_ Cu. Ft.  
 Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
 Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
 Fresh water \_\_\_\_\_ feet \_\_\_\_\_ feet  
 Salt water \_\_\_\_\_ feet \_\_\_\_\_ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			
10	<u>Wood Cond. 16'</u>	<u>16'</u>	Size of
8 1/4	<u>47'</u>	<u>47'</u>	
6 5/8	<u>6-1/4" 492'</u>	<u>492'</u>	Depth set
5 3/16			
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_  
 COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Coal			125				
Slate	Sandy shells			492			
Berea Grit			695	702			
Pay			702	711			
Soft Sand			702	706			
Finished drilling				721			
Cleaned to				733			



MAY 21 1952