

WR-35
Rev (9-11)

State of West Virginia
Department of Environmental Protection
Office of Oil and Gas
Well Operator's Report of Well Work

DATE: 1/14/2013
API #: 47-033-05638

Farm name: Lowe, Francis and Nancy Operator Well No.: Ora Unit 1H

LOCATION: Elevation: 1201' Quadrangle: West Milford

District: Union County: Harrison
Latitude: 8763' Feet South of 39 Deg. 15 Min. 00 Sec.
Longitude 541' Feet West of 80 Deg. 25 Min. 00 Sec.

Company: Antero Resources Appalachian Corp

Address:	Casing & Tubing	Used in drilling	Left in well	Cement fill up Cu. Ft.
1625 17th Street Denver, CO 80202	20" 94#	40'	40'	38 Cu. Ft.
Agent: CT Corporation System	13 3/8" 48#	593'	593'	824 Cu. Ft. Class A
Inspector: Tristan Jenkins	9 5/8" 36#	2554'	2554'	1040 Cu. Ft. Class A
Date Permit Issued: 6/14/2012	5 1/2" 20#	16549'	16549'	4135 Cu. Ft. Class H
Date Well Work Commenced: 6/25/2012				
Date Well Work Completed: 11/10/2012				
Verbal Plugging: N/A				
Date Permission granted on: N/A	2 3/8" 4.7#	7135'		
Rotary <input checked="" type="checkbox"/> Cable <input type="checkbox"/> Rig <input type="checkbox"/>				
Total Vertical Depth (ft): 7011' TVD				
Total Measured Depth (ft): 16565' MD				
Fresh Water Depth (ft.): 40'				
Salt Water Depth (ft.): None available				
Is coal being mined in area (N/Y)? N				
Coal Depths (ft.): Pad constructed on reclaimed PHG strip bench				
Void(s) encountered (N/Y) Depth(s) None				

OPEN FLOW DATA (If more than two producing formations please include additional data on separate sheet)

Producing formation Marcellus Pay zone depth (ft) 6853' TVD (Top)

Gas: Initial open flow --- MCF/d Oil: Initial open flow N/A Bbl/d

Final open flow 11640 MCF/d Final open flow N/A Bbl/d

Time of open flow between initial and final tests N/A Hours

Static rock Pressure 3600 psig (surface pressure) after --- Hours

Second producing formation --- Pay zone depth (ft) ---

Gas: Initial open flow --- MCF/d Oil: Initial open flow --- Bbl/d

Final open flow --- MCF/d Final open flow --- Bbl/d

Time of open flow between initial and final tests --- Hours

Static rock Pressure --- psig (surface pressure) after --- Hours

RECEIVED

JAN 25 2013

WV GEOLOGICAL SURVEY
MORGANTOWN, WV

I certify under penalty of law that I have personally examined and am familiar with the information submitted on this document and all the attachments and that, based on my inquiry of those individuals immediately responsible for obtaining the information I believe that the information is true, accurate, and complete.

Shauna Redi
Signature

1/14/13
Date

Were core samples taken? Yes _____ No **X**

Were cuttings caught during drilling? Yes **X** No _____

Were Electrical, Mechanical or Geophysical logs recorded on this well? If yes, please list **Yes - CBL**

This is a subsequent well. Artero only runs wireline logs on the first well on a multi-well pad (Wagner Unit 1H, API# 47-033-05485). Please reference the wireline logs submitted with Form WR-35 for Wagner Unit 1H.

NOTE: IN THE AREA BELOW PUT THE FOLLOWING: 1). DETAILS OF PERFORATED INTERVALS, FRACTURING OR STIMULATING, PHYSICAL CHANGE, ETC. 2). THE WELL LOG WHICH IS A SYSTEMATIC DETAILED GEOLOGICAL RECORD OF THE TOPS AND BOTTOMS OF ALL FORMATIONS, INCLUDING COAL ENCOUNTERED BY THE WELLBORE FROM SURFACE TO TOTAL DEPTH.

Perforated Intervals, Fracturing, or Stimulating:

Perforations: 7242'-16483' (2160 holes)

Frac'd w/ 17,750 gals 15% HCL Acid, 194,348 bbls Slick Water carrying 954,909# 100 mesh, 3,601,801# 40/70 and 2,152,707# 20/40 sand.

Plug Back Details Including Plug Type and Depth(s): **N/A**

<u>Formations Encountered:</u>	<u>Top Depth</u>	<u>Bottom Depth</u>
<u>Surface:</u>		
Big Lime est.	1453'	1564'
Big Injun est.	1565'	1972'
Fifty Foot Sandstone est.	1973'	2115'
Gordon est.	2116'	2382'
Fifth Sandstone est.	2383'	2435'
Bayard est.	2436'	3089'
Speechley est.	3090'	3305'
Balltown est.	3306'	3815'
Bradford est.	3816'	4482'
Benson est.	4483'	4786'
Alexander est.	4787'	5013'
Elk est.	5014'	5541'
Rhinestreet est.	5542'	6428'
Middlesex	6429'	6532'
West River Shale	6533'	6628'
Burket	6629'	6656'
Tully	6657'	6852'
Marcellus	6853'	7011' TVD

RECEIVED

JAN 25 2013

WV GEOLOGICAL SURVEY
MORGANTHAU

Hydraulic Fracturing Fluid Product Component Information Disclosure

Fracture Date:	11/3/2012
State:	West Virginia
County:	Harrison
API Number:	47-033-05838
Operator Name:	Antero Resources
Well Name and Number:	Ora Unit 1H
Longitude:	-80.4478881
Latitude:	39.2482639
Long/Lat Projection:	NAD27
Production Type:	Gas
True Vertical Depth (TVD):	7,011
Total Water Volume (gal)*:	8,313,480

RECEIVED

JAN 25 2013

WV GEOLOGICAL SURVEY
MORGANTOWN, WV

Hydraulic Fracturing Fluid Composition:

Trade Name	Supplier	Purpose	Ingredients	Chemical Abstract Service Number (CAS #)	Maximum Ingredient Concentration in Additive (% by mass)**	Maximum Ingredient Concentration in HF Fluid (% by mass)**	Comments
Freshwater	Antero		Water	7732-18-5	100.00%	89.99181%	
Hydrochloric Acid 10-15%	GoFRAC LLC		Hydrochloric Acid	7647-01-0	15.00%	0.03487%	
100 Mesh	GoFRAC LLC		Sand		100.00%	1.37643%	
40/70 White	GoFRAC LLC		Sand		100.00%	5.23728%	
20/40 White	GoFRAC LLC		Sand		100.00%	3.10283%	
Sodium Persulfate	GoFRAC LLC		Sodium Persulfate	7775-27-1	100.00%	0.00139%	
Ferriplex 66	GoFRAC LLC		Acetic Acid	64-19-7	50.00%	0.00020%	
			Citric Acid	77-92-9	30.00%	0.00012%	
			Water	7732-18-5	35.00%	0.00014%	
Plexbreak 145	GoFRAC LLC		Cocamide Diethanolamine Salt	68603-42-9	10.00%	0.00007%	
			Diethanolamine	111-42-2	5.00%	0.00004%	
			Ethylene Glycol Monobutyl Ether	111-78-2	15.00%	0.00011%	
			Methyl Alcohol	67-58-1	15.00%	0.00011%	
			Water	732-18-5	66.00%	0.00047%	
Plexhib 256	GoFRAC LLC		Alcohol Ethoxylate Surfactants	Trade Secret	30.00%	0.00019%	
			Methyl Alcohol	67-58-1	70.00%	0.00045%	
			n-olefins	Trade Secret	10.00%	0.00006%	
			Propargyl Alcohol	107-19-7	8.00%	0.00005%	
			thiourea-formaldehyde copolymer	68527-49-1	30.00%	0.00019%	
Plexaid 673	GoFRAC LLC		Methyl Alcohol	67-58-1	25.00%	0.00417%	
			Sodium Salt of Phosphonodimethylated Diamine	Trade Secret	5.00%	0.00083%	
			Water	7732-18-5	85.00%	0.01417%	
Plexcide 15G	GoFRAC LLC		Water	7732-18-5	90.00%	0.02381%	
			Glutaraldehyde	111-30-8	14.00%	0.00370%	
			Didecyl Dimethyl Ammonium Chloride	7173-51-5	3.00%	0.00079%	

		Alkyl Dimethyl Benzyl Ammonium Chloride	68424-85-1	3.00%	0.00079%
		Ethanol	64-17-5	3.00%	0.00079%
Plexslick 921 E	GoFRAC LLC	Alcohol Ethoxylate Surfactants	Trade Secret	8.00%	0.00494%
		Hydrotreated Petroleum Distillate	64742-47-8	30.00%	0.01853%
		Polyacrylamide-co-acrylic acid	6/9/9003	32.00%	0.01977%
		Water	7732-18-5	35.00%	0.02162%
LGR-01	GoFRAC LLC	Solvent naphtha, heavy aliphatic	64742-96-7	55.00%	0.05034%
		Guar Powder	9000-30-0	45.00%	0.04118%
		Organophilic clay	mixture of 68953-58-2, 68911-87-5, 14808-60-7	3.00%	0.00275%
		Sorbitan sesquioleate	8007-43-0	4.00%	0.00366%
		Ethoxylated Alcohol	78330-21-9	2.00%	0.00183%

* Total Water Volume sources may include fresh water, produced water, and/or recycled water

** Information is based on the maximum potential for concentration and thus the total may be over 100%

Ingredient information for chemicals subject to 29 CFR 1910.1200(i) and Appendix D are obtained from suppliers Material Safety Data Sheets (MSDS)

RECEIVED

JAN 25 2013

WV GEOLOGICAL SURVEY
MORGANTOWN, WV