JE

WR-35 Rev (9-11)

## State of West Virginia Department of Environmental Protection Office of Oil and Gas Well Operator's Report of Well Work

DATE:	8/26/2013				
API#:	47-033-05668				

1050	A management of the second				
CATION: Elevation: 1358'	Quadrangle: _E	Big Isaac			
District: Union	County: Harrison				
Latitude: 1,976' Feet South of 39 Deg.	12 Min. 00 Sec.				
Longitude 4,003' Feet West of 80 Deg.	30 Min.	Sec.			
Company: Antero Resources Corporation					
Address: 1625 17th Street	Casing & Tubing	Used in drilling	Left in well	Cement fill up Cu. Ft.	
Denver, CO 80202	20" 94#	63'	63'	60 Cu. Ft. Class A	
Agent: Ct Corporation System	13 3/8" 48#	547'	547'	759 Cu. Ft. Class A	
Inspector: Sam Ward	9 5/8" 36#	2,580'	2,580'	1050 Cu. Ft. Class A	
Date Permit Issued: 9/25/2012	5 1/2" 20#	16,157'	16,157'	4011 Cu. Ft. Class H	
Date Well Work Commenced: 12/6/2012					
Date Well Work Completed: 4/11/2013	2 3/8" 4.7#	7418'			
Verbal Plugging: N/A					
Date Permission granted on: N/A					
Rotary Cable Rig					
Total Vertical Depth (ft): 7338' TVD (Deepest Point Drilled)					
Total Measured Depth (ft): 16,157' MD, 7298' TVD (BHL)					
Fresh Water Depth (ft.): 140'					
Salt Water Depth (ft.): 1936'					
Is coal being mined in area (N/Y)? No					
Coal Depths (ft.): 178', 422', 458'					
Void(s) encountered (N/Y) Depth(s) None					
PEN FLOW DATA (If more than two producing formation  Producing formation Marcellus Pay z  Gas: Initial open flow MCF/d Oil: Initial open flow	one depth (ft) 7	,306' (TOP)	ta on separate s	sheet)	
Final open flow 11,943 MCF/d Final open flow	Bb	I/d			
Time of open flow between initial and final tests				RECEIVED	
Static rock Pressure 3600 psig (surface pressure) aft	terHour	S	Off	ice of Oil and Gas	
Second producing formationPay zon	ne depth (ft)		011		
Gas: Initial open flowMCF/d Oil: Initial open flo				FEB 1 8 2014	
Final open flow MCF/d Final open flow	Bb	I/d			
Time of open flow between initial and final tests	77		4.4	/V Department of	

I certify under penalty of law that I have personally examined and am familiar with the information submitted on this document and all the attachments and that, based on my inquiry of those individuals immediately responsible for obtaining the information I believe that the information is true, accurate, and complete.

Signature

Date

05/23/2014

Were core samples taken? Yes No_>	Were	cuttings caught during drilling	ng? YesNo_X
Were Electrical, Mechanical or Geophysical	logs recorded on this well? I	fyes, please list Yes- CBL	
This is a subsequent well. Antero only runs wireline logs on the first well or	n a multi-well pad (Rodney Unit 2H API#47-033-0	/5676). Please reference the wireline logs subm	itted with Form WR-35 for Rodney Unit 2H.
The Electrical, Mechanical or Geophysical logs recorded on this well? If yes, please list Yes. CBL  This is a subsequent well. Actors only June Medical logs on the Tool well on a multi-well paid (Plothey). Unit 2H APRIAT-033-08078, Please indicate logs underthind with Form WPR-35 for Roderby Unit 2H.  OTE: IN THE AREA BELOW PUT THE FOLLOWING: I), DETAILS OF PERFORATED INTERVALS, RACTURING OR STIMULATING, PHYSICAL CHANGE, ETC. 2). THE WELL LOG WHICH IS A SYSTEMATIC DETAILED GEOLOGICAL RECORD OF THE TOPS AND BOTTOMS OF ALL FORMATIONS, INCLUDING OAL ENCOUNTERED BY THE WELLBORE FROM SURFACE TO TOTAL DEPTH.  Perforated Intervals, Fracturing, or Stimulating:  Perforations: 7,455-16,103 (1,320 Holes)  Perforations: 7,455-16,103 (1,320 Holes)  Perforations: 7,455-16,103 (1,320 Holes)  Perforations: 7,455-16,103 (1,320			
Perforated Intervals, Fracturing, or Stimulating	ng:		
Perforations: 7,455- 16,103 (1,320 H	oles)		
Frac'd w/ 11,500 gals 15% HCL Acid	, 233,196 bbls Slick Wa	ter carrying 1,356,670	# 100 mesh,
5,177,840# 40/70 sand and 3,186, 0	10# 20/40 sand.		
······································			
Plug Back Details Including Plug Type and D	Pepth(s): NI/A		
	· · · · · · · · · · · · · · · · · · ·		
Formations Encountered: Surface:	Top Depth		Bottom Depth
<b></b>	. 40001		
<u> </u>			
•			
·			
Elk	est 5194'	5936'	
Rhinestreet	est 5937'	6645'	
Sycamore	est 6646'	6944'	
Middlesex	est 6945'	7115'	
Burkett	7116'	7130'	
Tully	7131'	7244'	
Hamilton	7245'	7305'	
Marcellus	7306'	7338' TVI	D

## Hydraulic Fracturing Fluid Product Component Information Disclosure

Job Start Date:	4/3/2013
Job End Date:	4/11/2013
State:	West Virginia
County:	Harrison
API Number:	47-033-05668-00-00
Operator Name:	Antero Resources Corporation
Well Name and Number:	Utter 2H
Longitude:	-80.50681670
Latitude:	39.19728330
Datum:	NAD27
Federal/Tribal Well:	NO
True Vertical Depth:	7,306
Total Base Water Volume (gal):	9,794,442
Total Base Non Water Volume:	30,641







## Hydraulic Fracturing Fluid Composition:

Trade Name	Supplier	Purpose	Ingredients	Chemical Abstract Service Number (CAS #)	Maximum Ingredient Concentration in Additive (% by mass)**	Maximum Ingredient Concentration in HF Fluid (% by mass)**	Comments
reshwater	Antero Resources	Water					
			Water	7732-18-5	100.00000	90.70898	
0/70 White	US Silica	Propppant					
			Sand	14808-60-7	100.00000	4.91440	
0/40 White	US Silica	Propppant					
			Sand	14808-60-7	100.00000	2.92370	
00 Mesh	US Silica	Propppant					
			Sand	14808-60-7	100.00000	1.26770	
eta M-4.0	PfP	Guar Gel					
			Petroleum Distillate	64742-47-8	55.00000	0.04677	
			Guar Gum	9000-30-0	50.00000	0.04252	
			Clay	1302-78-9	5.00000	0.00425	
			Surfactant	154518-36-2	1.00000	0.00085	
lexslick 953	Chemplex	Friction Reducer					
			Water	7732-18-5	35.00000	0.02152	
			Polyacrylamide-co-acrylic acid	9003-06-9	32.00000	0.01967	
			Hydrotreated Petroleum Distillate	64742-47-8	30.00000	0.01844	
			Alcohol Ethoxylate Surfactants	Proprietary	8.00000	0.00492	

Hydrochloric Acid 10- 5%	Reagent	Acid					
770			Hydrchloric Acid	7647-01-0	15.00000	0.03424	
Plexcide 15G	Chemplex	Biocide					
			Water	7732-18-5	90.00000	0.02285	
			Glutaraldehyde	111-30-8	14.00000	0.00355	
			Alkyl Dimethyl Benzyl Ammonium Chloride	68424-85-1	3.00000	0.00076	
			Ethanol	64-17-5	3.00000	.0.00076	
			Didecyl Dimethyl Ammonium Chloride	7173-51-5	3.00000	0.00076	
exaid 673	Chemplex	Scale Inhibitor					
			Water	7732-18-5	85.00000	0.01335	
			Methyl Alcohol	67-56-1	25.00000	0.00393	
			Sodium Salt of Phosphonodimethylated Diamine	Proprietary	5.00000	0.00079	
odium Persulfate	Chemplex	Breaker					
			Sodium Persulfate	7775-27-1	100.00000	0.00123	
exhib 256	Chemplex	Corrosion					
			Methyl Alcohol	67-56-1	70.00000	0.00049	
			thiourea-formaldehyde copolymer	68527-49-1	30.00000	0.00021	
			Alcohol Ethoxylate Surfactants	Proprietary	30.00000	0.00021	
			n-olefins	Proprietary	10.00000	0.00007	
			Propargyl Alcohol	107-19-7	8.00000	0.00006	
exbreak 145	Chemplex	Non-emulsifier					
			Water	732-18-5	66.00000	0.00052	
			Ethylene Glycol Monobutyl Ethe	111-76-2	15.00000	0.00012	
			Methyl Alcohol	67-56-1	15.00000	0.00012	
			Cocamide Diethanolamine Salt	68603-42-9	10.00000	0.00008	
			Diethanolamine	111-42-2	5.00000	0.00004	
rriplex 66	Chemplex	Iron Control	N Comments				
			Acetic Acid	64-19-7	50.00000	0.00022	
			Water	7732-18-5	35.00000	0.00016	
			Citric Acid	77-92-9	30.00000	0.00013	

Note: For Field Development Products (products that begin with FDP), MSDS level only information has been provided.
Ingredient information for chemicals subject to 29 CFR 1910.1200(i) and Appendix D are obtained from suppliers Material Safety Data Sheets (MSDS)

<sup>\*</sup> Total Water Volume sources may include fresh water, produced water, and/or recycled water 
\*\* Information is based on the maximum potential for concentration and thus the total may be over 100%