

west virginia department of environmental protection

Office of Oil and Gas 601 57th Street SE Charleston, WV 25304 (304) 926-0450 (304) 926-0452 fax Earl Ray Tomblin, Governor
Randy C. Huffman, Cabinet Secretary
www.dep.wv.gov

PERMIT MODIFICATION APPROVAL

October 07, 2013

ANTERO RESOURCES APPALACHIAN CORPORATION 1625 17TH STREET, SUITE 300 DENVER, CO 80202

Re: Permit Modification Approval for API Number 3305690 , Well #: CARPENTER UNIT 2H extended lateral

Oil and Gas Operator:

The Office of Oil and Gas has reviewed the attached permit modification for the above referenced permit. The attached modification has been approved and well work may begin. Please be reminded that the oil and gas inspector is to be notified twenty-four (24) hours before permitted well work is commenced.

Please call James Martin at 304-926-0499, extension 1654 if you have any questions.

Sincerely,

Gene Smith

Regulatory/Compliance Manager

Office of Oil and Gas



June 11, 2013

Antero Resources 1625 17th Street Denver, Colorado 80202 Office 303.357.7310 Fax 303.357.7315

West Virginia Department of Environmental Protection Office of Oil and Gas Attn: Ms. Laura Cooper 601 57th Street Charleston, WV 25304

Ms. Laura Cooper:

Antero Resources Appalachian Corporation (Antero) would like to submit the following permit modifications for two approved wells on the Washbourne Pad. We are requesting to extend the horizontal lateral length which will change the bottom hole locations of the Carpenter Unit 1H (API# 47-033-05689) and Carpenter Unit 2H (API# 47-033-05690).

Attached you will find the following documents:

- REVISED Form WW-6B, which shows the revised MD and Production Casing/Cement program
- > REVISED Form WW-6A1, which shows the leases we will be drilling into
- > REVISED Mylar Plat, which shows the new bottom hole location

If you have any questions please feel free to contact me at (303) 357-7323.

Thank you in advance for your consideration.

Sincerely,

Ashlie Mihalcin

Permit Representative

Antero Resources Appalachian Corporation

Enclosures

Received Office of Oil & Gas

JUN 1 3 2013

WW - 6B (3/13)

STATE OF WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS WELL WORK PERMIT APPLICATION

				-			
1) Well Operator:	Antero Reso	ırces Appalac	hian Corporation	494488557	033-Harrison	Union	Big Isaac
1				Operator ID	County	District	Quadrangle
2) Operator's Well Number: Carpenter Unit 2H			Well Pad Name: Existing Washbourne Pad				
3 Elevation, current ground: 1292' El				evation, proposed	post-construct	tion:	1292'
4) Well Type: (a) (Gas		Oil	Undergroun	d Storage		
	Other						
(b) I	f Gas: S	hallow		Deep			
	ŀ	Iorizontal					
5) Existing Pad? Yo	es or No:	Yes					
6) Proposed Target	Formation	(s). Depth	(s). Anticipate	ed Thicknesses an	d Associated	Pressure(s):	
Marcellus Shale: 7400' TV		3 300 3				(-)	
7) Proposed Total V		_	7,400' TVD				
8) Formation at Tot	tal Vertical	Depth:	Marcellus Shale				
9) Proposed Total N	Measured D	epth:	17,500' MD				
10) Approximate F	resh Water	Strata De	pths: 11	9', 423'			
11) Method to Dete	ermine Fres	h Water D	epth: o	ffset well records. Depths I	have been adjusted a	according to surface	e elevations.
12) Approximate S	altwater De	epths:	1334'				
13) Approximate C	oal Seam I	Depths:	67', 619'				
14) Approximate D	epth to Pos	ssible Voi	d (coal mine,	karst, other):	None antici	pated	
15) Does proposed adjacent to an a				lirectly overlying and depth of mine:	or No		
16) Describe propo	sed well w	ork: _	Orill, perforate, fracti	ure a new horizontal shallo	w well and complete	Marcellus Shale	
*Antero will be air drilling	the fresh water s	ring which make	es it difficult to determ	nine when freshwater is enco	ountered, therefore we	have built in a buffe	er for the casing
setting depth which helps	to ensure that all	fresh water zor	nes are covered.				
17) Describe fractu	ring/stimul	ating metl	nods in detail	:			
Antero plans to pump Sli	ckwater into the N	Marcellus Shale	formation in order to	ready the well for production	n. The fluid will be co	mprised of approxim	nately 99 percent
water and sand, with less	than 1 percent s	pecial-purpose	additives as shown in	the attached "List of Anticip	pated Additives Used	for Fracturing or Stir	mulating Well."
						F	Received
18) Total area to be	e disturbed,	including	roads, stock	oile area, pits, etc,	(acres):	Office 15.45 acres	of Oil & Gas (existing)
19) Area to be dist	urbed for w	ell pad on	lv. less acces	s road (acres):	3.05 acres	(existing)	N 1 3 2013

WW - 6B (3/13)

20)

CASING AND TUBING PROGRAM

ТҮРЕ	Size	New or Used	Grade	Weight per ft.	FOOTAGE: For Drilling	INTERVALS: Left in Well	CEMENT: Fill -up (Cu. Ft.)
Conductor	20"	New	H-40	94#	40'	40'	CTS, 38 Cu. Ft.
Fresh Water	13-3/8"	New	J-55/H-40	54.5#/ 48#	480'	480' *see above	CTS, 667 Cu. Ft.
Coal	9-5/8"	New	J-55	36#	2595'	2595'	CTS, 1057 Cu Ft.
Intermediate							
Production	5-1/2"	New	P-110	20#	17500'	17500'	4384 Cu. Ft.
Tubing	2-3/8"	New	N-80	4.7#		7200'	
Liners							

TYPE	Size	Wellbore Diameter	Wall Thickness	Burst Pressure	Cement Type	Cement Yield
Conductor	20"	24"	0.438"	1530	Class A	1.18
Fresh Water	13-3/8"	17-1/2"	0.38"/0.33"	2730/1730	Class A	1.18
Coal	9-5/8"	12-1/4"	0.352"	3520	Class A	1.18
Intermediate						
Production	5-1/2"	8-3/4" & 8-1/2"	0.361"	12630	Lead-H/POZ & Tail - H	H/POZ-1.44 & H-1.8
Tubing	2-3/8"	4.778"	0.19"	11200		
Liners						

PACKERS

Kind:	N/A		
Sizes:	N/A		Received
Depths Set:	N/A	(Received office of Oil & Gas

JUN 1 3 2013

*Note: Attach additional sheets as needed.

21) Describe centralizer placement for each casing string. Conductor: no centralizers
	Surface Casing: one centralizer 10' above the float shoe, one on the insert float collar and one every 4th joint
	spaced up the hole to surface.
	Intermediate Casing: one centralizer above float joint, one centralizer 5' above float collar and one every 4th collar
	to surface.
	Production Casing: one centralizer at shoe joint and one every 3 joints to top of cement in intermediate casing.
22) Describe all cement additives associated with each cement type.
	Conductor: no additives, Class A cement.
	Surface: Class A cement with 2% calcium and 1/4 lb flake, 5 gallons of clay treat
	Intermediate: Class A cement with 1/4 lb of flake, 5 gallons of clay treat
	Production: Lead cement- 50/50 Class H/Poz + 1.5% salt + 1% C-45 + 0.5% C-16a + 0.2% C-12 + 0.45% C-20 + 0.05% C-51
	Production: Tail cement- Class H + 45 PPS Calcium Carbonate + 1.0% FL-160 + 0.2% ACGB-47 + 0.05% ACSA-51 + 0.2% ACR-20
23) Proposed borehole conditioning procedures. Conductor: blowhole clean with air, run casing, 10 bbls fresh water.
	Surface: blowhole clean with air, trip to conductor shoe, trip to bottom, blowhole clean with air, trip out, run casing,
	circulate pipe capacity + 40 bbls fresh water followed by 25 bbls bentonite mud, 10 bbls fresh water spacer.
	Intermediate: blowhole clean with air, trip to surface casing shoe, trip to bottom, blowhole clean with air, trip out, run casing,
	circulate 40 bbls brine water followed by 10 bbls fresh water and 25 bbls bentonite mud, pump 10 bbls fresh water.
	Production: circulate with 14 lb/gal NaCl mud, trip to middle of lateral, circulate, pump high viscosity sweep, trip to base of curve,
	pump high viscosity sweep, trip to top of curve, trip to bottom, circulate, pump high viscosity sweep, trip out, run casing,
	circulate 10 bbls fresh water nump 48 bbls harite nill, nump 10 bbls fresh water followed by 48 bbls mud flush and 10 bbls water

Received Office of Oil & Gas

JUN 1 3 2013





