

THE OFFICE OF THE ENGINEER IN CHARGE OF THE SURVEYING DEPARTMENT OF THE STATE OF TEXAS
 HAS CONSIDERED THE REPORT OF SAID ENGINEER AND HAS THIS DAY CERTIFIED THAT THE SAID
 MICHAEL DOLAN
 TEN MILE
 HARRISON
 DATE



LEGEND

- Location
- Oil Well
- " " Aband.
- ⊗ Gas Well
- " " Aband.
- Dry Hole

Field Book No. 576-PRC-20
 Scale 1" = 40' Chas.
 July 26th 1904

8/12/18

S.F.R. Map No. 653 and July 1904

Stephen Pitts
 ENGINEERS CERTIFICATE

I, the undersigned, hereby certify that this map is correct and shows all the information to the best of my knowledge and belief, except for the oil and gas notes of the private firm of Messrs. [Name]

WEST VIRGINIA DEPARTMENT OF MINES

OIL AND GAS DIVISION

PRELIMINARY DATA SHEET NO. 1

File No. _____

Well No. 1 (558)

J. M. Read & Wm. Jones Company of Salem, W. Va.,
 on the Michael Dean Farm
 containing 315 acres. Location _____

Ten Mile District, in Harrison County, West Virginia

The surface of the above tract is owned in fee by Wolf Summit Coal Company
 of Clarksburg, W. Va., Carl L. Horner, Agent, address, and the mineral rights are owned by
Wolfsummit Coal Company of Clarksburg, W. Va.,

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit
 No. _____ issued by the West Virginia Department of Mines, Oil and Gas Division
 _____ 193 _____

Elevation of surface at top of well, 1446' Spirit
 Barometer.

The number of feet of the different sized casings used in the well.

_____	feet	_____	size,	_____	Wood conductor.
<u>348</u>	feet	<u>10"</u>	size, csg.	<u>1158</u>	feet <u>8 1/2"</u> sized csg.
<u>1679</u>	feet	<u>6-5/8"</u>	size, csg.	<u>2405</u>	feet <u>5-3/16"</u> sized csg.
<u>3451</u>	feet	<u>2"</u>	size, csg.	<u>419</u>	feet <u>4" liner</u> <u>2385 to 2804'</u> <u>Cave Wall Liner</u> packer at <u>2385 & 2804</u> sized csg.
_____	packer of	_____	size, set at	_____	_____
_____	packer of	_____	size, set at	_____	_____
_____	, in casing perforated at	_____	feet to	_____	feet.
_____	, in casing perforated at	_____	feet to	_____	feet.

Coal was encountered at 298 feet, thickness 84 inches, and at _____
 feet; thickness _____ inches; and at _____ feet; thickness _____ inches.

Liners were used as follows: (Give details) _____

July 30th, 1934.

Date.

J. M. Read & Wm. Jones

J. M. Reed & Co., Inc.

Company

COMPLETION DATA SHEET

Salina, J. Va.,

Address

NO 2

Well No.

21146-208 A

FORMATION RECORD

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
Pittsburgh Coal				398	405	7'		348
Little Dunkard Sand				838	850	15'		
Big Dunkard Sand				873	980	102'		
Gas Sand				1040	1110	70'		
First Salt Sand				1130	1190	60'		1151-1152
Second Salt Sand				1230	1290	70'		
Maxon Sand				1485	1490	5'		
Little Lime				1530	1545	15'		
Pencil Cave				1545	1600	15'		
Big Lime				1600	1660	60'		1639-639
Big Injun Sand				1667	1780	113'		
Squaw Sand				1888	1903	15'		
		Gas	1888-1903					
Gantz Sand				2030	2100	70'		
Fifty Foot Sand				2235	2300	45'		
Thirty Foot Sand				2330	2360	30'		
Gordon Stray Sand				2375	2390	15'		
Gordon Sand				2405	2430	25'		2-115-5 1/2"
Fourth Sand		show gas	2425	2440	2450	10'		
Fifth Sand				2744	2750	14'		
		Gas	2746-2750					
Shell				3345				419'-4 1/2"
		Gas	3345					
Shell				3391	3394	3'		
		Gas	3391-3394					
Speechley Sand				3431	3435	4'		3451 1/2 - 2"
		Oil	3431-3435					
							3458'	

shot

Well was not shot at feet; well was shot at 3458-3445 feet.

Fresh water at Not recorded salt
feet; fresh water at Not recorded feet.Well was producing
dry hols. Now exhausted to extent that it is no longer commercially productive.

**AFFIDAVIT IN TRIPPLICATE TO TIME AND MANNER OF
PLUGGING AND FILLING WELL**

(REQUIRED BY SECTION 10, CHAPTER 20, CODE 1922)

**WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS SECTION**

Wolf Summit Coal Company,
COAL OPERATOR

J. M. Raad & Ws. Moses
NAME OF WELL OPERATOR

Clarksburg, W. Va., * Carl L. Korman.
ADDRESS

Salem, W. Va.,
COMPLETE ADDRESS

COAL OPERATOR

Aug. 1st, 1935.
WELL AND LOCATION

ADDRESS

Ten Mile District

COAL OPERATOR

Harrison County

ADDRESS

Well No. #1. (H.C. & R. Co.'s No. 658)

Michael Dolan Farm

AFFIDAVIT TO BE MADE IN TRIPPLICATE: ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES

AFFIDAVIT

STATE OF WEST VIRGINIA,

COUNTY OF HARRISON,

} ss: **B.A. MITCHELL & A.G. PARKER**

and

being first duly sworn according to law depose and say that they are experienced in the work of plugging

and filling oil and gas wells and were employed by RAAD & MOSES, well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the

day of AUG, 1934, and that the well was plugged and filled in the following manner:

Manner in which sand was plugged: Filled hole with Clay and Mud to 3325-20 above shell and placed cement Plug ✓ INSTALLED Permanent bridge at 2780-30 below Fifth sand and filled hole with mud & Clay to 2415'-10 below where 5-3/16 casing was set, placed Wood plug and removed 5-3/16 casing. Installed permanent bridge at 1933-30' below big injun sand and filled hole with mud & Clay to 1689'-10' below where 6-5/8 casing was set, placed cement plug ✓ INSTALLED permanent bridge at 1310-20' below salt sand and filled hole with mud & Clay to 1168-10' below where 8 1/2 casing was set, placed Cement plug ✓ and removed 8 1/2 casing and continued billing with mud to 1120-20' above salt sand and placed wood plug ✓ INSTALLED bridge at 900' and filled with mud & Clay to 815' and placed cement plug, then filled with mud & Clay to 435-30' below Pittsburgh Coal seam, then filled with cement to 378-20' above Pitts. Coal Seam. removed 30 Feet of 10" Casing and filled hole from 378 to the surface with mud and clay and concrete monument erected over the hole.

Monument, 30 x 30 square and twelve inches deep with cement post in the center twenty two inches high. and the name written in the cement as follows,

Description of monument:

RAAD & MOSES" DOLAN #1, AUGUST 1st 1934 .

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, OIL AND GAS ACT OF 1922.)
and that the work of plugging and filling said well was completed on the.....day of AUGUST,

1934..a

And further deponent not not.



B.A. Mitchell