

LATITUDE 39° 15' 00"

LONGITUDE 80° 27' 30"



1.652

1.290

7'5 OGIS topo location

7.5' loc _____

15' loc _____
(calc.) _____

Company Raad & Moses

Farm Tanner Payne I

(Formerly HC & R Co # 1035)

Quad West Milford 7'12

County Harrison

District Union

WELL LOCATION MAP

File No. 033 - 30255

OIL AND GAS DIVISION

PRELIMINARY DATA SHEET NO. 1

File No. _____

Well No. 1035J. M. Reed & Wm. Moore

Company of

Selen, W. Va.

on the

Truman Payne

Farm

containing 100

acres. Location

Union

District, in

Harrison

County, West Virginia

The surface of the above tract is owned in fee by

of _____ address, and the mineral rights are owned by

of _____

The oil and gas privileges are held under lease by the above named company, and this well is drilled under permit

No. _____ issued by the West Virginia Department of Mines, Oil and Gas Division

_____ 193 _____

Elevation of surface at top of well, _____

Spirit
Barometric

The number of feet of the different sized casings used in the well.

feet

size. Wood conductor

803

feet

8 1/2"

size, csg.

1715

feet

6-5/8"

sized csg.

2332

feet

5-5/16"

size, csg.

3285

feet

2"

sized csg.

feet

size, csg.

feet

sized csg.

packer of _____

size, set at _____

packer of _____

size, set at _____

, in casing perforated at _____

feet to _____

feet

, in casing perforated at _____

feet to _____

feet

Coal was encountered at 235 feet, thickness 96 inches, and at _____

feet; thickness _____

inches; and at _____

feet; thickness _____

inches

Liners were used as follows: (Give details) _____

Date _____

Approved J. M. Reed & Wm. Moore

Checked _____

Name	Color	Character	Oil, Gas or Water	Top	Bottom	Thickness	Total Depth	Remarks
Pittsburgh Coal				235	243	8'		
Big Bankard Sand				750	798	48'		
First Salt Sand				958	1024	66'		
Second Salt Sand				1034	1095	61'		
Maxon Sand				1585	1610	25'		
Little Linn				1615	1630	15'		
Pencil Cove				1630	1652	22'		
Big Linn				1652	1715	63'		
Big Injun Sand				1715	1814	99'		
Gantz Sand				2050	2082	32'		
Fifty Foot Sand				2160	2180	20'		
Thirty Foot Sand				2265	2295	30'		
Gordon Stray Sand			Oil--2322	2325	2335	10'		
Gordon Sand			Gas-2369	2345	2415	70'		
Fifth Sand			Gas-2559-2567	2558	2571	13'		
Speckley Sand			Oil and Gas-3257-3265	3257	3267	10'	3265	

shot
Well was not shot at 2568-2568 feet; well was shot at 3257-3265 feet.

and
Fresh water at Not recorded feet; salt
fresh water at Not recorded feet.

producing
Well was hole Exhausted.

WEST VIRGINIA DEPARTMENT OF MINES
OIL AND GAS DIVISION

No Coal Operations in vicinity

Road & Moses.

COAL OPERATOR OR OWNER

NAME OF WELL OPERATOR

Boles, W. Va.

ADDRESS

COMPLETE ADDRESS

COAL OPERATOR OR OWNER

WELL AND LOCATION

ADDRESS

Union

District

LEASE OR PROPERTY OWNER

Harrison

County

Well No. (HC&RG. #1035)

ADDRESS

Truman Payne

Farm

NOTE: IT TO BE MADE IN TRIPlicate, ONE COPY TO BE MAILED BY REGISTERED MAIL TO THE DEPARTMENT, ONE COPY TO BE RETAINED BY THE WELL OPERATOR AND THE THIRD COPY (AND EXTRA COPIES IF REQUIRED) TO BE MAILED TO EACH COAL OPERATOR ABOVE NAMED AT THEIR RESPECTIVE ADDRESSES

AFFIDAVIT

STATE OF WEST VIRGINIA,

County of Harrison

ss:

Burt Mitchell and A.G. Farner,
being first duly sworn according to law depose and say that they are experienced in the work of plugging

and filling oil and gas wells and were employed by Road & MOSES, well operator,
and participated in the work of plugging and filling the above well, that said work was commenced on the

day of June, 1935, and that the well was plugged and filled in
the following manner:

Manner in which sand was plugged: Removed tubing and filled hole with clay mud
to 3237'-20" above Speechley sand and placed wood plug.

Installed permanent bridge at 2601'-30" below fifty sand and
filled with clay to 2350" placed wood plug and cement and removed
5-3/16 casing which was set at 2332; continued filling to 2245'-20"
above thirty foot sand and placed cement plug.

Installed permanent bridge at 1844'-30" below Big Injun Sand
and filled with clay to 1725'-10" below where 6-5/8 casing was
set, placed wood plug and removed 6-5/8 casing.

Manner in which coal was plugged: Installed permanent bridge at 1115'-20"
below salt sand and filled with clay to 813'-10" below where 8"
casing was set, placed wood plug and removed casing.

Installed permanent bridge at 273'-30" below Pittsburgh Coal
seam, then filled with cement to 215'-20" above coal seam, and
from that point to the surface the hole filled with clay.

Description of monument: Thirty inches square by 12" deep erected with
cement post 8" Square and three feet high with the following
wording ROAD & MOSES, PAYNE #1 JULY 1935.

(THE ABOVE DESCRIPTIONS MUST BE IN DETAIL AND IN ACCORDANCE WITH THE PROVISIONS OF SECTION 10, ARTICLE 4, CHAPTER 52 OF THE CODE)

and that the work of plugging and filling said well was completed on the _____ day of July,

1935.

And further deponents saith not

Burt Mitchell