



346A

0772  
 Ten Mile District, Harrison County, W. Va.  
 By South Penn Oil Co., C. of C. Bldg., Pittsburgh, Pa.  
 On 57½ acres, on Ten Mile Creek; surface owned by Ralph Snider,  
 Wolf Summit, W. Va., and minerals by Will E. Morris, et al.,  
 Parkersburg, W. Va.

Elevation, 1242.90' L.

Drilling commenced Aug. 2, 1919; completed, Oct. 1, 1919.

Rock pressure, 70 lbs. in 24 hrs.

Fresh water at 150'.

10" casing, 229' 6" (pulled); 8½", 1110'; 6¾", 1969'; 16' conductor.

Coal was encountered at 255-260 and 528-536'.

Gas well. Abandonment reported to Dept. of Mines Oct. 9, 1936.

Record to RGT from D. G. Courtney (Dept. of Mines) 5-5-37.

	Top.	Bottom.
Water at 150'.		
Bluff Sand	185	- 240
Native coal	255	- 260
Pittsburgh Coal	528	- 536
Little Dunkard Sand	962	- 997
Big Dunkard Sand	1087	- 1117
Gas Sand	1240	- 1315
1st Salt Sand	1448	- 1503
2nd Salt Sand	1693	- 1764
Big Line	1897	- 1980
Big Injun Sand	1980	- 2040
Squaw Sand	2090	- 2190
50-Ft. Sand	2418	- 2436
30-Ft. Sand	2519	- 2551
Gordon Stray Sand	2567	- 2590
Gordon Sand (gas, 2606'; 10/10 W. 2") <sup>183 M c f</sup>	2597	- 2630
Fourth Sand (gas, 2643'; 22/10 W. 2") <sup>198 M c f</sup>		
gas, 2679'; 32/10 W. in 3") <sup>587 M c f</sup>	2640	- 2697
Total depth		2771

300

WEST VIRGINIA DEPARTMENT OF MINES  
OIL AND GAS DIVISION

WELL RECORD

Permit No. HAR-346-A

Oil or Gas Well GAS  
(Kind)

Company South Penn Oil Company  
 Address C. of C. Bldg. Pittsburgh, Pa.  
 Farm Matilda Matheny Acres 57 1/2  
 Location (waters) Ten Mile Creek  
 Well No. 4 Elev. 1242.90'  
 District Ten Mile County Harrison  
 The surface of tract is owned in fee by Ralph Snider  
 Address Wolf Summit, W. Va.  
 Mineral rights are owned by Will E. Morris  
 et al Address Parkersburg, W. Va.  
 Drilling commenced Aug. 2, 1919  
 Drilling completed Oct. 1, 1919  
 Date shot --- Depth of shot ---  
 Open Flow 150 /10ths Water in See below for Inch  
various tests /10ths Merc. m. --- Inch  
 Volume 70 Cu. Ft. 24 lbs. --- hrs.  
 Rock Pressure --- lbs. --- hrs.  
 Oil --- bbls., 1st 24 hrs.  
 Fresh water --- feet  
 Salt water --- feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
16			Kind of Packer
13			
10	<u>229' 6" (Pulled)</u>		Size of
8 1/4	<u>1110</u>	<u>1110</u>	
6 5/8	<u>1959</u>	<u>1969</u>	Depth set
5 3/16			
3			Perf. top
2			Perf. bottom
Liners Used			Perf. top
<u>Conductor</u>	<u>16</u>		Perf. bottom

CASING CEMENTED --- SIZE --- No. FT. --- Date ---  
 COAL WAS ENCOUNTERED AT 255 FEET 50 INCHES  
528 FEET 96 INCHES FEET INCHES  
 FEET INCHES FEET INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil Gas or Water	Depth Found	Remarks
Bluff Sand			185	240	Water	150	
Native Coal			255	260			
Pittsburgh Coal			528	536			
Little Dunkard Sand			962	997			
Big Dunkard Sand			1087	1117			
Gas Sand			1240	1325			
1st Salt Sand			1448	1503			
2nd Salt Sand			1693	1764			
Big Lime			1897	1980			
Big Injun			1980	2040			
Squaw			2090	2190			
Fifty Foot Sand			2418	2436			
Thirty Foot Sand			2519	2551			
Gordon Stray Sand			2567	2590			
Gordon Sand			2597	2630			
Fourth Sand			2640	2697	Gas	2606	10/10 Water 2" 133 mt
					Gas	2643	22/10 Water 2" 198 mt
					Gas	2679	32/10 Water 3" 537 mt
Total Depth				2771			





