



Mary E. Gower Lease  
 0 1/2 %<sup>ac</sup>  
 Dora E. Campbell (surface)

Surface owned by Dora E. Campbell  
 Address: Mrs. Dora E. Campbell, P.O. Box 148, Reynoldsville,  
 No. Coal. W. Va.

- New Location
- Drill Deeper
- Abandonment

On 800 Map N20E S9S 312E 10.

Company	William Moses
Address	Salem, W. Va.
Farm	Mary E. Gower
Tract	Acres 0 1/2 % <sup>ac</sup> Lease No.
Well (Farm) No. 1	Serial No. 107875

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. 458-15448



LOCATED

MARY E. GOWER NO. 1 WELL.

Coal District, Harrison County, W. Va.

By Wm. Moses, Salem, W. Va.

Abandoned under permit Har-.....-A?

On.....acres.

Elevation, .....' L.

Drilling completed July 1915.

6 $\frac{5}{8}$ " casing, 1800'; 2" tubing, 2000'; all left in.

Gas? well. Record to Dept. of Mines stamped Feb. 21, 1952.

Record to RCT from Mrs. Griffith July 9, 1952. O.F.No.1388.

1544A

	Top.	Bottom.
Dunkard Sand	500	- 650
Big Injun Sand	1400	- 1505
Garden Sand	2060	- 2090
Total depth		2250

*map*



1388

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

WELL RECORD

Permit No. HAR-1544A

Oil or Gas Well (KIND)

Company Wm. Jones  
 Address Salem, W. Va.  
 Farm Mary B. Gower Acres  
 Location (waters) \_\_\_\_\_  
 Well No. One Elev. \_\_\_\_\_  
 District Coal County Harrison  
 The surface of tract is owned in fee by \_\_\_\_\_  
 Address \_\_\_\_\_  
 Mineral rights are owned by \_\_\_\_\_  
 Address \_\_\_\_\_  
 Drilling commenced \_\_\_\_\_  
 Drilling completed July 1952  
 Date Shot From \_\_\_\_\_ To \_\_\_\_\_  
 With \_\_\_\_\_  
 Open Flow /10ths Water in \_\_\_\_\_ Inch  
 /10ths Merc. in \_\_\_\_\_ Inch  
 Volume \_\_\_\_\_ Cu. Ft.  
 Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
 Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
 Fresh water \_\_\_\_\_ feet \_\_\_\_\_ feet  
 Salt water \_\_\_\_\_ feet \_\_\_\_\_ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			
10			Size of
8 1/4			
6 1/2		1800	Depth set
5 3/16			
3			Perf. top
2		2000	Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_  
 COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Dunkard			500	650			
Injun			1400	1505			
Gordon			2060	2090			
Total				2250			

