



New Location   
 Drill Deeper   
 Abandonment  7927

By - Richard Jackson  
 @ Clarksburg, W. Va.

FORMERLY H. N. G. Co. WELL No 7927

Company	<u>A. M. SNIDER</u>
Address	<u>HUNDRED, W. VA.</u>
Farm	<u>JAMES MONROE</u>
Tract	Acres <u>185</u> Lease No. <u>52677</u>
Well (Farm) No.	Serial No. <u>7927</u>
Elevation (Spirit Level)	<u>1146'</u>
Quadrangle	<u>Clarksburg</u>
County	<u>HARRISON</u> District <u>CLARK</u>
Engineer	<u>HENRY A. HAIN</u>
Engineer's Registration No.	<u>3150</u>
File No.	<u>A.M.S-12-60</u> Drawing No. _____
Date	<u>JAN. 25, 1960</u> Scale <u>1" = 40 FEET</u>

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

**WELL LOCATION MAP**  
 FILE NO. HAR-1738-A

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.



1814

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

Quadrangle Clarksburg

Permit No. 1738-A

WELL RECORD

Oil or Gas Well  (KIND)

Company Richard Jackson, Inc.  
Address 614 East Main St., Clarksburg, W. Va.  
Farm James Monroe Acres 185  
Location (waters) \_\_\_\_\_  
Well No. 7987 (Hope) Elev. 1145  
District Clark County Harrison  
The surface of tract is owned in fee by Same  
Address Clarksburg, W. Va.  
Mineral rights are owned by Same  
Address \_\_\_\_\_

Drilling commenced Jan. 16, 1914  
Drilling completed March 18, 1914  
Date Shot in Speerley sand  
With \_\_\_\_\_

Open Flow \_\_\_\_\_ /10ths Water in \_\_\_\_\_ Inch  
\_\_\_\_\_ /10ths Merc. in \_\_\_\_\_ Inch  
Volume \_\_\_\_\_ Cu. Ft.  
Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
Oil \_\_\_\_\_ bbls., 1st 24 hrs.  
WELL ACIDIZED \_\_\_\_\_  
WELL FRACTURED \_\_\_\_\_

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			
10	175	175	6x10 A.L. 919
8 3/4	207	207	Size of 6x8 B.H. 1322
6 5/8	1822	1822	2x8 A. 2136-9"
5 3/16	2130	2130	Depth set
3			2x8 B.H. 2040
2	3012	3012	Perf. top 6x8 B.H.
Liners Used			Perf. bottom
			Perf. top
			Perf. bottom

CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_

COAL WAS ENCOUNTERED AT \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES  
\_\_\_\_\_ FEET \_\_\_\_\_ INCHES FEET \_\_\_\_\_ INCHES

RESULT AFTER TREATMENT \_\_\_\_\_  
ROCK PRESSURE AFTER TREATMENT \_\_\_\_\_  
Fresh Water \_\_\_\_\_ Feet \_\_\_\_\_ Salt Water \_\_\_\_\_ Feet \_\_\_\_\_

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth	Remarks
<b>Below Coal</b>							
Dunkard Sand			306	434			
Salt Sand			720	915			
Monro Sand			1060	1110	Water 900'		
Injun Sand			1360	1465	Water 1110'		
Berea Sand			1620	1638			
Ganta Sand			1760	1766			
Fifty ft Sand			1840	1862			
Thirty ft Sand			1896	1958	Gas 1875'		
Gordon Sand			2100	2146			
Fourth Sand			2190	2211	Gas 1944'		
Fifth Sand			2256	2276			
Speerley S			2372	2383	Gas 2265'		
Total Depth				2306			
Deeper				2384			

RECEIVED  
JUN 29 1960  
WEST VIRGINIA  
DEPT. OF MINES