

PETER I. LYNCH NO. 1 WELL.

70122
NOT LOCATED
 577-A?

Union District, Harrison County, W. Va.

By.....

George Rinchart, Contractor.

Drilling completed Dec. 20, 1910.

10" casing, 125' (pulled); 8 1/2" casing, 843' (pulled); 6 3/8" casing, 1410'; 5 1/8" casing, 1550';
 3" tubing, 2312'.

Top perforation, 2263'; top of anchor, 2155'; top of packer, 2151'.

Well tubed with 3" tubing.

Top of 30-qt. shot, 2260'; bottom of 30-qt. shot, 2263'.

Well cleaned out. Finished Oct. 1, 1917. 2" tubing run in well, 2309'.

6 3/8" x 2" Spang anchor packer, set at 2154'; top of perforation, 2264'.

5" casing and packer run Nov. 1924; tubed Jan. 17, 1925.

2" tubing, 2340'. Top of perforation, 2263'; bottom, 2280'.

Tubing packer set at 1524'. 36 ft. small hole bit out of gauge.

Record in Eastern Petroleum Co. Well Record book of Clifton Oil & Gas Co.

	Top.	Bottom.
Conductor	0	16
Slate and shell	75	490
Little Duckard Sand	490	530
Slate and lime shell	530	655
Big Duckard Sand	655	675
Slate and lime shell	675	690
Sandy lime (1/2 bailers water at 700')	690	775
White lime	775	920
Slate	920	930
Lime	930	975
Slate and lime shell	975	1120
Red rock	1120	1140
Slate and lime shell	1140	1210
Sand	1210	1280
Black slate	1280	1295
Little Lime	1295	1310
Pencil Cave	1310	1335
Big Lime	1335	1410
Big Injun Sand	1410	1530
Slate	1530	1535
Squaw Sand	1535	1565
Slate and lime	1565	1745
Fifty-foot Sand	1745	1790
Slate	1790	1965
Gordon Sand	1965	1983
Slate and lime	1983	2100
Sand	2100	2128
Slate	2128	2130
Sand	2130	2170
Slate and lime	2170	2262
Fifth Sand	2262	2280
Total depth		2309
Total depth (after cleaning out?)		2345