



New Location X  
 Drill Deeper  
 Abandonment

Company R.E. MCCABE  
 Address CHARLESTON, W.VA.  
 Farm E.W. BOGGESS MRS. & R.L. FISHER  
 Tract \_\_\_\_\_ Acres 128 Lease No. \_\_\_\_\_  
 Well (Farm) No. ONE Serial No. \_\_\_\_\_  
 Elevation (Spirit Level) 656.0  
 Quadrangle KENNA - SW  
 County JACKSON District RIPLEY  
 Engineer C. B. Holsclaw  
 Engineer's Registration No. 250  
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_  
 Date FEB. 17, 1940 Scale 1" = 600'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. JAC-72-71

+ Denotes location of well on United States Topographic Maps; scale 1 to 62,500. latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing

6-6-1940

WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
W E L L R E C O R D

Gas Well

Permit No. Jac-71  
Kenna Quad.

CASING & LIFTING

Company	R. E. McCabe	13	63-7
Address	Charleston, W. Va.	10	704-3 704-3
Farm	Bogness-Fisher ACRES 128	8-1/4	1246 1246
Location	Duddeon Fork	7	4353 4353
Well No.	1 ELEV. 633.3 DF	2	4363 4363
District	Ripley - Jackson County		
Surface	R. L. Fisher, Kenna, W. Va.		4353 feet of 7" cemented
Mineral	E. W. Bogness Mrs. & R. L. Fisher		with 25 sacks of cement
Commenced	March 28, 1940		5/31/40
Completed	June 14, 1940		
Shot	6/19/40 - Depth 4995		
Open Flow	22/10ths Water in 7" OD 5/10ths Merc. in 7" OD		
Volume	3,500,000 c.f.		
Rock Pressure	1720 lbs. 30 days		
Water	-		

Soil	0	10	Berea Grit	2250	2260	
Red Rock	10	55	Slate & Shells	2250	3465	Show Gas
Blue Lime	55	60				3465
Blue Slate	60	70	Shale	3465	3525	
Red Rock	70	75	Slate & Shells	3525	3930	
Gray Slate	75	100	Brown Shale	3930	4075	
Blue Lime	100	135	White Slate	4075	4555	
White Slate	135	170	Brown Shale	4555	4838	Gas 4555
Red Rock	170	200	Corniferous Lime	4838	4948	
Slate	200	240	Oriskany Sand	4948	4992	
Sand	240	270	Black Lime	4992		
White Slate	270	285	Total Depth		4992	
Red Rock	285	310				
Lime	310	355	Gas 4952 - 2,023,000 ft.			
Red Rock	355	420	Blow down 499,000			
Lime	420	488	Gas 4971-4974 - 1,057,000			
Red Rock	488	506	Blow Down 381,000			
Lime	506	607	Filled Back 4975			
Slate	607	630	Shot 30 qts. nitroglycerin			
R.D. Sand	630	740	4953-4974 lift. anchor			
Slate & Shell	740	845	Test 1 hr after shot 3,559,000			
Slate	845	875	30 day rock pressure 1720#			
Sand	875	936				
Slate	936	960				
Sand Broken	960	1100				
Slate	1100	1245				
Sand	1245	1285				
Slate	1285	1300				
Sand - Salt Sand	1300	1525	Water 1370-1403 - Salt Sand			
White Slate	1525	1528				
Sand	1528	1573				
Slate & Shell	1573	1588				
Sand Gray	1588	1593				
Slate Black	1593	1610				
Big Lime	1610	1765				
Injun	1765	1803				
Slate	1803	1808				
Squaw Sand	1808	1830				
Slate	1830	1835				
Sand	1835	1840				
Slate	1840	1845				
Lime	1845	1850				
Slate & Shells	1850	2190				
Lime	2190	2200				
Blue Slate	2200	2240				
Brown Shale	2240	2250	Gas 2250-2260			