



2.47-5  
 2.48  
 3.85-W  
 3.81-W

New Location   
 Drill Deeper   
 Abandonment

Company	MULLINS GAS CO.
Address	CHARLESTON W.VA.
Farm	C. C. BOARD
Tract	Acres 58 Lease No.
Well (Farm) No.	1 Serial No. 1
Elevation (BAROMETER)	690
Quadrangle	RIPLEY SC
County	JACKSON District RIPLEY
Engineer	<i>E. J. ...</i>
Engineer's Registration No.	659
File No.	60-89 Drawing No.
Date	OCT. 14, 1941 Scale 1" = 660'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

**WELL LOCATION MAP**  
 FILE NO. JAC-226

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
W E L L R E C O R D

Permit No. Jac-226

Company	Mullins Gas Co.	Dry Hole		
Address	507 Kan. Bank & Tr. Bldg., Chas. W. Va.	CASING & TUBING		
Farm	C.C. Board et al Acces 50	18	74	74
Location	Mill Creek	16	205	--
Well No	1	13	625'5	--
District	Ripley	10	982'10	--
Surface	Jackson County	8	1971'5	1971'5
Mineral	C.C. Board et al, Dunbar, W. Va.	7	4888	4888
Commenced	Oct. 31, 1941			Step B.H. Packer
Completed	Jan. 31, 1942			Size 8 5/8x10"
Shot	Jan. 31, 1942			Depth 1971'5"
Volume	Dry Hole			
Oil	1/2 bbl. in 44 hrs.			7" casing cemented
Fresh Water	174 ( 4 blrs. 1 hr.)			25 sacks Hi-Early
Salt Water	1650 4 blrs.; 1695' Hole Full			

Slate & Red Rock	0	90	Slate	Dk	1335	1380
Sand	90	95	Sand		1380	1395
White Slate	95	115	Broken Sand	Bk	1395	1475
Red Rock	115	130	Lime		1475	1480
Sand	130	195	Dark Slate		1480	1490
White Slate	195	205	Salt Sand		1490	1710
Red Rock	205	210	Maxon Sand		1710	1835
Sand	210	236	Big Limo		1835	1890
White Slate	236	242	Shale		1890	1895
Red Rock	242	252	Sand In Jun		1895	1973
Slate & Shell	252	275	Break	Black	1973	1977
<del>Red Rock</del>	275	303	Limo		1977	1992
White Slate	303	318	Shale	Dk	1992	2030
Sand	318	343	White Slate		2030	2100
Red Rock	343	355	Black Slate		2100	2120
Slate & Shell	355	390	Gray Slate		2120	2340
Red Rock	390	410	Berea Grit		2340	2348
Sand	410	440	White Slate		2348	2400
White Slate	440	450	Black Slate & Shells		2400	2450
Sand	450	465	Gray Shale & Slate		2450	2916
Lime	465	470	Black Slate		2915	3100
Wh. Slate & Shells	470	560	Blue & Gr. Shale		3100	3580
Sand	560	585	Brown Shale - 441		3580	3650
Slate & Shell	585	605	Brown Shale & Shells		3650	3680
Red Rock	605	625	Gray Slate		3680	3850
Slate & Shells	625	640	Brown Shale		3850	3985
Red Rock	640	660	Gray Shale		3985	4005
Sand	660	692	Brown Shale		4005	4180
Pink Rock	692	708	White Slate		4180	4280
Red Rock	708	735	Brown Shale		4280	4475
White Slate	735	765	White Slate		4475	4565
Sand	765	800	Dark Slate		4565	4680
Slate & Red Rock	800	880	Brown Shale		4680	4690
Sand	880	895	Gray Shale		4690	4800
White Slate	895	900	Black Shale - MARCELLUS		4800	4872
Pink Rock	900	920	Corniferous Lino	AD	4872	4978 SLM
Slate & Shells	920	1065	Oriskany Sand		4978	
Sand	1065	1145	TOTAL DEPTH			5020
Lime	1145	1155				
Slate Gr	1155	1215	Gas Show 2343'	SLM 6/10 W 1"	25 M	
Slate Bk	1215	1265	GAS AND OIL RECORD			
Shale Br	1265	1280	Gas	4978-4979		
Sand Shells	1280	1320	Show of Oil	4981-1/2 to 4986--1 blr.		
Slate Gr	1320	1325	in 2 hrs.			
Lime	1325	1335	Gas	4986-4989		

Shot from 4977-4993 with 60 qts. of glycorine.

4872 4978  
663 663  
4209 4315