



*Abandoned
April 47*

*155
389
3,85-W*

New Location X
Drill Deeper
Abandonment

Company Godfrey L. Cabot, Inc.
 Address 900 Union Bldg. Charleston, W. Va.
 Farm The Putnam Company
 Tract Part of Acres 22,900[±] Lease No. 3-464
 Well (Farm) No. 30 Serial No. 1020
 Elevation (Spirit Level) 849.
 Quadrangle Kenna N.W. C
 County Jackson District Ripley
 Engineer Charles Neely Sturm
 Engineer's Registration No. 375
 File No. _____ Drawing No. _____
 Date Oct. 20, 1941 Scale 1" = 1320'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. JAC-230

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.
 - Denotes one inch spaces on border line of original tracing.

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No.	JAC-230	Gas Well	
Company	Godfrey L. Cabot, Inc.	Casing Record	
Address	Charleston, W. Va.	10 3/4"	886 886
Farm	Putnam Company	8 5/8"	2089 -
Well No.	30	Serial No.	1020
District	Ripley	Elev.	356
Commenced	12-2-41	7"	5056 5056
Completed	3-18-42	2 3/8"	5203 5203 Bot./
Shot	3-22-42	joint welded.	
		1 - 10 3/4"x12" Casing	
		shoo.	
Volume	B.S. 539 M.C.F.; 1 hr. A.S. 1,583 M.C.F.	1 - 8 5/8" B.H.Packer 53	
Rock Pressure	1625 lbs. in 19 hrs. Orisk. Sand Test Cas.	sacks Aquagel	
Fresh water	170' 1/2 Blr. per hr.	1 - 7" OD. Sp. Orisk. B.H.	
Salt water	1000' 3 blrs. per hr.	Packer 40 sacks aqua- gel	

Soil	0	15-Corn. Lime	5036	5134	Tubed & Shut in 4-1-42
Red Rock	15	130-Oriskany	5134	5168	Tubed under line pressure
Slate, Bl.	130	140-Lime	5168	5195	Perf. Top 5149 Bot. 5157
Limo, Wh.	140	170 Sand	5195	5207	Perf. Top 5202 Bot. 5208
Red rock	170	270 Lime	5207	5210	S.L. Producing Sand Record:
Slate, Wh.	270	338	5207	SIM	Orisk. Sand from 5136 to
Red Rock	338	395			5164 Init. Prod. 582 M.C.F.
Slate, Bk.	395	423			Gas
Sand, Wh.	423	430			
Slate, Wh.	430	433	Corn. Lime	5036	5134
Sand, Wh.	433	500	Oriskany	5134	5168
Slate, Wh.	500	515	Limo	5168	5195
Sand, Wh.	515	543	Sand	5195	5207
Slate, Wh.	543	555	Limo	5207	5210
Red Rock	555	665			S.L.

Slate, Wh.	665	670			
Red Rock	670	690			
Sand, Wh.	690	720			
Slate, Wh.	720	726			
Limo, Wh.	726	736			
Sand, Wh.	790	812			
Red Rock	812	815			
Limo, Wh.	815	829			
Red Rock	829	840			
Slate, Wh.	840	851			
Sand, Wh.	851	902			
Slate, Wh.	902	916			
Gritty Limo, Wh.	916	941			
Sl. & Sh., Wh.	941	960			
Sand, Wh.	960	1010			
Slate, Wh.	1010	1018			
Sand, Wh.	1018	1073	Oil Show		
Slate, Wh.	1073	1103			
Sand, Wh.	1103	1149			
Slate, Wh.	1149	1276	Oil 1100 Show		

GAUGES IN ORISKANY - Before Shot

3-9-42	5136-39	203 M
Shut down testing casing.		
3-13-42		Gauge before drilling 133 M
3-13	5145	223 M
3-13	5149	223 M
3-14	5152	160 M
3-14	5156	321 M
3-14	5161	492 M
3-14	5164	582 M
3-14	5166	492 M
3-17	5168	492 M
3-17	5168	492 M
3-17	5178	348 M
3-18	5180	492 M
3-18	5184	492 M
3-18	5190	492 M
3-18	5198	492 M
3-19	5207	440 M
3-19	5210	361 M

GAUGES IN ORISKANY - AFTER Shot

Gauge Before shot	539 M
5 Mins. A.S.	2073 M
10 "	1892 M
15 "	1796 M
20 "	1893 M
1 Hr.	1583 M

Salt Sand, Wh.	1276	1303	
Settling Sand	1303	1320	
Salt Sand, Wh.	1320	1350	
Slate, Wh.	1350	1508	
Salt Sand, Wh.	1508	1853	Water sand 1710-20
Gritty Limo, Wh.	1853	1900	
Maxton Sand, Wh.	1900	1976	
Big Limo, Gray	1976	2024	Water level 340'
Injun Sand, Wh.	2024	2062	
Slate, Bk.	2062	2080	
Limo, Bk.	2080	2105	2039 SLM
Sl. & Sh., Wh.	2105	2476	
Br. Shale	2476	2479	
Borca Grit, Br.	2479	2493	
Sl. & Sh., Wh.	2493	3699	
Br. Shale	3699	3740	
Sl. & Sh., Wh.	3740	4070	
Br. Shale	4070	4330	
Slate, Wh.	4330	4762	
Br. Shale	4762	4862	
Slate, Wh.	4862	4900	
Br. Shale	4900	5003	
Bk. Shale - MARCELLUS	5003	5036	

5036 5134 5207
 856 856 856

 4180 4278 4351