



0.58-S  
 2.57-S  
 2.97-W  
 2.92-W

LOC. 1.1 M. W. OF HEREFORD  
 New Location X  
 Drill Deeper   
 Abandonment

Company COLUMBIAN CARBON CO.  
 Address BOX 1240 CHARLESTON W. VA.  
 Farm R. A. SHINN ET AL  
 Tract \_\_\_\_\_ Acres 269.5 Lease No. WU-62  
 Well (Farm) No. 1 Serial No. \_\_\_\_\_  
 Elevation (Spirit Level) 760.6  
 Quadrangle RIPLEY SW -8- SC  
 County JACKSON District RIPLEY  
 Engineer J. Sell  
 Engineer's Registration No. 772  
 File No. \_\_\_\_\_ Drawing No. 63  
 Date FEB 27, 1942 Scale 1" = 660'

STATE OF W. VA.  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. Jac-291-R

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

6-6-192

WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
W E L L R E C O R D

Permit No. Jac-291-R

Company  
Address  
Farm  
Location  
Well No  
District  
Surface  
Mineral  
Commenced  
Completed  
Not Shot  
Volume  
Rock Pressure  
Fresh Water  
Salt Water

Columbian Carbon Co.  
Box 1240, Charleston, W. Va.  
R.A. Shinn et al, Acres 269.5  
Stationcamp Run  
1 (GW-655) Elev. 764.8 D.F.  
Ripley Jackson County  
"  
"  
4-6-42  
6-12-42  
11, 255MCF  
1650 lbs. 2 days  
184' 3-15" blrs. pr. hr; 300' 1 1/2-15"  
blrs. pr. hr; 560' 3-15" blrs. pr. hr.  
1195' 1-10" blr. in 3 hrs.; 1290' 1-10"  
blr. pr. hr.; 1740' Hole Full

Gas Well  
CASING & TUBING  
16 40'2 40'2  
13 3/8 634'10 0  
10 1/2 1102'5" 0  
8 5/8 2083'8  
7 5005'10  
5005'10

Red Rock	0	40	Brown Shale	4650	4900
Lime Shell	40	45	Black Shale - MARCELLUS	4900	4967SLM
Red Rock	45	85	Corniferous Lime - 463	4967SLM	5068SLM
White Slate	85	100	Oriskany Sand	5068SLM	5087
Red Rock	100	135	TOTAL DEPTH		5087DLM
Slate & Shells	135	190			
Red Rock	190	230	Pay: 5070' SLM-5087' DLM		
Sand	230	305			
Red Rock	305	312	CEMENT RECORD:		
Sand	312	345	4-16-42 Aquagelled 13 3/8" casing.		
Red Rock	345	355	Ran 18 sacks aquagel and 50# fibrotex,		
Slate & Shells	355	385	mixed 6%.		
Red Rock	385	420			
Slate	420	440	4-22-42 Aquagelled 10 1/2" casing. Ran		
Red Rock	440	455	21 sacks aquagel.		
Slate & Shells	455	515			
Sand	515	567	5-10-42 Aquagelled 8 5/8" casing.		
Coal	567	570	Ran 25 sacks aquagel and 50# Fibrotex		
Slate	570	630	mixed 6%.		
Lime	630	633			
Slate	633	710	6-2-42 Cemented 7" casing. Ran 32		
Red Rock	710	825	sacks 6% aquagel with 50# fibrotex		
Slate & Shells	825	950	ahead of cement. Ran 32 sacks		
Red Rock	950	965	Superior cement. 16' cement in hole.		
Slate & Shells	965	1060			
Sand	1060	1095			
Slate	1095	1110			
Lime	1110	1115			
Slate	1115	1140			
Sand	1140	1200			
Slate	1200	1230			
Sand	1230	1295			
Slate	1295	1330			
Sand	1330	1350			
Slate	1350	1475			
Sand	1475	1500			
Slate	1500	1660			
Sand	1660	1840			
Big Lime	1840	1907			
Sand	1907	1917			
Lime	1917	1950			
Big Injun Sand	1950	2040			
Slate	2040	2085 SLM			
Shells	2085 SLM	2090			
Slate & Shells	2090	2400			
Brown Shale	2400	2417			
Borea Grit	2417	2425 Gas	2420 small show		
Slate & Shells	2425	3920 Gas	show 3170'		
Brown Shale - 441	3920	4050			
White Slate	4050	4075			
Brown Shale	4075	4225			
White Slate	4225	4650			