



New Location X
 Drill Deeper
 Abandonment

*Abandoned
 Oct 51*

*6.26 S 30° 55' W
 6.22 S
 2.42 W
 2.40 W*

Company COLUMBIAN CARBON Co.
 Address Box 1240 CHARLESTON W.VA.
 Farm C.A. PARRISH
 Tract _____ Acres 230 Lease No. C-1329
 Well (Farm) No. 1 Serial No. _____
 Elevation (Spirit Level) 651.0
 Quadrangle RIPLEY 8 SWC
 County JACKSON District RIPLEY
 Engineer C.U. Granham
 Engineer's Registration No. E83
 File No. _____ Drawing No. _____
 Date 3/12/42 Scale 1" = 665'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. JAC-310

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500. latitude and longitude lines being represented by border lines as shown.
 - Denotes one inch spaces on border line of original tracing.

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
W E L L R E C O R D

Permit No. Jac 310

Company Columbian Carbon Co.
Address Box 1240, Charleston, W.Va.
Farm C.A. Parrish Acres 230
Location Joes Run
Well No 1 (GW-652) Elev. 654.3 DF
District Ripley Jackson County
Surface H.C.Parris et al (contact Col.
 Carbon Co. for addresses)

Gas Well
CASING & TUBING
16 34" 6 34" 6
13 3/8 540" 0
10 1/2 1043" 8 0
8 5/8 1968" 11 0
7 4942" 6 4942" 6

Mineral Same
Commenced 3-25-42
Completed 6-21-42
Not shot
Volume 11,476 MCF
Rock Pressure 1610 lbs. 72 hrs.
Fresh Water 260' 1-16" blrs. hr.; 410-25' 2-15"
 Blrs. pr. hr.; 785' 1/2 blrs. pr. hr.
Salt Water 1215' 4 blrs. pr. hr.; 1638' Hole Full

Gravel Sand	0	30	Limo	1783	1829
Red Rock	30	70	Sand - Injan	1829	1907
Black Slate	70	82	Slate	1907	1954
White Slate	82	100	Limo	1954	2036
Red Rock	100	110	Slate & Shell	2036	2280
White Slate	110	117	Brown Shale	2280	2298
Sand	117	160	Berea Sand	2298	2305
Slate	160	164	Slate	2305	2424
Gray Lime	164	180	Limo	2424	2464
Red Rock	180	195	Slate & Shells	2464	3977
Limey Sand	195	220	Brown Shale	3977	4076
Red Rock	220	250	Slate & Shells	4076	4525
Sand	250	265	Brown Shale	4525	4858 SLM
Red Rock	265	290	Corniferous Lime - 463	4858 SLM	4969 SLM
Light Slate	290	318	Oriskany Sand	4969 SLM	4986 DIM
Red Rock	318	345	TOTAL DEPTH		4986 DIM
Lime Shell	345	363			
Slate Shells	363	379			
Sand	379	465	PAY; 4973-86 (Sh. Gas 2299', show gas		
White Slate	465	535	CEMENT RECORD: 4050-56')		
Lime Shell	535	536			
White Slate	536	550	4-1-42 Aquagelled 13 3/8" casing		
Sand	550	590	Ran 15 sacks aquagel and 1 sack Fibrotex,		
Slate Shells	590	601	mixed 6 %.		
Red Rock	601	635			
Lime Shell	635	640	4-7-42 Aquagelled 10 1/2" casing. Ran 15		
Slate	640	645	sacks aquagel and 1 sack Fibrotex mixed		
Red Rock	645	730	6%.		
Slate & Shells	730	783			
Coal	783	785	4-23-42 Aquagelled 8 5/8" casing. Ran		
White Slate	785	845	24 sacks aquagel and 1 sack Fibrotex,		
Sand	845	870	mixed 6 %.		
Red Rock	870	880			
Slate Shells	880	977	6-3-42 Cemented 7" casing. Ran 50		
Sand	977	990	sacks aquagel, 19 sacks cement and 1		
Slate Shells	990	1037	sack Fibrotex.		
Sand	1037	1065			
Dark Slate	1065	1154			
Sand	1154	1330			
Slate	1330	1375			
Sand	1375	1400			
Slate & Shells	1400	1430			
Sand	1430	1440			
Slate	1440	1535			
Sand	1535	1550			
Slate & Shells	1550	1628			
Salt Sand	1628	1735			
Limo	1735	1744			
Big Lime	1744	1778			
Sand	1778	1783			

4858 4969
654 654

4204 4315