



New Location
 Drill Deeper
 Abandonment

Company GODFREY L CABOT INC.
 Address 900 UNION Bldg. Charleston W.Va.
 Farm G.C. Winters et al
 Tract _____ Acres 160 UNIT Lease No. WV-15
 Well (Farm) No. 1 Serial No. 1043
 Elevation (Spirit Level) 838.09
 Quadrangle Kenna N.W.
 County JACKSON District Ripley
 Engineer Roy Barton
 Engineer's Registration No. _____
 File No. _____ Drawing No. _____
 Date 4-23-42 Scale 1" = 1320'

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON

WELL LOCATION MAP
 FILE NO. JAC-338

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.

- Denotes one inch spaces on border line of original tracing.

6-6-192

WEST VIRGINIA DEPARTMENT OF MINES
OIL & GAS DIVISION
WELL RECORD

Permit No. Jac 338		Gas Well
Kenna Quad		CASING & TUBING
Company	Godfrey L. Cabot, Inc.	10 $\frac{3}{4}$ " 1122 1122
Address	Charleston, W.Va.	85/8 2154 -
Farm	Winters (Unit 15)	7 5025 5025
Location	---	1- $\frac{1}{2}$ " 5084 5084
Well No	1 (Ser 1043) Elev. 838	
District	<u>Ripley Jackson County</u>	10 $\frac{3}{4}$ " O.D. Casing Coupling
Surface	---	bevelled
Mineral	---	85/5" Spang B.H.Packer;
Commenced	May 12, 1942	28 bags aquagel
Completed	July 4, 1942	7 Sp. Orisk. B.H.Packer;
Shot	7-7-42 5100-5112 30 qts.	40 bags aquagel; 4
Volume	B.S. 60 MCF; 50 Min A.S. 411 MCF	bags fibertex.
Rock Pressure	1695 # 42 hrs.	Screw cap on bottom
Fresh Water	900' $\frac{1}{2}$ blr. pr. hr.	Joint.
Salt Water	1670 H.F. Water Sand 1670-1735	Tubed & Shut in 8-10-42
		Perf. top 5082-bot 5088

Soil	0	14	Corniferous Lime - 463 SLM 5005	5097	5097
Shell Gray	14	25	Oriskany	5097	5131
Red Rock	25	60	Lime, Oriskany	5131	5138
Sand Gray	60	80	Sand, Oriskany	5138	5158
Red Rock	80	246	Lime	5158	5182 SLM
Slate, Gray	246	270	TOTAL DEPTH	485	5182
Sand, White	270	290			
Red Rock	290	325	SLM 5005, 5025-5102-5182 and 2154		
Slate, blue	325	365			
Red Rock	365	390	GAUGES IN ORISKANY SAND *B.S.		
Sand, White	390	435	6-30-42 5101 103MCF		
Red Rock	435	465	5102 133MCF		
Blue Shell	465	475	5107 146 MCF		
Red Rock	475	525	5109 158 MCF		
Slate, Dark	525	680	Shut in to test casing.		
Red Rock	680	750	7-2-42 5109 103 M		
Sand, Gray	750	765	5111 to 84 M		
Red Rock	765	850	5182		
Sand, Gray	850	872	GAUGES IN ORISKANY * A.S.		
Coal	872	875	Gauges B.S. 60 M		
Sand, Gray	875	912	5 Mins A.S. 557 M		
Slate, Dark	912	935	10 " " 444 M		
Sand, Grey	935	960	15 " " 444 M		
Slate, Light	960	1112	20 " " 444 M		
Sand, Grey	1112	1258	50 " " 411 M		
Slate, Dark	1258	1316			
Sand, Gray	1360	1380			
Sand, Gray	1380	1476			
Slate & Shells, Dark	1476	1630			
Salt Sand, Medium	1630	1805			
Slate, Soft	1805	1811			
Sand	1811	1969			
Big Lime, Medium	1969	2041			
Injun Sand, white	2041	2100			
Slate, dark	2100	2110			
Lime, Dark	2110	2132			
Slate, Dark	2132	2138			
Lime, Grey	2138	2351	SLM 2154		
Slate & Shells, dark	2351	250; 5			
Brown shale	2505	2520			
Berea Sand	2520	2535			
Slate & Shells, dark	2535	3325	Smell Gas 2520		
Brown Shale - 442	3325	3380			
Slate & Shells, dark	3380	3760			
Brown Shale - 441	3760	3815			
Slate & Shells, dark	3815	4015			
Brown shale	4015	4135			
Slate, White	4135	4190			
Brown Shale	4190	4205			
White Slate	4205	4720			
Brown Shale	4720	5005			