



New Location   
 Drill Deeper   
 Abandonment

Company	COLUMBIAN CARBON COMPANY		
Address	BOX 873 CHARLESTON, W.VA.		
Farm	C.H. HOLLIDAY		
Tract	Acres	Lease No.	
	96	C-1576	
Well (Farm) No.	1	Serial No.	
Elevation (Spirit Level)	1058.0		
Quadrangle	BELLEVILLE 8 S343 W140 - SC		
County	JACKSON	District	GRANT
Engineer	<i>C. P. Crankham</i>		
Engineer's Registration No.	683		
File No.	Drawing No.		
Date	MARCH 9, 1948	Scale	1" = 660'

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO JAC-590

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
 - Denotes one inch spaces on border line of original tracing.

Sample 22-F (0-5109)

Deep Well

3.48 S  
 3.52 S  
 1.39 W

W 10/48

WEST VIRGINIA DEPARTMENT OF MINES  
OIL & GAS DIVISION  
W E L L R E C O R D

Permit No. Jac 590  
Belleveille Quad.

Company  
Address  
Farm  
Location  
Well No.  
District  
Surface

Columbian Carbon Company  
Box 873, Charleston 23, W.Va.  
G.H. Holliday Acres 96  
Skull Run of Nesselroad  
1 GW 1060 Elev. 1058' G  
Grant Jackson County  
G.H. Holliday, Route #1,  
Rockport, W.Va.

Dry Hole  
CASING & TUBING

16 22 pulled  
13 3/8 48# 967'6 Pld.  
10 1/2 48# 1338'2 40'6  
8 1/4 24# 2145'5 Pld.  
7 22# 4989'9 1494'10

Mineral  
Commenced  
Completed  
Not shot  
Volume  
Fresh Water  
Salt Water

Same  
3-18-48  
9-22-48

Midget B.H. Packer  
Size 7"  
Depth 4979 SLM

No coal

Dry Hole

861' 2-16" blr. per hr.; 875' 2-16" blr. per hr.  
1835' 4-10" blr. hr.; 1940' H.F.

Clay	0	9
Red Rock	9	381
Lime	381	450
Red Rock & Shells	450	673
Sand	673	688
Red Rock & Shells	688	735
Lime	735	830
Sand	830	891
Red Rock	891	894
Sand	894	926
Slate	926	936
Lime	936	973
White Slate	973	994
Sand	994	1030
Red Rock	1030	1228
Slate & Shells	1228	1276
Red Rock	1270	1288
Slate & Shells	1288	1326
Sand	1326	1378
Slate 1325DLM - 1326' SLM	1378	1484
Sand	1484	1655
Slate & Shells	1655	1730
Sand - <i>S&amp;S Sand</i>	1730	1960
Lime - <i>Big Lime</i>	1960	2030
Sand - <i>Isipum</i>	2030	2100
Lime 2136 DLM- 2133 SLM	2100	2138
Slate & Shells	2138	3682
Shale & Shells	3682	4308
White Slate	4308	4710
Shale	4710	4966
Lime - <i>Ab</i> 4982' DLM-4979' SLM	4966	5072
Sand - <i>ORISKANY</i>	5072	5094
Dark Lime	5094	5101
Sand	5101	5112
Lime	5112	5172
Total Depth		5172
Dry Hole-plugged and abd. 11-19-48		

CEMENT RECORD:

4-9-48 13 3/8" casing- ran 25 bags  
aquagel. No circulation or returns.  
4-20-48 10 1/2" casing- ran 25 bags  
aquagel- no circulation or returns.  
5-6-48 8 5/8 " casing- ran 25 bags  
aquagel- Returns O.K.  
6-15-48 7" casing- ran aquagel thru  
tubing - ran 50 bags aquagel and  
100 bags cement- no circulation or  
returns.  
C.C.Co.Crew

*Top of Orisk below 5072 + 5087*

5072	5112	4966
1056	1056	1056
<hr/>		
4014	4054	3908

485