



- (Disposal Well) NEW LOCATION
- RECONDITION
- DRILL DEEPER
- ABANDONMENT

CERTIFICATE

"I, the undersigned, hereby certify that this map is correct to the best of my knowledge and belief and shows all the information required by paragraph 6 of the rules and regulations of the oil and gas section of the mining laws of West Virginia."
 Minimum degree of accuracy is one part in 200

Signed *William A. Shady* L.L.S. No. 116

N.B. III Pg. 41

COMPANY	COMMONWEALTH GAS CORPORATION		
ADDRESS	P.O. BOX 1433 CHARLESTON, W.VA. 25325		
FARM	J. W. WIGAL ET AL - MIN (Stewart Sayre)		
MAP	OV-26	ACRES	172
LEASE NO.	2378		
WELL (FARM) NO.	2	SERIAL NO.	755-B
ELEVATION (SPIRIT LEVEL)	594.3'		
QUADRANGLE	RAVENSWOOD (S.E.)		
COUNTY	JACKSON	DISTRICT	RIPLEY
POINT OF PROVEN ELEVATION	U.S.G.S. BM-W-106 shown above		
FILE NO.	DRAWING NO.		
DATE	Dec. 6, 1971		
SCALE	1" = 660'		

STATE OF WEST VIRGINIA
 DEPARTMENT OF MINES
 OIL AND GAS DIVISION
 CHARLESTON
WELL LOCATION MAP
 FILE NO. **JAC-1321**

+ DENOTES LOCATION OF WELL ON UNITED STATES TOPOGRAPHIC MAPS SCALE 1 TO 62 500. LATITUDE AND LONGITUDE LINES BEING REPRESENTED BY BORDER LINES AS SHOWN.
 - DENOTES ONE INCH SPACES ON BORDER LINE OF ORIGINAL TRACING.

8-0 Ripley (311)

DEC 22 1971



RECEIVED

MAY 25 1972

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

- Rotary
- Spudder
- Cable Tools
- Storage

Disposal
salt water
(KIND)

Location Ravenswood S.E.

WELL RECORD

Permit No. Jac-1321

Oil or Gas Well

Company Commonwealth Gas Corporation
 Address P.O. Box 1433, Charleston, W.Va. 25325
 Farm J. W. Wigan, etal (Mineral) Acres 172
 Location (waters) Parchment Creek
 Well No. 755B Elev. 594.2
 District Ripley County Jackson
 The surface of tract is owned in fee by Stewart Sayre,
Ripley, W. Va. 25271 Address
 Mineral rights are owned by J. W. Wigan
2316 Rockland Ave., Address Belpre, Ohio 45714
 Drilling commenced 1/12/72
 Drilling completed 1/19/72
 Date Shot --- From --- To ---
 With ---
 Open Flow --- /10ths Water in --- Inch
--- /10ths Merc. in --- Inch
 Volume --- Cu. Ft.
 Rock Pressure --- lbs. hrs.
 Oil --- bbls., 1st 24 hrs.
 WELL ACIDIZED 1000 gal. Penetrating Acid
 WELL FRACTURED ---

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			Kind of Packer
16			
13			
10			Size of
8x 5/8"	160.02	160.02	Depth set
6x			
5 3/16			
4-1/2	1972.65	1972.65	Perf. top 1828 } Perf. bottom 1848 }
2			
Liners Used			Perf. top Perf. bottom

CASING CEMENTED 1 1/2 SIZE 1972 No. Ft. 1/15/72 Date
Cemented to surface w/439 CF.
 COAL WAS ENCOUNTERED AT --- FEET --- INCHES
--- FEET --- INCHES --- FEET --- INCHES
--- FEET --- INCHES --- FEET --- INCHES

RESULT AFTER TREATMENT 360 BPD @ 375 psig Displacement

ROCK PRESSURE AFTER TREATMENT
 Fresh Water --- Feet Salt Water --- Feet

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth	Remarks
Surface			0	40			
Sand & Shale			40	157			
Shale			157	300			
Sand & Shale			300	970			
Sand			970	1060			
Shale			1060	1135			
Sand			1135	1245			
Shale			1245	1285			
Sand			1285	1322			
Shale			1322	1588			
Salt Sand			1588	1654			
Pencil Cave			1654	1660			
Big Lime			1660	1790			
Shale			1790	1828			
Big Injun			1828	1881			
Shaly Sand			1881	1985			
TOTAL DEPTH				1985			

370

(over)

JUN 5 1972
 JUN 5 1972