

## KENNA CASTO NO. 2 WELL.

Not located.

Washington District, Jackson County, W. Va.

South Penn Oil Co.

On 50 acres; surface owned by O. C. Price, RFD 2, Gay, W. Va..

and mineral rights by Kenna Casto, Charleston, W. Va., and O. O. Price  
C. B. Stants, Stants Mills, W. Va.

Elevation, 756'.

16' conductor; 5 $\frac{1}{4}$ " casing, 535'; 6-5/8", 1084'; 2" tubing, 1515'.Callanan Bottom Hole Packer, 6-5/8" x 8 $\frac{1}{2}$ , set at 1073'.

No coal encountered.

Abandonment reported to Dept. of Mines June 15, 1931.

Well was not shot.

Water in Salt Sand.

	Top.	Bottom.
Conductor	0 -	16
Sand	16 -	70
Slate and shells	70 -	115
Red rock	115 -	165
Slate	165 -	180
Sand	180 -	190
Slate	190 -	200
Red rock	200 -	210
Slate and shells	210 -	250
Red rock	250 -	260
Slate and shells	260 -	315
1st Pittsburgh Sand	315 -	345
Slate and shells	345 -	425
2nd Pittsburgh Sand	425 -	485
Red rock	485 -	490
Slate	490 -	500
Red rock	500 -	535
Lime shell	535 -	540
Red rock	540 -	570
Black lime	570 -	585
Red rock	585 -	605
Slate and shells	605 -	660
Red rock	660 -	690
Sand	690 -	725
Slate and shells	715 -	755
Little Dunkard Sand	755 -	785
Slate and shells	785 -	880
Big Dunkard Sand	880 -	1005
Slate and shells	1005 -	1040
Gas Sand	1040 -	1065
Slate	1065 -	1073
Shell	1073 -	1190
Sand	1190 -	1220
Slate and shells	1220 -	1270
Sand	1270 -	1300
Slate and shells	1300 -	1469
Salt Sand (gas, 1495-1504')	1469 -	
Break	1504 -	1506

Oil show, 1523'

Total depth

1526

285

Filled up with stone to 1523'; drove 6-5/8" wood plug 3' at 1520'; filled up with stone to 1518'; filled up with cast iron to 1517'; drove 6-5/8" lead plug at 1515'. Total depth now 1515'. This was done in order to shut off water in Salt Sand.