

FORM OG-8

STATE OF WEST VIRGINIA DEPARTMENT OF MINES

OIL & GAS DIVISION DEPT. OF MINES

OIL AND GAS WELLS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

NONE				Hugh	Spencer	20	
	PERATOR OR OWNER	ner que merche del ser est sus sus produites banqueste passana	manuscript and appropriate for the second second second		NAME OF WELL		
			***************************************	West	Union,		26456
NONE	ADDRESS	í	over 400 Sept.	War and	COMPLETE A		77
	PERATOR OR OWNER			AINIL. Q	OLZO VELL, AND L	OCATION	19
	-	The sets of the first between one who do not construct and the	of his online or vision he or on his because or	Cour	t House	CONTINUE AND MAN AND TO A SERVICE SO THE SERVICE AND AND AND THE BOTH THE B	District
10 to 10 to 10 to	ADDRESS						
	Of Highways	ort. An PP MET file out this topy sale feature. File disciplines are	Approximate the self-to-control that his figure and an end, in	Lewi	E proprieta anticolor de l'action de la company de la comp	Citiva hander in wares in a street of man manner is a constant.	County
Charleston.			Well N	. 40	OL		
	ADDRESS						
				W.S.	Cunning	gha m	Farm
STATE INSPECTOR S	SUPERVISING PLUGG	ING W11	liam B	loss	9T		
		AFFID	AVIT				
STATE OF WEST	VIRGINIA,	1					
County of Doddr	îdee	ss:					
•	oak	·)	J De	nvor	Cox		
being first duly sw	orn according to la	w depose a	ma			ienced in the	work of
	oil and gas wells an						:
well operator, and p	participated in the w	ork of plug	ging and	filling	the above	well, that s	
was commenced on and filled in the fol	the 23 day of lowing manner:	Februar	» ¥	, 197	1, and that	t the well was	s plugged
SAND OR ZONE RECORD	FILLING	MATERIAL	MARIONARIA (Special de la valencia d Specialista (Specialista de la valencia del valencia de la valencia de la valencia del valencia de la valencia del valencia del valencia de la valencia de la valencia del valenc	lc	LUGS USED	C.	ABING
FORMATION		- Antonomistade communication in the contraction of			SIZE & KIND	CSG PULLED	CSG LEFT IN
hot 3" Tubing	off at 2550 F	t. and r	ulled	3" T	ubing.	3" 2550	
		n. White the control of the control				7" 1150	899
Installed bridg			lled w	th 1	.0 ft.	811.	81
Clay, 10-Ft. St	one & 40 Ft.	Coment.				10"	18
fundallad budda	0050 E4		מיים להם דו	dela	7 0.		
<u>Installed bridg</u> stone to 2000 F		*************************	The state of the s		CALLED TO SECURE OF SECURE OF SECURE OF SECURE		
SCUMB CO COOU I	Co SUG GOMOND	ed antre		110 7.	V 0	1	-
	- Control of the Cont						
Ripped 7" Casir	g st 1150 Ft.	and in:	stalle	bri	dee on		
Ripped 7" Casir top of vparted o	g at 1150 Ft.	and in:	stalle	bri	dge on	Fto	
top of vparted o	asing and fil	and in: led with	stalle n 10 F	bri	dge on	Fito	
top of warted on tone & 10 bags	asing and fil	led with	10 F	; CI	.ey, 10	Fte	
top of warted on tone & 10 bags colled hole to	esing and fil coment, 900 Ft. and c	led with	10 F	; CI	.ey, 10	Ft.	
top of wparted of tone & 10 bags Gelled hole to Gelled hole from	esing and filement, 900 Ft. and common 770 Ft. to	led with emented Surface	n 10 F	t. Cl	ay, 10 70 Ft.		
top of wparted of tone & 10 bags delied hole to Spotted coment	esing and filement, 900 Ft. and common 770 Ft. to	led with emented Surface	n 10 F	t. Cl	ay, 10 70 Ft. to surf	200.	
top of vparted of tone & 10 bags Gelled hole to Gelled hole from Spotted coment COAL SEAMS	esing and filement, 900 Ft. and common 770 Ft. to	led with emented Surface	n 10 F	to 7	70 Ft.	800 6	
top of vparted of tone & 10 bags Gelled hole to Gelled hole from Spotted coment COAL SEAMS	esing and filement, 900 Ft. and common 770 Ft. to	led with emented Surface	n 10 F	to 7	70 Ft. to surf	ade. rion of monum d due to	being
top of vparted of stone & 10 bags Gelled hole to Gelled hole from Coal seams AME:	esing and filement, 900 Ft. and common 770 Ft. to	led with emented Surface	n 10 F	to 7	70 Ft. to surf	800 6	being
top of vparted of tone & 10 bags Gelled hole to Gelled hole fro Spotted coment COAL SEAMS AME)	esing and filement, 900 Ft. and common 770 Ft. to	led with emented Surface	n 10 F	to 7	70 Ft. to surf	ade. rion of monum d due to	being
top of vparted of tone & 10 bags Gelled hole to Gelled hole fro Coal seams AME: AME: AME: AME: AME: and that the work	coment, 900 Ft. and c m 770 Ft. to plug at 50 Ft of plugging and fil	led with	n 10 F	to 7	70 Ft. to surf DESCRIPT OF OR OF THE	ade. Tion of Monum d due to ht-of-way	being
ame) AME) AME) ame) and that the work March	coment, 900 Ft. and c m 770 Ft. to plug at 50 Ft of plugging and fil	led with	n 10 F	to 7	70 Ft. to surf DESCRIPT OF OR OF THE	ade. Tion of Monum d due to ht-of-way	being
Gelled hole to Gelled hole fro Spotted coment COAL SEAMS AME) AME and that the work March And further dep	of plugging and file of plugging and pluggin	led with emented Surface . &comes	n 10 F	to 7	to surf	ade. FION OF MONUM d due to ht-of-way	day of
cop of vparted of tone & 10 bags delied hole to delied hole fro potted coment coal seams ame) ame and that the work March And further dep	of plugging and file of plugging and file onents saith not.	led with emented Surface . &comes	n 10 F	to 7	to surf	ade. Tion of Monum d due to ht-of-way	day of