



New Location   
 Drill Deeper   
 Abandonment

✓ ✓ ✓ JUN 21 1942

H 4	2.87 W	#1	2.95 W
	3.52 W		3.45 W
H 4	✓	#6	2.77 W
	✓		3.41 W

Company Frick-Reid Supply Corporation  
 Address Sandyville, West Virginia  
 Farm Neri Keeney  
 Tract \_\_\_\_\_ Acres 149 Lease No. \_\_\_\_\_  
 Well (Farm) No. 1-4-6 Serial No. \_\_\_\_\_  
 Elevation (Spirit Level) 725-949-726  
 Quadrangle Madison  
 County Lincoln District Union  
 Engineer A. K. Westfall  
 Engineer's Registration No. Co. Surveyor, Ritchie Co.  
 File No. \_\_\_\_\_ Drawing No. \_\_\_\_\_  
 Date May 23, 1942 Scale 1" = 40 Feet

STATE OF WEST VIRGINIA  
 DEPARTMENT OF MINES  
 OIL AND GAS DIVISION  
 CHARLESTON

WELL LOCATION MAP  
 FILE NO. LIN-308-A #1  
LIN-309-A #6

+ Denotes location of well on United States Topographic Maps, scale 1 to 62,500, latitude and longitude lines being represented by border lines as shown.  
 - Denotes one inch spaces on border line of original tracing.

STATE OF WEST VIRGINIA  
DEPARTMENT OF MINES  
OIL AND GAS DIVISION

608

WELL RECORD

Permit No. 309-A

Oil or Gas Well (KIND) Oil well

Company Frick-Reid Supply Corporation  
 Address Drawer 2481, Tulsa, Okla.  
 Farm Neri Keeney Acres 149  
 Location (waters) Sugartree Br. Mud River  
 Well No. Six Elev. 726  
 District Union County Lincoln  
 The surface of tract is owned in fee by Mrs. Maggie Keeney  
Griffithville Address W. Va.  
 Mineral rights are owned by Mrs. Maggie Keeney  
Griffithville Address W. Va.  
 Drilling commenced March 27, 1916  
 Drilling completed May 5, 1916  
 Date Shot 5/9/1916 From 2174 To 2192  
 With 90 lbs. Nitro-glycerine  
 Open Flow /10ths Water in \_\_\_\_\_ Inch  
 \_\_\_\_\_ /10ths Merc. in \_\_\_\_\_ Inch  
 Volume \_\_\_\_\_ Cu. Ft.  
 Rock Pressure \_\_\_\_\_ lbs. \_\_\_\_\_ hrs.  
 Oil \_\_\_\_\_ 3 bbls., 1st 24 hrs.  
 Fresh water 10 feet \_\_\_\_\_ feet  
 Salt water 820 feet \_\_\_\_\_ feet

Casing and Tubing	Used in Drilling	Left in Well	Packers
Size			
16			Kind of Packer
13			
10 Wood	10	10	Size of
8 1/4	270	270	
6 5/8	1480	1480	Depth set
5 3/16			
3			Perf. top
2		2193	Perf. bottom
Liners Used			Perf. top
			Perf. bottom

CASING CEMENTED \_\_\_\_\_ SIZE \_\_\_\_\_ No. Ft. \_\_\_\_\_ Date \_\_\_\_\_  
 COAL WAS ENCOUNTERED AT 238 FEET \_\_\_\_\_ INCHES  
242 FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES  
 \_\_\_\_\_ FEET \_\_\_\_\_ INCHES \_\_\_\_\_ FEET \_\_\_\_\_ INCHES

Formation	Color	Hard or Soft	Top	Bottom	Oil, Gas or Water	Depth Found	Remarks
Sand & gravel			10	10	Water	10	Hole full
Sand			10	208			
Slate			208	238			
Coal			238	242			
Sand			242	360			
Slate			360	445			
Lime			445	490			
Slate			490	510			
Lime			510	535			
Sand			535	545			
Slate			545	636			
Lime			636	650			
Slate & shells			650	730			
Salt sand			730	1355	Water	820	Hole full
Slate			1355	1365			
Red rock			1365	1390			
Lime			1390	1432			
Slate			1432	1440			
Black lime			1440	1470			
Pencil			1470	1477			
White lime			1477	1680			
Injun			1680	1745			
Slate			1745	1800			
Shells			1800	1920			
Slate			1920	2150			
Brown shale			2150	2171			
Berea sand			2171	2193			
Total depth			2196				



