

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE ST. MONONGAH WV 26582  
Address  
CONSOLIDATION COAL CO.  
Coal Operator or Owner  
1 BRIDGE ST. MONONGAH WV 26582  
Address  
CONSOLIDATION COAL COMPANY  
Lease or Property Owner  
1000 Consol Energy Dr. Canonsburg, PA 15314  
Address

CONSOLIDATION COAL CO.  
Name of Well Operator  
1 BRIDGE ST. MONONGAH, WV 26582  
Complete Address  
GLOVER GAP 7.5'  
Well Location  
MANNINGTON  
District  
MARION  
County  
3985  
Well No.  
CONSOLIDATION COAL COMPANY  
Farm

STATE INSPECTOR SUPERVISING PLUGGING Bill Heubusch

RECEIVED  
Office of Oil & Gas

AFFIDAVIT

DEC 21 2011

STATE OF WEST VIRGINIA,  
County of MONONGALIA ss:

WV Department of  
Environmental Protection

DELBERT MOORE and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 11<sup>th</sup> day of August, 2011 and that the well was plugged in the following manner:

Formation	Filling Material	Plugs Used Size & Kind	Casing Pulled	Casing Left In
Removed 2 3/8" tubing from the surface to 842'. Cleaned 12 1/4" hole from the surface to 50'. Cleaned 9 7/8" hole from 50' to 933'. Top of 8 5/8" casing at 933'. Cleaned 7 7/8" hole from 993' to 1938'. Tagged solid plug at 1938'. Removed 96' of 8 5/8" casing from 933' to 1029'. Left 416' of 8 5/8" casing in the hole from 1029' to 1445'. Cement bond log indicated that the 8 5/8" casing was cemented in from 1029' to 1445'. Cut remaining 8 5/8" casing at 1335', 1250', 1200', 1167', 1117' and 1067'. Left 184' of 10 3/4" casing in the hole from 50' to 234'. Left 20' of 16" conductor pipe in hole from 20' to surface. Cleaned 9 7/8" hole thru Pittsburgh Coal 960' to 967'. <b>Cement hole from 1938' back to surface as follows:</b> From 1938' to 1167' with 180 sacks of 35/65 Poz Mix. From 1167' to 860' with 115 sacks of Thixotropic Cement with green dye. From 860' to surface with 235 sacks of Econofill Cement. A total of 530 sacks of cement were used to fill the hole from 1938' to surface. Cement did circulate at the surface.	16" Conductor	0'	20'	
		10 3/4" Casing	0'	184'
		8 5/8" Casing	96'	408'
<b>Coal Seams</b>		<b>Description of Monument</b>		
<u>PITTSBURGH</u>	960' to 967'	77" of 7" casing w/company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to the cement plug at ground level.		
(Name)				
(Name)				
(Name)				

... And that the work of plugging and filling said well was completed on the 6<sup>th</sup> day of September, 2011

And further deponents saith not.

Delbert Moore  
Delbert Moore

Kevin S. Wright  
Kevin S. Wright

Jacqueline L. Shriver  
Notary Public

Permit No. 47-49-00174-P  
Well No. 3985

Sworn to and subscribed before me this 5<sup>th</sup> day of December, 2011  
My commission expires:  
March 18, 2020

