

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address
CONSOLIDATION COAL CO.
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address
ROBERT D. GRIM
Lease or Property Owner
13245 OLD FREDRICK RD. SYKESVILLE, MD 21784
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE STREET MONONGAH, WV 26554
Complete Address
GLOVER GAP 7.5'
Well Location
MANNINGTON
District
MARION
County
2905
Well No.
GRIM, ROBERT D.
Farm

RECEIVED
Office of Oil & Gas
DEC 21 2011

STATE INSPECTOR SUPERVISING PLUGGING Bill Hushak

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

WV Department of
Environmental Protection

DELBERT MOORE and KEVIN WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 18th day of October, 2011 and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
	Cleaned 12 1/4" hole from surface to 198'. Cleaned 9 7/8" hole from 198' to the top of the 8 5/8" casing at 1119'. Cleaned 7 7/8" hole from 1119' to 1908'. Remove 8 5/8" casing from 1119' to 1336'. Left 300' of 8 5/8" casing in the hole from 1336' to 1636'. Cut remaining 8 5/8" casing at 1536' and 1436'. Cleaned 9 7/8" hole thru Pittsburgh Coal 1132' to 1142'. Left 20' of 16" conductor in hole from 20' to surface.	16" Conductor 8 5/8" casing	0' 215'	20' 300'
Cement hole from 1908' to surface as follows.				
From 1908' to 1342' with Super Lite Cement.				
From 1342' to 1032' with 165 sacks of Super Tropic Cement with green dye.				
From 1032' to surface with Super Lite Cement. A total of 835 sacks of cement were used to fill the hole from 1908' to surface. Cement did circulate at the surface.				
Coal Seams		Description of Monument		
<u>Pittsburgh</u>	(1132' - 1142')	77" of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.		

... and that the work of plugging and filling said well was completed on the 8th day of November, 2011

And further deponents saith not.

Delbert E Moore
Delbert Moore

Kevin S. Wright
Kevin S. Wright

Sworn to and subscribed before me this 15th day of December 2011

Jacqueline L. Shriver
Notary Public

Permit No. 47-049-00258-P
Well No. 2905



My commission expires:

March 18, 2020