

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL COMPANY
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address

CONSOLIDATION COAL COMPANY
Coal Operator or Owner
1 BRIDGE STREET MONONGAH, WV 26554
Address

PERRY, NANCY, THOMAS & LINDA WEST
Lease or Property Owner
829 DONEGAL DRIVE, FOLLANSBEE, WV 26037
Address

CONSOLIDATION COAL CO.
Name of Well Operator
1 BRIDGE STREET MONONGAH, WV 26554

Complete Address
GLOVER GAP 7.5'
Well Location
MANNINGTON

District
MARION
County
7072
Well No.
JOHN WEST
Farm

STATE INSPECTOR SUPERVISING PLUGGING

[Signature]

AFFIDAVIT

STATE OF WEST VIRGINIA,
County of MONONGALIA ss:

DELBERT MOORE and **KEVIN S. WRIGHT** being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 20th day of March, 2017 and that the well was plugged in the following manner:

Sand or Zone Record Formation	Filling Material	Casing/Tubing Size	Casing Pulled	Casing Left In
Removed all 2,917' of Sucker Rods from Surface to 2,917'. Removed all 2,957' of 2" tubing from Surface to 2,857'. Tripped in open ended 2 3/8" drill pipe to 3,008'. Tagged bottom of hole at 3,000'. Removed 1,620' of 4 1/2" casing from Surface to 1,620'. Left unknown amount of 4 1/2" casing in the hole from 1,620' to unknown depth due to Cement Bond. The remaining 4 1/2" casing had pre-existing perforations at 2,806', 2,800', 2,841', 2,810', 2,712', 2,660', 2,810', 1,986', and 1,966'. Tagged bottom hole cement plug with open ended 2 3/8" drill pipe at 1,620'. Attempted to pull 8 5/8" casing at the surface by exerting a pull of 150% of the 8 5/8" casing weight. Due to extreme cement bond, the 8 5/8" casing was section milled from 604' to 623'. Milled 8 5/8" casing through Pittsburgh Coal Seam from 609' to 616'. Left an unknown amount of 8 5/8" casing in the hole from the surface to an unknown depth. Perforated remaining 8 5/8" casing with 3 shots at each of the following depths: 816', 764', 718', 667', 508', 409', 310', 209', and 109', for a total of 27 shots.	5/8" Sucker Rods	2,957'	0'	
	2 3/8" Tubing	2,957'	0'	
	4 1/2" Casing	1,620'	Unknown	
	8 5/8" Casing	19'	Unknown	
	11 3/4" Casing	0'	Unknown	
	16" Conductor	0'	15'	
Cemented hole from 3,008' back to Surface as follows: Cemented bottom hole from 3,008' back to 1,620' with 85 sacks of Expandable Cement. Cemented hole from 1,620' to 816' with 155 sacks of Expandable Cement. Cemented hole for 816' to 509' with 100 sacks of Thixotropic Cement with green dye. Cemented hole from 509' to Surface with 100 sacks of Expandable Cement. Cement did circulate at Surface. A total of 440 sacks was used to Cement Wellbore. Left 15' of 16" Conductor Casing in the hole from 15' to Surface.				
Coal Seams		Description of Monument		
Pittsburgh	(609' - 616')	77' of 7" casing w/ company name, well number, permit number and date cemented stated on 7" casing. Well marker will be attached to cement plug at ground level.		

... and that the work of plugging and filling said well was completed on the 1st day of May, 2017.

And further deponents saith not.



Subscribed and sworn to before me this 16th day of May 2017

[Signature]
Delbert Moore

[Signature]
Kevin S. Wright

[Signature]
Notary Public

My commission expires: 08/14/17

Permit No. 47-049-00834-P
Well No. 7072

RECEIVED
Office of Oil and Gas
MAY 31 2017
WV Department of
Environmental Protection