FORM WR-38 (Affidavit of Plugging)

STATE OF WEST VIRGINIA **DEPARTMENT OF ENERGY** OIL AND GAS WELLS DIVISION

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO. Coal Operator or Owner 1 BRIDGE ST. MONONGAH WV 26582 **Address CONSOLIDATION COAL CO. Coal Operator or Owner** 1 BRIDGE ST. MONONGAH WV 26582 **Address** CONSOLIDATION COAL COMPANY **Lease or Property Owner** 1 BRIDGE ST. MONONGAH WV 26582 **Address**

CONSOLIDATION COAL CO. Name of Well Operator 1 BRIDGE ST. MONONGAH, WV 26582 **Complete Address GLOVER GAP 7.5' Well Location**

MANNINGTON District <u>MARION</u> County 5064 Well No.

CONSOLIDATION COAL COMPANY Farm

STATE INSPECTOR SUPERVISING PLUGGING

RECEIVED Office of Oil & Gas

AFFIDAVIT

DEC 2 1 2011

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

WV Department of **Environmental Protection**

DELBERT MOORE and KEVIN S. WRIGHT being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 12th day of September, 2011 and that the well was plugged in the following manner:

	Filling Material	Plugs Used	Casing Pulled	Casing Left In
Formation	i iiiig inateriai	Size & Kind	1 41104	Loit III
Cleaned hole with 2 3/8" drill pipe from the surface to 2807'. Removed all 5 ½" casing from the surface to 2167'. Cemented bottom hole from		16" Conductor	0'	20'
2807' back to 2200' with 100 sacks of Class A cement. Cleaned 6 1/4" hole from the surface to top of bottom hole plug at 2200'. Removed 7"		7" Casing	1215'	500'
casing from the surface to 1215'. Left 500' of 7" casing in the hole from 1215 to 1715. Cut remaining 7" casing at the following depths;		5 1/2" Casing	2167'	0'
1614', 1514', 1414', 1348' and 1316'. Cleaned 12 ¼" hole from the surface to 346'. Cleaned 9 7/8" hole from 346' to 1215'. Cleaned 6 ¼" hole from 1215' to the top of the bottom hole plug at 2200'. Cleaned				
9 7/8" hole through the F	Pittsburgh Coal 728' – 736'. Left 20' of 16"			
conductor pipe in the hole from 20' to surface. Cemented hole from 2807' back to surface as follows:				
From 2807' to 2200' with 100 sacks of Class A Cement. From 2200' to 936' with 130 sacks of 35/65 Poz Mix Cement. From 936' to 628'				
with 275 sacks of Thixatropic Cement with green dye. From 628' to surface with 230 sacks of Econofill Cement. A total of 735 sacks of				3
cement were used to fill the hole from 2807' to surface. Cement did circulate at the surface.				
Coal Seams		Description of Monument		
<u>PITTSBURGH</u>	728' to 736'	77" of 7" casing w/company name, well number,		
(Name)		permit number and date cemented stated on 7"		
(Name)		casing. Well marker will be attached to the		
(Name)		cement plug at ground level.		

... And that the work of plugging and filling said well was completed on the 26th day of September, 2011

And further deponents saith not.

Kell S. Wingl Kevin S. Wright

Sworn to and subscribed before me this 5th day of DULINDER, 2011

My commission expires: MWCh

OFFICIAL SEAL
STATE OF WEST VIRGINIA
NOTARY PUBLIC Permit No. 47-49-01038-P
Jacqueline L. Shrive Well Bo. 5064
Westover, WV 26501
My Commission Exp. March 18, 2020