FORM WR-38 (Affidavit of Plugging)

STATE OF WEST VIRGINIA DEPARTMENT OF ENERGY OIL AND GAS WELLS DIVISION

49.02132 P Revised

AFFIDAVIT OF PLUGGING AND FILLING WELL

AFFIDAVIT SHOULD BE MADE IN TRIPLICATE, one copy mailed to the Division, one copy to be retained by the Well Operator and the third copy (and extra copies if required) should be mailed to each coal operator at their respective addresses.

CONSOLIDATION COAL CO.
Coal Operator or Owner
BRIDGE ST. MONONGAH WV 26582

Address

CONSOLIDATION COAL CO.

Coal Operator or Owner

1 BRIDGE ST. MONONGAH WV 26582

Address DENNIS DUNIGAN

Lease or Property Owner RR 4 BOX 37 METZ, WV 26585 Address **CONSOLIDATION COAL CO.**

Name of Well Operator

1 BRIDGE ST. MONONGAH, WV 26582 CEIVED

Complete Address

Office of Oil & Gas

GLOVER GAP Well Location

Cillo

MANNINGTON

MAR 1 5 2012

District MARION

MARION County WV Department of Environmental Protecti

<u>3968</u> Well No.

). ENNIC

3/14/12

<u>DUNIGAN, DENNIS</u> Farm

STATE INSPECTOR SUPERVISING PLUGGING

AFFIDAVIT

STATE OF WEST VIRGINIA, County of MONONGALIA ss:

<u>DELBERT MOORE</u> and <u>KEVIN S. WRIGHT</u> being first duly sworn according to law depose and say that they are experienced in the work of plugging and filling oil and gas wells and were employed by Consolidation Coal Company well operator, and participated in the work of plugging and filling the above well, that said work was commenced on the 20th day of January, 2011 and that the well was plugged in the following manner:

Sand or Zone Record	Filling Material	Plugs Used	Casing Pulled	Casing Left In
Formation		Size & Kind		
Cleaned 12 ¼" hole fig 7/8" at 231'. Cleane hole to 7 7/8" at 1478' Tagged plug at 1551'. 1087' to 1094'. Left 20 surface. Cement hole from 10 From 1551' to 1220' with the from 1551' to 1220' with the from 914 to surface with the figure of 769 sacks o	om the surface to 231'. Reduced hole to d 9 7/8" hole from 231' to 1478'. Reduced . Cleaned 7 7/8" hole from 1478' to 1551'. Cleaned 9 7/8" hole thru the Pittsburgh Coal 3' of 16" conductor pipe in the hole from 20' to 651 back to surface as follows: with 175 sacks of 35/65 Poz Mix Cement. The 284 sacks of Thixatropic Cement with dye. With 310 sacks of Econofill Cement. If cement were used to cement the hole from ment did circulate at the surface.	16" Conductor	0'	20'
		·		
Coal Seams	<u> </u>	Description of Monur	nent	
Coal Seams	1087' to 1094'	77" of 7" casing w/con	npany name, v	vell number
PITTSBURGH	1087' to 1094'	77" of 7" casing w/con	npany name, vie cemented s	tated on 7"
	1087' to 1094'	77" of 7" casing w/con	npany name, v e cemented s II be attached	tated on 7"

... and that the work of plugging and filling said well was completed on the 3rd day of February, 201

And further deponents saith not.

Keuri S. W.

Sworn to and subscribed before me this

Hth day of March, 2012

Notary Public

Permit No.<u>47-049- 02132- P</u> REVISED Well No. <u>3968</u>

My commission expires:

OFFICIAL SEAL
STATE OF WEST VIRGINIA
NOTARY PUBLIC
Jacqueline L. Shriver.
12 Rousch Drive
Westover, WV 26501
My Commission Exp. March 18, 2020